

HDZY01-----全自动轴承单面注脂机

产品名称	HDZY01-----全自动轴承单面注脂机
公司名称	无锡市惠荣自动化科技有限公司
价格	.00/1
规格参数	品牌:惠荣 型号: HDZY01
公司地址	无锡滨湖区梅园徐巷449号
联系电话	0510-85200718 13961888421

产品详情

HDZY01-----全自动轴承单面注脂机

?????

1? ??????ø15mm-ø40mm???????????

2? ??????????????????????????

3? ??????????????????????????

4? ??

5? ??????????---?????---????????---?????????

6? ??????????7???

?????

1? ??

2? ?????????????????????????????????

3? ?????????????????????????????????

4????????????????????????????????

?????

?????? ø15-ø40mm

???? ?1?/?

???? ??????

???? ???????

?? 220V 50HZ 3A

?? 0.4MPa

???? 600×600×1600

?? ?100KG

????????????????? ????0510-85200718 ????0510-85200728

WuXi HuiRong Automation Technology Co., Ltd. ???www.huirongat.com ???huirongat@163.com

HDZY01 -----

Auto bearing grease injection machine

Major functions?

- 1? Applicable for quick and accurate greasing of bearing with an external diameter of $\varnothing 15\text{mm}-\varnothing 40\text{mm}$.
- 2? Loading plate and machine designed as a whole, reducing transition and increasing efficiency.
- 3? Circumscribed grease supply can provide high pressure oil supply. Precise quantitative valve control single amount of grease infusion
- 4? Quick and convenient in changing model type. Machine is widely used. Deep groove ball bearing, flat bearing, needle bearing ,etc, all can be used.
- 5? Manufacturing procedure: disc feeding--belt transmission--press tightly to fix bearing then grease injection--products being finished.
- 6? Intelligent operating system, 7 inches true color touching screen , parameters and states information display at the same time, easy to operate.

Structural features?

- 1?The machine integrates feeding disc, used as a single, is currently the industry's most efficient model type.
- 2?The model can be changed through adjusting channel width and replacing grease injection control head, very convenient and practical..
- 3?Stepper motor intelligently correct greasing position. grease injection volume can be adjusted through quantitative valve body. Precise amount of grease output.
- 4?All components using best quality configurations to ensure long term working stability of equipments.

Technical parameters?

Applicable range	∅15-∅40mm
Working efficiency	1 seconds for one piece
Bearingloading mode	disc type feeder
Grease injection method	Accurate quantitative grease injection
Power	220V 50Hz 5A
Air source	0.4MPa
External dimensions	1300×600×1600mm
Weight	300kg

???????????????? ????0510-85200718 ????0510-85200728

WuXi HuiRong Automation Technology Co., Ltd. ???www.huirongat.com ???huirongat@163.com