## HZYJ03----全自动中小型轴承注脂压盖机

产品名称	HZYJ03全自动中小型轴承注脂压盖机
公司名称	无锡市惠荣自动化科技有限公司
价格	.00/1
规格参数	品牌:惠荣 型号:HZYJ03
公司地址	无锡滨湖区梅园徐巷449号
联系电话	0510-85200718 13961888421

## 产品详情

HZYJ03-----全自动中小型轴承注脂压盖机

5? ???????????????????????????????????

?????

1? ??????????????????????????

3? ??????????????????????

??????????????????????

4? ??5???????????????????

?????????????????

5????????????NG??????

6??????????????????????

???????

?????

??

	??????	ø62-ø90mm
????		?3?/? (????4?)
????		????????
????		??????
????		?????????
????		????????0.1mm

220V 50HZ 5A

??? 0 .4MPa ???? 1900×800×1750 ?? ?500KG

???????????????????510-85200718 ???0510-85200728

WuXi HuiRong Automation Technology Co., Ltd. ???www.huirongat.com ???huirongat@163.com

HZYJ03-----Auto small and medium sized bearing greasing capping machine

Major functions?

1?Applicable for precise greasing and dust cap press with an external bearing diameter of ø62mm- ø90mm.

2?Plastic cage automatic recognition and flip function; single and double-sided greasing model switch function.

3?Circumscribed grease supply car provide high pressure grease; precise quantitative valve control single amount of grease infusion.

4?Inspect greasing with pervious to light type, electronic weighing scales inspection function can also be equipped according to customer requirements.

5?Manufacturing procedures: test flexibility--grease on the first side(or recognize side)--turn over--grease on the second side--greasing inspection--NG ejection-put cap on the first side(or put plastic cap)--press the first iron cap--gland inspection--turn over--put cap on the second side(or put plastic cap)--press the second iron cap--gland inspection--NG ejection--even distribution of grease --qualified products being finished.

6?Intelligent operating system,7 inches true color touching screen, parameters and states information display at the same time, clear at a glance, easy to operate.

Structuralfeatures?

1?Together with loading plates, the machine can be used separately as well as connecting with automatic production line to produce.

2?Inspect bearing flexibility before greasing, avoiding locked dead or inflows of bearing with bad rotation.

3?Find the greasing position correctly with intelligent marching type; quantitative regulation of high pressure grease quantitative valve ensures the amount of grease accurately consistent.

4?Linear slide rail cover delivery platform, accuracy and smoothness in delivering, no block in cap and adjustable in the gaps between guide mechanism and the platform.

Plastic cover gaskets are also cut more smoothly.

5? Check height of cover with high precision linear potentiometer,

eliminating NG products automatically.

6?All components using best qualityconfigurations to ensure

long term working stability of equipments.

Technical parameters?

Applicable range ø 62-ø90mm

Working efficiency ?3--4 seconds for one piece

Bearingloading mode Automatic line

or loading tray

Greasing inspection Pervious to light type or matching weight

confirmation

Gland inspection linear transducer?

accuracy 0.1 mm

Power 220V 50Hz 5A

Air source 0.4MPa

External dimensions 1900×800×1750mm

Weight 500kg

??????????????????510-85200718 ???0510-85200728

WuXi HuiRong Automation Technology Co., Ltd. ???www.huirongat.com ???huirongat@163.com