

HSLZY01/02-全自动双列轴承注脂压盖机

产品名称	HSLZY01/02-全自动双列轴承注脂压盖机
公司名称	无锡市惠荣自动化科技有限公司
价格	.00/1
规格参数	品牌:惠荣 型号:HSLZY01/02
公司地址	无锡滨湖区梅园徐巷449号
联系电话	0510-85200718 13961888421

产品详情

HSLZY01/02-----全自动双列轴承注脂压盖机

?????

1? ??????ø22mm-ø62mm?????????????????

2? ???

3? ??????????????OK?????????????????

4? ??????????????????????????????????????

5? ??????????????????????????OK?NG?

6? ??????????????????---?????---?????---??---?????---?????---NG???---?????????---?????---?????????---?????---
--NG???---??---???????

7? ??????????7?????????????????????????????????????

?????

1? ?????????????????????

2? ???

3? ?????????????????????10mg?????

4? ?????????????????????????????????

????????????????

5? ?????????????????NG??????

6? ?????????????????????????????

????????????

?????

???? HSLZY01 ø22-ø40mm

???? HSLZY02 ø40-ø62mm

???? ?3.5-4?/?

???? ????????????

???? ????????????

?? 220V 50HZ 3A

?? 0.4MPa

???? 1800×700×1750

?? ?400KG

????????????????? ????0510-85200718 ????0510-85200728

WuXi HuiRong Automation Technology Co., Ltd. ???www.huirongat.com ???huirongat@163.com

HSLZY01/02 -----

Auto double-row bearing greasing capping machine

Major functions?

1? Applicable for double-row bearing's greasing and sealed cap press with an external bearing diameter of $\varnothing 22\text{mm}-\varnothing 62\text{mm}$.

2? Respective greasing on both sides, greasing from the side of cages, precise quantitative valve control the single volume of greasing.

3? Weighing method before and after to determine whether greasing is OK or not, bearings without steel balls can also be tested out.

4? Press sealed caps in double sides, flexible gland head design, Flat press in without any flange.

5? Height check function after gland, determine OK or NG according to the setted tolerance.

6? Manufacturing procedures?Check the front weight--- grease on the first side ---- turn over --- grease on the second side ---Check the weight back---NG ejection--- first side put plastic cap ---cap inspection---second side put plastic cap --- cap inspection ---NG ejection --- even distribution of grease ---qualified products being finished?

7? Intelligent operating system, 7 inches true color touching screen , parameters and states information display at the same time, easy to operate.

Structuralfeatures?

1?Single use and auto manufacture after being connected with pre-project are acceptable.

2?Specially designed high pressure and multi pointed greasing structure according to the small gap characteristics between double row bearing, leading to smooth greasing into bearing tracks.

3?Test weight respectively before and after greasing, 10mg weighing accuracy.

4?Specially designed flexible gland methods according to the double-row sealed cap characteristics, Flat press in without any flange.

5?linear transducer testing gland height, automatic elimination of NG product.

6?All components using best quality configurations to ensure long term

working stability of equipments.

Technical parameters?

Applicable range HSLZY01 \varnothing 22- \varnothing 40mm

HSLZY02 \varnothing 40- \varnothing 62mm

Working efficiency 3.5-4 seconds for one piece

Bearingloading mode loading plates provision;

attachment production

greasing methods high pressure injection,

quantitative greasing

Power 220V 50Hz 5A

Air source 0.4MPa

External dimensions 1800×700×1750mm

Weight 450kg

????????????????? ???0510-85200718 ???0510-85200728

WuXi HuiRong Automation Technology Co., Ltd. ???www.huirongat.com ???huirongat@163.com