

合力3吨叉车电瓶批发-合力叉车3吨蓄电池多少钱？

产品名称	合力3吨叉车电瓶批发-合力叉车3吨蓄电池多少钱？
公司名称	广州贝朗斯动力电源有限公司
价格	30500.00/组
规格参数	品牌:MACI,火炬,迅启,FAAM,GS,Hoppecke,Hawker,KOBE,Hitachi,天能 型号:40-4PZS480 合力电瓶:80V/4PZS480
公司地址	中国 广东 广州 白云区 夏花二路28号
联系电话	86 020 86603123 13538843060

产品详情

合力3吨叉车蓄电池是一款80V480Ah、4PZS480牵引动力蓄电池，HELI铁箱尺寸：1028X711X784mm，配套叉车电瓶可选：日本GS、意大利FAAM、贝朗斯、迅启、天能、火炬等叉车蓄电池品牌。更换合力电瓶叉车电瓶哪个牌子好呢？不同牌子的合力蓄电池价格不一样，使用设计寿命也存在差距，合力CPD30电动叉车专用蓄电池一般哪些地方有得购买？可选广州贝朗斯动力电源有限公司作为供应商，服务周到，售后响应快捷，报价实惠。目前市面叉车电瓶品牌很多，但让人放心的没多少个，专业程度、诚信度不够，商业心太重，消费者购买合力叉车电瓶的时候必须留个心眼，避免造成损失，广州贝朗斯公司是合力蓄电池公司授权代理商，负责国内合力电瓶叉车蓄电池的线上、线下销售，全国实行联保，快捷上门安装。[合力电瓶叉车蓄电池批发价](http://www.goepe.com/apollo/prodetail-berens-7020675.html)一般面向叉车维修店、叉车配件店、机电物资公司、汽修配件店执行，广州贝朗斯公司合力车型常用蓄电池备件一般有现货，当天可发出，合力叉车电瓶属于哪种类型？按材质分是铅酸蓄电池系列，铅在硫酸溶液中的阳极氧化，在一定条件下发生钝化，结果导致输出容量的降低，降低的程度依赖于放电时的温度、硫酸的浓度以及放电的电流密度。由于钝化机理的作用，蓄电池的放电输出电压和容量受放电电流大小的影响。对于同样的完全充电的电池，在相同的温度下，采用不同倍率的放电电流，其放电输出电压幅值有很大的差别。根据不同使用需要所设计的蓄电池的输出曲线会有差别，起动使用的蓄电池一般设计工作在低倍率，大多为0.05C，其输出容量与电流的变化关系不大。电动叉车电池一般是中低倍率放电，其电池往往只维持3个小时甚至更短，电池工作在0.5C倍率附近，而且负载的功率范围随机性很大，由于高倍率下的以钝化为主的电池内部反应的存在，使得高倍率下的输出容量出现严重的非线性。

[叉车电池 HELI叉车蓄电池](http://www.berens-power.com)在合金中加入固溶体或合金中加入，以阻挡战小的相上浮或密度大的能有效地防止：微偏析。显微偏析盼她状偏析枝晶偏析和晶界偏析种胞状偏析前已指出当成分过冷度较小时固溶体晶体呈照状方式生成。如果合全状偏析枝晶偏析。如前所述，枝晶偏析是由非平衡凝固造成的，这使先凝固的枝干和后凝固的枝桐的成分不均匀。合金通常以树枝状生长，一棵树枝晶就形成一颗晶粒，因此枝晶偏析内偏德山理。偏析元素在固溶体中的扩散能力越小，则晶内偏析越大；在个晶粒范围内，故也称为晶内偏析影响枝晶偏析程度的主要因素有凝固速度越大，晶内偏析也越军，凝固温度范围越宽。

我们可以用电池容量温度系数的概念来表征温度的影响。容量的温度系数即温度每下降1时，容量相对于25时下降的百分数。温度的影响在高速率放电制下尤为明显。Force 3 ton forklift battery is a 80V480Ah and 4PZS480 traction power battery, HELI iron box size: 1028X711X784mm, forklift battery supporting optional: Japan GS, Italy FAAM, Bei Xunqi, lens, day, torch brand forklift battery etc.. Replacement battery forklift battery which brand is good? Different brands of battery prices are not the same, there is a gap in the use of design life, joint CPD30 electric forklift batteries which are generally have to buy? Optional lens power Co. Ltd. Guangzhou Bei as a supplier, customer service and thoughtful service, quick response, affordable price. At present the market a lot of forklift battery brand, but not much reassuring, professionalism, integrity is not enough, the commercial heart is too heavy, when consumers buy Heli forklift battery must stay in mind, to avoid losses, Guangzhou Bei rance company is authorized agents force battery company, in charge of domestic battery forklift battery line force and sales of the line, the national implementation of UNPROFOR, fast door installation. Heli forklift battery battery general wholesale price for forklift repair shop, forklift accessories shop, mechanical and electrical supplies, automotive accessories shop, Guangzhou Bei Langsi Heli battery models commonly used spare parts generally spot, the day can be issued, which belongs to the type of forklift battery? According to the material is a series of lead-acid batteries, lead anodic oxidation in sulfuric acid solution, passivation occurs under certain conditions, resulting in reduced output capacity, temperature, sulfuric acid reduced dependence on the degree of the discharge concentration and discharge current density. The output voltage and capacity of the battery are affected by the discharge current. For the same fully charged battery, at the same temperature, the output voltage amplitude is very different with the discharge current of different magnification. According to the different needs of the design of the output curve of the battery will be different, the start use of the general design of the battery at low magnification, mostly 0.05C, and its output capacity and current changes little. Electric forklift battery is low rate discharge, the battery is only maintained for 3 hours or less, the battery at 0.5C rate and power range near the load random greatly due to the passivation mainly inside the battery reaction under a high magnification of the presence of the output of the high rate capacity under severe nonlinear. HELI forklift battery in the alloy adding solid solution alloy or join the body to stop the war, small phase floating or high density can effectively prevent the micro segregation. Segregation for her segregation dendrite segregation and grain boundary segregation for cellular segregation has pointed out that as a small degree of supercooling solid solution crystal according to the form of a generation. If the segregation of dendrite segregation. As mentioned earlier, dendrite segregation is caused by non-equilibrium solidification, the solidification solidified stems and branches after Tong uneven components. Usually by dendritic growth of alloy, a dendrite formation of a dendrite segregation in grain, therefore Deshanli. Partial segregation elements in solid solution diffusion ability in the body of the smaller, while crystal segregation is higher; in a grain size range, it is also known as the effect of segregation factors of dendrite segregation degree of solidification velocity increasing, crystal segregation is in the solidification temperature range is wide. We can use the concept of the battery temperature coefficient to characterize the effect of temperature. The temperature coefficient of the capacity is the percentage of the volume falling at 25 DEG C when the temperature drops to about 1 degrees centigrade. The effect of temperature is especially obvious in the high rate discharge system.

合力电动叉车蓄电池部分电瓶型号表

合力蓄电池型号		额定电压		(V)			
5hr额定容量	(Ah)	***大外形尺寸(mm)					
极柱数量	容器材料	本厂型号					
标准型号		长	宽				
槽高	总高(焊)			总高(活)			
2PzS120	D-120-K2	2	120	47			
198	360	395	405	2	PP		
3PzS180	D-180-K3	2	180	65			
198	360	395	405	2	PP		
4PzS240	D-240-K4	2	240	83			
198	360	395	405	2	PP		
5PzS300	D-300-K5	2	300	101			
198	360	395	405	2	PP		
6PzS360	D-360-K6	2	360	119			
198	360	395	405	2	PP		

7PzS420	D-420-K7	2	420	137
198	360	395	405	2 PP
8PzS480	D-480-K8	2	480	155
198	360	395	405	2or4 PP
9PzS540	D-540-K9	2	540	173
198	360	395	405	2or4 PP
10PzS600	D-600-K10	2	600	191
198	360	395	405	2or4 PP
2PzS140	D-140-K2	2	140	47
198	405	440	450	2 PP
3PzS210	D-210-K3	2	210	65
198	405	440	450	2 PP
4PzS280	D-280-K4	2	280	83
198	405	440	450	2 PP
5PzS350	D-350-K5	2	350	101
198	405	440	450	2 PP
6PzS420	D-420-K6	2	420	119
198	405	440	450	2 PP
7PzS490	D-490-K7	2	490	137
198	405	440	450	2 PP
8PzS560	D-560-K8	2	560	155
198	405	440	450	2or4 PP
9PzS630	D-630-K9	2	630	173
198	405	440	450	2or4 PP
10PzS700	D-700-K10	2	700	191
198	405	440	450	2or4 PP
2PzS160	D-160-K2	2	160	47
198	456	491	501	2 PP
3PzS240	D-240-K3	2	240	65
198	456	491	501	2 PP
4PzS320	D-320-K4	2	320	83
198	456	491	501	2 PP
5PzS400	D-400-K5	2	400	101
198	456	491	501	2 PP
6PzS480	D-480-K6	2	480	119
198	456	491	501	2 PP
7PzS560	D-560-K7	2	560	137
198	456	491	501	2 PP
8PzS640	D-640-K8	2	640	155
198	456	491	501	2or4 PP
9PzS720	D-720-K9	2	720	173
198	456	491	501	2or4 PP
10PzS800	D-800-K10	2	800	191
198	456	491	501	2or4 PP
2PzS180	D-180-K2	2	180	47
198	525	560	570	2 PP
3PzS270	D-270-K3	2	270	65
198	525	560	570	2 PP
4PzS360	D-360-K4	2	360	83
198	525	560	570	2 PP
5PzS450	D-450-K5	2	450	101

198	525	560	570	2	PP
6PzS540		D-540-K6	2	540	119
198	525	560	570	2	PP
7PzS630		D-630-K7	2	630	137
198	525	560	570	2	PP
8PzS720		D-720-K8	2	720	155
198	525	560	570	2or4	PP
9PzS810		D-810-K9	2	810	173
198	525	560	570	2or4	PP
10PzS900		D-900-K10	2	900	191
198	525	560	570	2or4	PP
2PzS200		D-200-K2	2	200	47
198	570	605	615	2	PP
3PzS300		D-300-K3	2	300	65
198	570	605	615	2	PP
4PzS400		D-400-K4	2	400	83
198	570	605	615	2	PP
5PzS500		D-500-K5	2	500	101
198	570	605	615	2	PP
6PzS600		D-600-K6	2	600	119
198	570	605	615	2	PP
7PzS700		D-700-K7	2	700	137
198	570	605	615	2	PP
8PzS800		D-800-K8	2	800	155
198	570	605	615	2or4	PP
9PzS900		D-900-K9	2	900	173
198	570	605	615	2or4	PP
10PzS1000		D-1000-K10	2	1000	191
198	570	605	615	2or4	PP
2PzS240		D-240-K2	2	240	47
198	690	725	735	2	PP
3PzS360		D-360-K3	2	360	65
198	690	725	735	2	PP
4PzS480		D-480-K4	2	480	83
198	690	725	735	2	PP
5PzS600		D-600-K5	2	600	101
198	690	725	735	2	PP
6PzS720		D-720-K6	2	720	119
198	690	725	735	2	PP
7PzS840		D-840-K7	2	840	137
198	690	725	735	2	PP
8PzS960		D-960-K8	2	960	155
198	690	725	735	2or4	PP
9PzS1080		D-1080-K9	2	1080	173
198	690	725	735	2or4	PP
10PzS1200		D-1200-K10	2	1200	191
198	690	725	735	2or4	PP
2PzS280		D-280-K2	2	280	47
198	720	755	765	2	PP
3PzS420		D-420-K3	2	420	65
198	720	755	765	2	PP

4PzS560	D-560-K4	2	560	83
198	720	755	765	2 PP
5PzS700	D-700-K5	2	700	101
198	720	755	765	2 PP
6PzS840	D-840-K6	2	840	119
198	720	755	765	2 PP
7PzS980	D-980-K7	2	980	137
198	720	755	765	2 PP
8PzS1120	D-1120-K8	2	1120	155
198	720	755	765	2or4 PP
9PzS1260	D-1260-K9	2	1260	173
198	720	755	765	2or4 PP
10PzS1400	D-1400-K10	2	1400	191
198	720	755	765	2or4 PP

产品特点及主要用途：为替代进口，我公司研制了符合德国DIN标准要求的PzS系列牵引用铅酸蓄电池。为国内进口叉车和牵引车配套，也可用于其它电动牵引车辆。本产品还可用于出口。