

隔爆型电动闸阀Z941H-16C

产品名称	隔爆型电动闸阀Z941H-16C
公司名称	江苏博纳阀门有限公司
价格	4500.00/个
规格参数	品牌:博纳 型号:Z941H-16C 产地:常州
公司地址	常州市天宁区青龙桐家工业园
联系电话	0519-85504455 13951223144

产品详情

一、产品概述：

隔爆型电动闸阀Z941H-16C简单地说就是用电动执行器控制阀门，从而实现阀门的开和关。其可分为上下两部分，上半部分为电动执行器，下半部分为铬钼钢闸阀。电动闸阀使用电能作为动力由直行程的电动执行机构驱动阀门，实现阀门的开关、调节动作。从而达到对管道介质的开关或是调节目的。电动法兰闸阀配有转矩控制机构、现场操作机构和手、电动切换机构。除就地操作外，还可以进行远距离操作、PLC控制、4~20mA电流输入输出智能控制等。

二、隔爆型电动闸阀制造标准：

设计规范：GB/T 12234

结构长度：GB/T 12221

连接法兰：JB/T 79

试验与检验：JB/T 9092

压力-温度：GB/T 9131

产品标识：GB/T 12220

三、隔爆型电动闸阀（Z941H）主要零部件材质

阀体/阀盖	ZG1Cr18Ni9Ti	ZG00Cr18Ni10	ZG1Cr18Ni12M02Ti	ZG00Cr17Ni14M02	WCB
零件名称	ZG1Cr18Ni9Ti	ZG00Cr18Ni10	ZG1Cr18Ni12M02Ti	ZG00Cr17Ni14M02	WCB系列
闸板	ZG1Cr18Ni9Ti	ZG00Cr18Ni10	ZG1Cr18Ni12M02Ti	ZG00Cr17Ni14M02	1Cr13
阀杆	1Cr18Ni9Ti	00Cr18Ni10	1Cr18Ni12M02Ti	00Cr17Ni14M02	1Cr13
填料	PTFE编织	PTFE编织	PTFE编织	PTFE编织	石墨
垫片	304L + PTFE	304L + PTFE	316 + PTFE	316L + PTFE	石墨
压盖	ZG1Cr18Ni9Ti	ZG00Cr18Ni10	ZG1Cr18Ni12M02Ti	ZG00Cr17Ni14M02	WCB
填料压环	1Cr18Ni9Ti	00Cr18Ni10	1Cr18Ni12M02Ti	00Cr17Ni14M02	1Cr13
螺栓	1Cr17Ni2	1Cr17Ni2	1Cr17Ni2	1Cr17Ni2	35CrMoA
螺母	1Cr18Ni9Ti	1Cr18Ni9Ti	1Cr18Ni9Ti	1Cr18Ni9Ti	45

四、隔爆型电动闸阀主要连接尺寸

		Z941H-16C																		
寸	DN	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350	400	450	500	600
L	mm	130	150	160	180	200	250	265	280	300	325	350	400	450	500	550	600	650	700	800
H	mm	175	180	210	210	350	358	373	435	500	614	674	818	1225	1415	1630	1780	2050	2181	2400
W	mm	180	180	200	200	200	240	240	280	320	360	360	400	450	500	500	600	720	720	720

（如需提供隔爆型电动闸阀Z941H-16C性能参数、结构尺寸参数、价格等详情，请联系我们的销售、技术工程师，电话：0519-85504455/13951223144黄工-江苏博纳阀门厂。）