

HP RX2800i4小型机报价现货

产品名称	HP RX2800i4小型机报价现货
公司名称	北京中盛广信息技术有限公司
价格	45000.00/台
规格参数	品牌:HP 型号:RX2800i4 产地:美国
公司地址	北京市大兴区西红门镇宏旭路1号15101013227
联系电话	15101013227

产品详情

HP RX2800i4小型机报价现货哪里有

联系电话:小李15101013227 QQ : 2537338435

整机信息

品牌 HP

类型 小型机

CPU信息 1 到 4 个 Intel Itanium 2 处理器，时钟频率为 1.3GHz 或 1.5GHz。一级缓存 32KB;二级缓存 256KB；三级缓存 6MB (1.5GHz)或 3MB (1.3GHz)。

CPU类型 安腾2

CPU插槽数 2

CPU激活

机架类型 机架式

机架空间 7U

硬盘信息 内置HDD驱动器托架 4 个；最大存储容量 438GB；Ultra320SCSI 36GB 73GB 146GB。

最大硬盘数量 4

内存提示 有 48 个DIMM插，两个 24 插槽扩展。RAM类型PC2100ECC Registered，DDR266A SDRAM。

支持内存容量范围 最大内存容量 96G

内存插槽数量 48

内存是否需要激活

电源描述 输入电流 100V~10A,200V~5A (每条线路);线路频率 50-60Hz;最大输入功率 2089W;最大输出功率 930W。

单机电源数量 3

介质托架 1 个开放式托架，用于DVD-ROM或DDS

适配器插槽 PCI-X插槽 9 个(3x133 MHz, 6x66MHz)；PCI插槽 1 个(33 MHz)

端口 10/100/1000BT LAN;10/100BT管理LAN；3xRS-232串行端口;VGA (可选)；2 个USB接口(可选)。

IO适配器 Ultra160 SCSI网卡

IO扩展

发布日期

下架日期

服务截止期

操作系统 HP-UX 11i v2；Microsoft Windows Server 2003企业版；Linux。

产品尺寸 高度311毫米/12.25英寸/7U EIA；宽度482毫米/19英寸；深度774毫米/30.5英寸。

产品重量 72.6千克/160磅

配件信息

FC号 PN号 描述

CPU

A6695-69005

Processor (extender) board - Has four processor sockets - Plugs into the system baseboard

A6820-69101

Intel Itanium 2 processor - 900MHz (McKinley, 400MHz front side bus, 1.5MB Level-3 cache)

A6820A

Intel Itanium 2 processor upgrade - Includes one 900MHz (200MHz front side bus, 1.5MB cache)processor

A6836A

Intel Itanium 2 processor upgrade - Includes one 1.0GHz (200MHz front side bus, 3MB cache) processor

A9809-69001

Intel Itanium 2 processor - 1.00GHz (McKinley, 400MHz front side bus, 3.0MB Level-3 cache)

A9810-69001

Intel Itanium 2 processor - 1.5GHz (McKinley, 400MHz front side bus, 3.0MB Level-3 cache)

系统板

A6695-69306

System baseboard - Has slots and connections for processor boards, memory boards, and other boards

A6869-67501

VGA video/USB core I/O PCI board - Has one video connector and two USB connectors

A6875A

Management processor board - For controlling the system console, reset and power management functions - Includes SIO (remote, console and UPS), VGA and LAN connectors - NOT supported in tower configurations

内存

A6746A

2.0GB DDR-SDRAM memory upgrade kit - Includes four 512MB, 266MHz, PC2100, non-ECC DDR-SDRAM DIMM memory modules

A6833A

1.0GB DDR-SDRAM memory upgrade kit - Includes four 256MB, 266MHz, PC2100, non-ECC DDR-SDRAM DIMM memory modules

A6834-69001

1.0GB, 266MHz, PC2100, non-ECC DDR-SDRAM DIMM memory module

A6834A

4.0GB DDR-SDRAM memory upgrade kit - Includes four 1.0GB, 266MHz, PC2100, non-ECC DDR-SDRAM DIMM memory modules

A6967AX

256MB, 266MHz, PC2100, non-ECC DDR-SDRAM DIMM memory module

A6968AX

512MB, 266MHz, PC2100, non-ECC DDR-SDRAM DIMM memory module

硬盘

A5558A

12GB/24GB Single-Ended SCSI-2 DDS-3 (DAT) tape drive - 5.25in form factor

A6091A

HP 73GB hot-plug Ultra2 SCSI hard drive - 10,000 RPM, low profile

A6091AR

HP 73GB hot-plug Ultra2 SCSI hard drive - 10,000 RPM, low profile

A6276-69002

73.4GB hot-swap Ultra-2 LVD SCSI hard drive module - 10,000 RPM, low profile

A6736-69002

18GB hot-plug Ultra160 Wide Low Voltage Differential (LVD) SCSI hard drive - 10,000 RPM, low profile, 80-pin SCA connector

A6736A

18GB hot-plug Ultra160 Wide Low Voltage Differential (LVD) SCSI hard drive - 10,000 RPM, low profile, 80-pin SCA connector

A6736AR

18GB hot-plug Ultra160 Wide Low Voltage Differential (LVD) SCSI hard drive - 10,000 RPM, low profile, 80-pin SCA connector

A6737-69002

36GB hot-plug Ultra160 Wide Low Voltage Differential (LVD) SCSI hard drive - 10,000 RPM, low profile, 80-pin SCA connector

A6737A

36GB hot-plug Ultra160 Wide Low Voltage Differential (LVD) SCSI hard drive - 10,000 RPM, low profile, 80-pin SCA connector

A6737AR

36GB hot-plug Ultra160 Wide Low Voltage Differential (LVD) SCSI hard drive - 10,000 RPM, low profile, 80-pin SCA connector

A6738-69002

73GB hot-plug Ultra160 Wide Low Voltage Differential (LVD) SCSI hard drive - 10,000 RPM, low profile, 80-pin SCA

A6738A

73GB hot-plug Ultra160 Low Voltage Differential (LVD) SCSI hard drive - 10,000 RPM, low profile, 80-pin SCA connector

A6738AR

73GB hot-plug Ultra160 Low Voltage Differential (LVD) SCSI hard drive - 10,000 RPM, low profile, 80-pin SCA connector

A6845-69002

18GB hot-plug Ultra160 Wide Low Voltage Differential (LVD) SCSI hard drive - 15,000 RPM, low profile, 80-pin SCA connector

A6845A

18GB hot-plug Ultra160 Wide Low Voltage Differential (LVD) SCSI hard drive - 15,000 RPM, low profile, 80-pin SCA connector

A6845AR

18GB hot-plug Ultra160 Wide Low Voltage Differential (LVD) SCSI hard drive - 15,000 RPM, low profile, 80-pin SCA connector

A6846-69002

36GB hot-plug Ultra160 Wide Low Voltage Differential (LVD) SCSI hard drive - 15,000 RPM, low profile, 80-pin SCA connector

A6846A

36GB hot-plug Ultra160 Wide Low Voltage Differential (LVD) SCSI hard drive - 15,000 RPM, low profile, 80-pin SCA connector

A6846AR

36GB hot-plug Ultra160 Wide Low Voltage Differential (LVD) SCSI hard drive - 15,000 RPM, low profile, 80-pin SCA connector

A7051A

73GB hot-plug Ultra160 Wide Low Voltage Differential (LVD) SCSI hard drive - 10,000 RPM, low profile, 80-pin

SCA connector

A7051AR

73GB hot-plug Ultra160 Wide Low Voltage Differential (LVD) SCSI hard drive - 10,000 RPM, low profile,80-pin SCA connector

RAID卡

P3475B

NetRAID-2m dual channel disk array controller with 128MB cache - PCI board with two internal 68-pin high density and four external 68-pin very high density Ultra3 SCSI connectors

SCSI卡

A5159A

Dual port PCI Fast Wide High Voltage Differential SCSI-3 adapter - Has two external very high density 68-pin connectors and two internal high density 68-pin connectors - For HP-UX operating system

A6828A

Single channel Ultra160 LVD SCSI adapter board - Compliant with SCSI SPI-3, supports up to 15 devices - Has one 68-pin very high density external connector, and one 68-pin high density internal connector - For HP-UX operating system

A6828AR

Single channel Ultra160 LVD SCSI adapter board - Compliant with SCSI SPI-3, supports up to 15 devices - Has one 68-pin very high density external connector, and one 68-pin high density internal connector - For HP-UX operating system

A6829A/A6829-60101

Dual channel Ultra160 LVD SCSI adapter board - Compliant with SCSI SPI-3, supports up to 30 devices - Has two 68-pin very high density external connectors, and two 68-pin high density internal connectors - For HP-UX operating system

A6829AR

Dual channel Ultra160 LVD SCSI adapter board - Compliant with SCSI SPI-3, supports up to 30 devices - Has two 68-pin very high density external connectors, and two 68-pin high density internal connectors - For HP-UX operating system

网卡

A5506B

100Base-TX LAN four port host adapter board (Supports all PCI bus configurations) - Has four RJ-45 connectors - Require one 64-bit PCI slot - For HP-UX operating system - LAN Adapter - 4 port 100Base-TX PCI LAN adapter -

Has four RJ-45 ports - Supports al

A6847A

1000Base-SX Gigabit Ethernet network interface adapter board - Has one duplex fiber optic connector, requires one 64-bit PCI slot - For HP-UX operating system

A8084A

FireWire (IEEE-1394A) adapter - 3-port

A8685A

1000Base-T Gigabit Ethernet network interface adapter board - Has one RJ-45 connector - Requires one PCI slot - For HP-UX operating system

B5509BA

100Base-TX LAN host adapter board with one RJ-45 port - Requires one PCI slot - Includes the board, software, software license, and installation instructions - For HP-UX operating system

P3492A

10/100Base-T IPSec (3DES) LAN host adapter board - With one RJ-45 connector - Requires one PCI slot - For Windows and Linux operating systems

显卡

A6869A

HP Graphics USB Card (rx5670) - VGA video/USB core I/O PCI board - Has one video connector and two USB connectors

电源

A5527-69001

Hot-swap redundant power supply - 100/240VAC input, 50/60Hz, autoswitching

光驱

A5557A

Narrow Single-Ended SCSI-2 slot load DVD-ROM drive - 6X DVD-ROM read, 32X CD-ROM read (Pioneer DVD-303/304) - Has headphone jack and volume control

磁带机

C1537-69202

12GB/24GB Single-Ended SCSI-2 DDS-3 (DAT) tape drive - 5.25-inch form factor - (part of A3542A, A4249A)

风扇

A5191-04003

172mm I/O card cage `hot swap` fan

A5191-67006

`Hot swap` fan for the power converter

A6695-04006

172mm `hot swap` chassis fan

线缆

8120-1378

Power cord (Jade Gray) - 18 AWG, 2.3m (7.5ft) long - Has straight (F) C13 receptacle (for 120V in USA, Canada, Latin America, Korea, Taiwan, Thailand, Spain, Brazil, and Vietnam)

A5191-63002

Drive power cable - 4-pin (F) connector to 4-pin (F) connector - 8.5cm (3.3in) long - From DVD-ROM/DDS drive to drive/media backplane

A5191-63003

Power cable - 10-pin (F) connector to 10-pin (F) connector - 11.4cm (4.5in) long - From PCI I/O backplane to drive/media backplane

A5191-63004

Data cable - Has 10-pin (F) connectors - From PCI I/O backplane to disk/media backplane

A5191-63006

SCSI ribbon cable - One 68-pin (M) connector on each end - 39.6cm (15.6in) long - SCSI bus-B - From 4-port SCSI card to drive/media backplane

A5191-63009

Power cable assembly - Large 6-pin (F) connector to small 6-pin (F) connector - 8.3cm (3.3in) long - For the rear chassis fan

A5191-63010

Power cable assembly - Large 6-pin (F) connector to small 6-pin (F) connector - 20.2cm (8.0in) long - For the front chassis fan

A5191-63011

Ribbon cable - Has two 10-pin (F) connectors - 54cm (21.3in) long - From system board to display board

A5191-63013

Drive power cable - Has two 4-pin (F) connectors - 13.5cm (5.3in) long - From DDS drive to disk/media backplane

A5220-67003

Narrow Single-Ended SCSI-2 slot load DVD-ROM drive - 6X DVD-ROM read, 32X CD-ROM read (Pioneer DVD-303/304) - Has headphone jack and volume control

A6144-63005

Power harness cable kit - Includes cable and hardware

A6695-63001

SCSI ribbon cable - One 68-pin (M) connector on each end - Bus A inner SCSI cable

A6695-63002

Outer removable media SCSI ribbon cable - One 68-pin (M) connector on each end

A6695-63004

Chassis intrusion switch cable

A6695-63007

NetRAID SCSI cable - Has one Very High Density 68-pin SCSI connector at each end

A6695-63008

NetRAID board SCSI ribbon cable - For channel 1

A6695-63009

SCSI ribbon cable - From DDS drive to disk media backplane

A6695-63010

SCSI ribbon cable - One 50-pin (M) connector on each end

A7003A

NetRaid board SCSI cables kit - Includes channel 0 and 1 cables

机壳

A5191-04013

Front bezel assembly - Mounts on the front of the server - Requires bezel hardware kit

A6695-04011

Top cover

其它

5001-7430

Empty I/O slot cover

5040-6317

Chassis intrusion switch

A3639-04024

PCI card separator/extractor with light pipe

A5191-60013

Display board - Has on/off switch and five server status LEDs

A5191-67104

Disk/media backplane - Has power and SCSI connectors for removable media mass storage devices on one side and four SCA connectors for hot-plug hard drives on the other side

A5191-69105

Power converter - Converts the input voltage 100/240V to power that can be used by the power supplies - Has three power cord input plugs

A5236-40024

Disk filler panel - Fills an empty drive module slot

A6695-00023

Rear I/O card guide

A6695-00024

Rear chassis brace

A6695-00025

Front I/O card guide

A6695-00026

Shuttle plate

A6695-00054

Memory extender slot filler - Fills an empty memory extender slot

A6695-69004

PCI card backplane - Has 12 PCI slots

A6695-69101

MP/SCSI core I/O PCI board

A6747-69101

Memory extender (carrier) board - Has 20 DIMM slots

A6747A

Memory extender (carrier) board - Has 20 DIMM slots

A6794-69001

LAN/SCSI core I/O PCI board (Procurium)