

FEATURES

????????????????

????????????

????????????????????????????

????????????????????

Product model and Technical data

型号	HEP	单动作型执行机构用	For spring return type
	15	耐压防爆型dExdIIBT6	Explosion proof type
	16	本质安全型iExialICT6	Intrinsically safe explosion proof type
结构Enclosure	17	室外防水型e ExelIT6	Weather proof type

Technical performance

输入信号Input signal	4 ~ 20 mA DC可进行分程控制调整范围4 ~ 12 , 1 adjustment.Adjustable range: 4 ~ 12, 12 ~ 20 mA DC.	The split range is possible by span adjustment and zero	
输入阻抗Input impedance	250 ± 10	气源压力Air supply	140 ~ 160 KPa, 120 ~ 160 KPa
耗气量Air consumption	单动作型	Single acting type : 5NI / min at 140 KPa air supply	

重复精度 Repeatability-----	-0.2% F.S	
电气接口 Wiring connection		Rc 1/2
单动作型执行机构 For single action actuator		IP65
环境温度 Ambient temperature	-40 ~ 80	防护等级 Protection
外壳材料 Housing material	合金 Alloy	表面涂层 Coating-----
		± 1.0% F.S
重量 Approx. weight	回差 Hysteresis-----	喷塑 Epoxy resin group paint
	灵敏度 Response level-----	
		-0.1% F.S

????????????????????

????????????????????0512-52346722????0512-52346722????