HP C3000工作站原装正品质量保证

产品名称	HP C3000工作站原装正品质量保证
公司名称	北京中盛广信息技术有限公司
价格	35.00/台
规格参数	品牌:HP 型号:C3000 产地:美国
公司地址	北京市大兴区西红门镇宏旭路1号15101013227
联系电话	15101013227

产品详情

HP C3000工作站原装正品质量保证

本店承诺

1.品质保证

本店有线下实体公司经营数十年,所有整机备件100%保证正品,原厂原标。

2.售后服务

本店所有售出整机及备件,免费保修一年。

我们有数名专业的HP IBM SUN系统工程师为您提供联机调试,故障排除,备件更换服务。

3.北京市内12小时内上门服务,北京以外地区24小时内提供上门服务。

4.测试报告

本店所有产品均通过测试平台联机测试,并可根据用户要求出具测试报告,品质更有保障。

整机配置

HPC3000HP Visualize C3000 400MHZ CPU/512M/18G

A4986-66510HP C3000主板

0950-2877HP9000Power Supply 500W for C3000,C3600,C3750 A3863-66501HP 512MB 120MHZ SDRAM DIMM (Memory) A4982-66501HP 9000 A4982B Visualize fxe A4982-66501 PCI显卡 其他 Processor, Operating System and Memory Operating System Installed HP-UX 10.2 ACE 9912 HP-UX 11.0 ACE 9911 Processor 400 MHz PA-8500 processor with 1.5 MB cache processor speed 400 MHz Maximum Memory 8 GB Memory slots 8 memory slots Internal drives Internal Hard Disk Drive 9Gb, 18Gb, and 36Gb 32X CD-ROM Optional Floppy Disk Drive System features External I/O Ports RJ45 10/100 BaseTx Ethernet NSE SCSI 50-pin in high-density external port

Ultra2 SCSI LVD 68-pin in high-density external port
Two Serial (RS-232) ports
Two USB (Universal Serial Bus) ports (keyboard and Mouse only)
One Parallel (IEEE 1284) port
Four Audio ports (Line In, Line Out, Microphone In, and Headphones Out)
Keyboard
USB
Option I/O Slots (6 total)
Two PCI 1X (half card) 2 slots
Three PCI 2X (full size)
One PCI 4X (full size)
Network interface
10/100 BaseTx
Dimensions (w x d x h)
9" x 25.8" x 17.5"
Chassis Type
Deskmount
Warranty Standard Statement
Three year for end users
Workstation Bill of Materials (A4986A)
Drives
9.1GB Ultra2 Wide SCSI LVD hard drive - 10,000 RPM, 3.5-inch form factor, 1.0-inch high, 80-pin SCA connector (Seagate Cheetah, model ST39102LC)Get Price
9.1GB Ultra2 Wide SCSI LVD hard drive - 7,200 RPM, 3.5-inch form factor, 1.0-inch high, and 80-pin SCA connector (Quantum Atlas V, 3.5 series)Get Price
18GB Ultra2 Wide SCSI LVD hard drive - 10,000 RPM, 3.5-inch form factor, 1.0-inch high, 80-pin SCA connector

(Seagate Cheetah, model ST318203LC)Get Price

36.4GB Ultra2 Wide SCSI LVD hard drive - 10,000 RPM, 3.5-inch form factor, 1.0-inch high, 80-pin SCA connector (Seagate Cheetah, model ST336704LC)Get Price

Single Connector Attach (SCA) hard disk drive mounting bracket - Allows mounting of removable hard drives in the drive bayGet Price

CD-ROM drive mounting bracketGet Price

Floppy disk drive mounting bracket - Mounts below the CD-ROM driveGet Price

SCA (Single connector attach) hard disk backplane PCA - Has one female 68-PIN connector, and two 80-PIN SCA hard drive connectors - Mounts to the rear of the hard drive bayGet Price

9.1GB Ultra2 wide SCSI LVD hard drive - 7,200 RPM, 3.5-inch form factor, 1.0-inch high, 80-pin SCA connectorGet Price

9.1GB Ultra2 wide SCSI LVD hard drive - 10,000 RPM, 3.5-inch form factor, 1.0-inch high, 80-pin SCA connectorGet Price

18GB Ultra2 Wide SCSI LVD hard drive - 10000 RPM, 3.5in form factor, 1.0in high, 80-pin SCA connectorGet Price

32x-max CD-ROM drive - Half-height CD-ROM drive with ATAPI IDE connectorGet Price

1.44MB floppy drive - 3.5-inch form factor with IDE PC/AT interfaceGet Price

36GB Ultra2 Wide LVD SCSI hard drive - 10000 RPM, 3.5in form factor, 1.0in high, 80-pin SCA connectorGet Price

Fans

Tubeaxial fan (Panaflo model FBA09A12H) 92mm x 92mm x 25mm thick fan with 22cm long three wire cable - 12VDC nominal operating voltage - Mounts to the I/O card cage bracketGet Price

Tubeaxial fan kit (Panaflo model FBA12G12H) - 120mm x 120mm x 37mm thick fan with 30cm long 3-wire cable - 12VDC nominal operating voltage - Includes ESD wrist strap and instructions - Mounts on the rear of the chassis assembly (Two used)Get Price

Graphics

VISUALIZE-FX2 graphics board - 1280 x 1024 accelerated 3D solids double-buffered 12-plane color graphics board with 8 overlay planes - (Part of A4552A)Get Price

HP VISUALIZE-fx2 graphic accelerator board - 24/8 bit accelerated 3D solids - Has EVC video connector - Requires HP-UX 10.20 with 'Additional Core Enhancements' (ACE)Get Price

VISUALIZE-FX2 graphic accelerator board - 24/8 bit accelerated 3D solids - Has EVC video connector - Requires HP-UX 10.20 with 'Additional Core Enhancements' (ACE)Get Price

VISUALIZE-FX4 graphics board - 1280 x 1024 accelerated 3D solids double-buffered 24-plane color graphics board with 8 overlay planes - (Part of A4553B, replacement for A4553A)Get Price

HP VISUALIZE-FX4 PCI graphics cardGet Price

Video output board for VISUALIZE-FX series graphics products only - Provides NTSC, PAL, AND S-VIDEO outputsGet Price

Texture memory mapping accelerator board - 16MB texture memory and 32KB x 32KB virtual texture cache - For A4553A/B (VISUALIZE-FX4) graphics board - Adds 8 planesGet Price

Texture memory upgrade for VISUALIZE-FX4 - Adds 16MB texture memory and 32KB x 32KB virtual texture cacheGet Price

Texture memory upgrade for VISUALIZE-FX4 - Adds 16MB texture memory and 32KB x 32KB virtual texture cacheGet Price

HP VISUALIZE-EG PCI graphics card with 4MB memory - The EG card is 8 plane with 8 overlay planes - Can be used in either a 3.3V or 5.0V PCI slot - (Part of A4977A)Get Price

HP VISUALIZE-EG PCI graphics card with 4MB memory - The EG card is 8 plane with 8 overlay planes - Can be used in either a 3.3V or 5.0V PCI slotGet Price

Memory

128MB, 120MHz SDRAM DIMM memory module - (Part of A4993A)Get Price

256MB, 120MHz SDRAM DIMM memory module - (Part of A4994A)Get Price

512MB, 120MHz SDRAM DIMM memory module - (Part of A4995A)Get Price

1024MB, 120MHz SDRAM DIMM memory module - (Part of A6016A)Get Price

128MB, 120MHz SDRAM DIMM memory moduleGet Price

256MB, 120MHz SDRAM DIMM memory moduleGet Price

512MB, 120MHz SDRAM DIMM memory moduleGet Price

1024MB, 120MHz SDRAM DIMM memory moduleGet Price

Other

Disposable ESD ground wrist strapGet Price

Power Supplies

Power supply assembly (500 watts) - Includes power supply, safety interlock switch, and AC power connector - Mounts in the lower left of the chassis assemblyGet Price

Power supply assembly (500 watts) - Includes power supply, safety interlock switch, and AC power connector - Mounts in the lower left of the chassis assembly Get Price

Power supply assembly (500 watts) - Includes power supply, safety interlock switch, and AC power connector -

Mounts in the lower left of the chassis assembly Get Price

Power supply assembly (500 watts) - Includes power supply, safety interlock switch, and AC power connector - Mounts in the lower left of the chassis assemblyGet Price

Processors

C3000 to C3600 upgrade kitGet Price

Rack Mount Kits and Accessories

Rack mount kit - Includes the rack mount base, left and right rack ear panels, heavy duty slide rails, various screws, nuts, spacers, and an installation guideGet Price

Terminator

NSE (Narrow single-ended) external passive SCSI terminator module - 50 pin (M) with latch/spring clipsGet Price

LVD (Low voltage differential)/single-ended SCSI terminator - Has integral status LED which displays single-ended or low voltage differential mode - 68 pin (M) with thumbscrewsGet Price

咨询热线:小李15101013227 QQ:2537338435