

# HP B180L工作站

产品名称	HP B180L工作站
公司名称	北京中盛广信息技术有限公司
价格	8500.00/台
规格参数	品牌:HP 型号:B180L 产地:美国
公司地址	北京市大兴区西红门镇宏旭路1号15101013227
联系电话	15101013227

## 产品详情

HP B180L工作站

### 整机参数

HP B180L HP Visualize b180L : 180MHZ/256MB/9GB

A4190-66528 HP B180L MOTHERBOARD

0950-3021 HP B180L 200W POWEWR SUPPLY

A4200-66545 HP B CLASS 100MHZ 512KB CACHE MEMORY

A3830-60001 HP 128MB ECC MEMORY MODULE HP B132L B180L

A4190-66523 HP B Class B180 5 Volt Backplane Board With Eisa

82350-66501 HP agilent E2078A 82350A PCI-GPIB卡

E1489-66511 HP E1489-66511 PCA MXI CONTROLLER

### 备件详情

#### CPU

B132L: PA-7300LC 132MHz with 64/64KB int. L1 (+ 1MB ext. L2)

B132L+: PA-7300LC 132MHz with 64/64KB int. L1 (+ 1MB ext. L2)

B160L: PA-7300LC 160MHz with 64/64KB int. L1 (+ 1MB ext. L2)

B180L+: PA-7300LC 180MHz with 64/64KB int. L1 (+ 1MB ext. L2)

## Chipset

LASI ASIC, which features:

NCR 53C710 8-bit single-ended SCSI-2

Intel 82596CA 10Mbit Ethernet controller

WD 16C522 compatible parallel

Harmony CD/DAT quality 16-bit stereo audio

NS 16550A compatible serial

Wax chip

EISA bus converter (GSC-to-EISA)

Second RS232 serial

Dino GSC-to-PCI bridge

Phantom PseudoBC GSC+ port

Visualize-EG (Graffiti) graphics

Intel 82503 Ethernet transceiver, media auto-selection

CS4215 or AD1849 programmable CODECs

WD37C65C Floppy controller

B132L, B160L: NCR 53C720 16-bit Fast-Wide high-voltage differential (HVD) SCSI-2

B132L+, B180L+: Symbios Logic 53C875 16-bit Ultra-Wide SCSI-2 controller

B132L+, B180L+: DEC 21142/43 (Tulip) Fast-Ethernet controller

## Buses

GSC general system-level I/O bus

B132L (both): 33MHz 132MB/s

B160L: 40MHz 160MB/s

B180L+: 36MHz 144MB/s

EISA additional expansion I/O bus

PCI-32/33 high-performance device I/O bus

SCSI-2 Fast-Narrow single-ended bus

B132L, B160L: SCSI-2 Fast-Wide high-voltage differential main storage I/O bus

B132L+, B180L+: SCSI-2 Ultra-Wide single-ended main storage I/O bus

## Memory

72-pin ECC SIMMs, 60ns or faster

Takes 16-256MB modules (latest firmware-rev needed)

Six slots

32MB (2 × 16) minimum, 1.5GB (6 × 256) maximum

## Expansion

B132L, B160L:

One slot for either a GSC (EISA formfactor) or PCI 32-bit/33MHz, 3.3V card

One slot for either a GSC (EISA formfactor), PCI 32-bit/33MHz, 3.3V or EISA card

B132L+, B180L+:

One slot for either a GSC (EISA formfactor) or PCI 32-bit/33MHz, 5V card

One slot for either a GSC (EISA formfactor), PCI 32-bit/33MHz, 5V or EISA card

I/O slot layout (from top to bottom):

PCI-32/33 or GSC

PCI-32/33 or EISA or GSC

## Drives

One tray for a 68-pin half-height 3.5 SCSI hard drive, either Fast-Wide high-voltage differential (B132L, B160L) or Ultra-Wide SE (+-models)

One tray for a 3.5 Floppy drive

One tray for a 50-pin half-height 5.25 Fast-Narrow 50-pin SE SCSI drive, external accessible, can also accommodate a hard drive.

## External connectors

50-pin HD SCSI-2 Fast-Narrow single-ended

B132L, B160L: 68-pin HD SCSI-2 Fast-Wide high-voltage differential

B132L+, B180L+: 68-pin HD SCSI-3 Ultra-Wide single-ended

Two DB9 male RS232C serial

DB25 female parallel

B132L, B160L: TP/RJ45 10Mbit Ethernet

B132L+, B180L+: TP/RJ45 10/100Mbit Ethernet

15-pin AUI 10Mbit Ethernet

EVC graphics port1

Two PS/2 connectors for keyboard & mouse

Four phone jacks (microphone, headphones, line-in and line-out)