国产拖链电缆丨进口易格斯缆普代替型号电缆

产品名称	国产拖链电缆丨进口易格斯缆普代替型号电缆
公司名称	上海埃因电线电缆有限公司
价格	2.00/米
规格参数	埃因:上海 8x2.5:1 上海:1
公司地址	上海市奉贤区青村镇奉村路333号
联系电话	189****8807 189****8807

产品详情

国产拖链电缆丨进口易格斯缆普代替型号电缆

应用安装范围 The range of application: 适用于干燥或潮湿的室内,无强应力缓释或强制引导的自由连续往复运动下的安装, 特别是工业使用环境下的频繁弯曲场合,如木工机械、机床加工设备、物流输送系统、起重机场合等。 It is suitable for dry or wet rooms and installation without strong stress or free continuousreciprocatingmovement. It is special suitable for the working places o f Woodworking Machine, machine tool equipment,logistics conveyer system, crane and other r elated equipments.电缆特性 Character: 防水、防油、耐寒、抗紫外线、耐磨、阻燃 Waterproofing; oil resistance; cool resistance; abrasion resistance; flame resistance;anti-ultraviolet. 作为拖链电缆时, 弯曲寿命500万次以上。 Bending for life: above 5,000,000 电缆结构 屏蔽:镀锡铜丝编织屏蔽,编织密度大于85% Construction: 导体:多股超细精绞无氧铜丝,符合VDE0295CLASS 6标准 Conduct or: Fine strands of oxygen-free copper wire, acc. to VDE0295 CLASS 6 绝缘:特殊混合PVC 绝缘 Insulation: special PVC 颜色:≤0.5mm颜色表示,棕、黑、蓝、紫、粉红、橙 ≥0.5mm黑色数字白色号码编号,3芯以上带有黄绿接地线(黄绿可选) Colour:≤0.5mmbrown, black, blue, purple, pin k, orange ≥0.5mmCores black with consecutive white numbering. 3 cores or mor e with green/yellow earth wire 护套:特殊改性PVC护套 黑色(RAL9005)或灰色(RAL7001) Sheath: special PVC; black(RAL9005) or grey(RAL7001) 额定电压:截面<0.5mm2: 300/300V 截面≥0.5m m2: 300/500V Related voltage:SQ<0.5mm2: 300/300V SQ≥0.5mm2: 300/500V 测试电压:2000 V Test voltage: 2000V 使用温度范围:固定安装:-40 ° C至+70 ° C 移动安装:- 5 ° C至+70 ° C。 T he working temperature: fixed: -40 ° C ----- +70 ° C moved: - 5 ° C ----- +70 ° C 最小弯曲半径:固定安装:5x电缆外径; 移动安装:当行程<10米时,弯曲半径为7.5×d,当行程≥10米时,弯曲半径为10×d。 Minimun bending radius: fixed: 5×out er diameter moved: When travel < 10 m, bendi ng radius of 7.5 x d, When travel≥10 m, bending radius of 10 x d.

国产拖链电缆丨进口易格斯缆普代替型号电缆