

ASROCK C226 WS 12 9.6主板

产品名称	ASROCK C226 WS 12 9.6主板
公司名称	北京亿威腾达科技有限公司
价格	1500.00/片
规格参数	品牌:ASROCK 型号:C226 WS 产地:台湾
公司地址	北京市朝阳区大黄庄平房路(北京市运输公司)6号楼D-05室
联系电话	010-62669460 13718090467

产品详情

主板物理信息

- 型式 - ATX
- 尺寸 - 12" x 9.6" (30.5 cm x 24.4 cm)

处理器系统

- CPU - Supports New 4th and 5th Generation Intel XeonE3-1200 v3/v4*/ Core i7/i5/i3/Pentium/Celeron Processors (Socket 1150)- Supports Intel K-Series CPU Supports Hyper-Threading Technology- Supports Intel Turbo Boost 2.0 Technology version 3.0 or above is required
- 插槽 - Single socket H3 (LGA1150)
- 电源设计 - 6 Power Phase Design
- 芯片组 - Intel C226

系统内存

- 容量 - 4 x 240-pin DDR3 DIMM slots- Support up to 32GB, un-buffered DIMM
- 类型 - Dual Channel DDR3 1600/1333 UDIMM and ECC UDIMM- Supports DDR3
- 电压 - Supports 1.35V to 1.60V

扩展插槽

- PCIe 3.0 x 16 - 2 slots (PCIE6/PCIE3 : x16/x0 or x8/x8 mode)
- PCIe 2.0 x 4 - 1 slot (PCIE1: x4 mode)
- PCIe 2.0 x 1 - 3 slots (PCIE4/PCIE5/PCIE7)
- PCI - 1 slot (PCIE2)

存储

- SATA 控制器 - Intel C226 : 6 x SATA3 6.0 Gb/s, support RAID 0, 1, 5, 10, Intel Rapid Storage a SWAP.
- 额外存储控制器 - 2x Marvell SE9172 : 4 x SATA3 6.0 Gb/s, support RAID 0, 1, NCQ, AHCI and

		(1 share with eSATA)
以太网		
	接口	- Gigabit LAN 10/100/1000 Mb/s
	网络控制器	- 2 x Intel i210- Supports Wake-On-LAN- Supports Energy Efficient Ethernet 802.3az- Supports Dual LAN with Teaming function- Supports PXE
显示		
	控制器	- Intel HD Graphics Built-in Visuals and the VGA outputs can be supported only on processors which are GPU integrated
	显存	- Max. shared memory 1760MB
	输出接口	- HDMI: max resolution up to 4096 x 2304@ 24 Hz- DisplayPort 1.2 : max resolution up to 3840 x 2160 @ 60 Hz- DVI : max resolution up to 1920 x 1200 @ 60 Hz
音频		
	音频编解码器	- ALC1150
后侧面板 I/O 接口		
	PS/2 键盘/鼠标	- 1
	VGA 接口	- 1 x HDMI + 1 x DVI-I + 1 x Display port
	USB 2.0 接口	- 4
	USB 3.0 接口	- 4
	eSATA 接口	- 1 (eSATA3)
	网络接口	- 2 x RJ45 Gigabit Ethernet LAN ports- LAN Ports with LED (ACT/LINK LED and Power LED)
	音频	- 5+1 Jack
	1394	- 1
	SPDIF	- 1
内置接口		
	串口连接插座	- 1 (COM1)
	电源 LED 连接头	- 1
	机壳开启侦测连接头	- 1
	辅助面板接头	- 1 (include chassis intrusion, front LAN LED)
	TPM 接口	- 1
	风扇接口	- 5 (2 x 4-pin, 3 x 3-pin)
	ATX 电源	- 1 (24-pin) + 1 (8-pin)
	USB 3.0 连接头	- 1 (each support 2 USB 3.0)
	USB 2.0 连接头	- 3 (each support 2 USB 2.0)
系统 BIOS		
	BIOS 类型	- 64Mb AMI UEFI Legal BIOS with GUI support
	BIOS 功能	- Plug and Play (PnP)- ACPI 1.1 Compliance Wake Up Events- SMBIOS 2.3.1 Support- DRAM Voltage Multi-adjustment- CPU Core, IGPU, DRAM, 1.8V PLL, VTT, Vcore Voltage Multi-adjustment
硬件监控		
	温度	- CPU Temperature Sensing- System Temperature Sensing
	风扇	- CPU/Rear/Front Fan Tachometer- CPU Quiet Fan (Allow Chassis Fan Speed Adjustment by CPU Temperature)- CPU/Rear/Front Fan Multi-Speed Control
	电压	- Voltage Monitoring: +12V, +5V, +3.3V, CPU Vcore
支持操作系统		
	操作系统	Microsoft Windows- Microsoft Windows 8 / 8 64-bit / 7 / 7 64-bit- Windows 10 64-bit- Microsoft Windows 2012 R2 64-bit

特点

独特功能

- ASRock Instant Flash

使用环境

温度

- Operation temperature Range: 10C ~ 35C / Non operation temperature: -40C ~