

AD2550R-U3S3 服务器主板

产品名称	AD2550R-U3S3 服务器主板
公司名称	北京亿威腾达科技有限公司
价格	1200.00/片
规格参数	品牌:ASROCK 型号:AD2550R-U3S3 产地:台湾
公司地址	北京市朝阳区大黄庄平房路(北京市运输公司)6号楼D-05室
联系电话	010-62669460 13718090467

产品详情

主板物理信息

- 型式 - Mini ITX
- 尺寸 - 6.7" x 6.7" (17.02 cm x17.02 cm)

处理器系统

- CPU - Intel Dual-Core Atom D2550 Processor
- 插槽 - 1x micro-FCBGA11
- 电源设计 - 1+1 Power Phase Design
- 芯片组 - Intel ICH10R

系统内存

- 容量 - 2 x SO-DIMM slots- Support up to 4GB
- 类型 - Single Channel DDR3 memory technology- Supports DDR3 1066 DIMM
- 电压 - 1.5V

扩展插槽

- PCIe 3.0 x 16 - 1 slot (x1)
- mini PCIe - NA (optional)

存储

- SATA 控制器 - Intel ICH10R : 5 x SATA2 3.0 Gb/s, support RAID 0, 1, 5, 10
- 额外存储控制器 - Marvell SE9172; 2 x SATA3 6.0 Gb/s

以太网

- 接口 - Gigabit LAN 10/100/1000 Mb/s
- 网络控制器 - 2 x Intel 82574L- Supports Wake-On-LAN- Supports Energy Efficient Ethernet Supports Dual LAN with Teaming function Supports PXE

显示

- 控制器 - Integrated (GMA3600)

输出接口	- Supports D-Sub with max. resolution up to 1920x1200 @ 60Hz- Supports HDMI resolution up to 1920x1200 @ 60Hz
后侧面板 I/O 接口	
PS/2 键盘/鼠标	- 1
VGA 接口	- D-sub x 1, HDMI x1
USB 2.0 接口	- 6
USB 3.0 接口	- 2
eSATA 接口	- 1
网络接口	- 2 x RJ45 Gigabit Ethernet LAN ports- LAN Ports with LED (ACT/LINK LED and Power LED)
串口	- 1
内置接口	
辅助面板接头	- 1 (include chassis intrusion, location button & LED, front LAN LED)
TPM 接口	- 1
风扇接口	- 3 (1 x 4-pin, 2 x 3-pin)
ATX 电源	- 1 (24-pin)
USB 3.0 连接头	- 1 (each supports 2 USB 3.0)
USB 2.0 连接头	- 2 (each supports 2 USB 2.0)
A 型 USB 2.0 连接头	- 1
LVDS 接口	- NA (optional)
前面板	- 1
扬声器	- 1 (4 pin)
板载 LED	
Standby PWR LED 5vsb	- 1
系统 BIOS	
BIOS 类型	- 16Mb SPI Flash ROM- AMI UEFI BIOS
硬件监控	
温度	- CPU Temperature Sensing- System Temperature Sensing
风扇	- CPU/Rear/Front Fan Tachometer- CPU Quiet Fan (Allow Chassis Fan Speed Adjustment by CPU Temperature)- CPU Fan Multi-Speed Control
电压	- Voltage Monitoring: +12V, +5V, +3V, CPU Vcore, memory
支持操作系统	
操作系统	- Microsoft Windows 7 / Home Server 2011 / Storage Server 2008 R2 / Server 2008 / Fedora.
	*64bit OS no graphic driver support, need to use inbox graphic driver.
特点	
独特功能	- ASRock Instant Flash- ASRock Crashless BIOS- Boot Failure Guard (B.F.G.)
使用环境	
温度	- Operation temperature Range: 10 ° C ~ 35 ° C / Non operation temperature: -40 ° C ~ 70 ° C