

汗蒸房温控器 华阳天地

产品名称	汗蒸房温控器 华阳天地
公司名称	北京华阳天地电子科技有限公司
价格	.00/个
规格参数	品牌:华阳天地 型号:HY329DH-WT 控制类型:温度
公司地址	北京市昌平区回龙观镇东半壁店村南北区西路13号
联系电话	13601233022 13161759593

产品详情

品牌	华阳天地	型号	HY329DH-WT
控制类型	温度	控制模式	智能温度控制调节器
测量对象	发热电缆	温度范围	0-95 ()
测温误差	1 ()	开孔尺寸	86*86*13 (mm)
安装型式	标准86盒安装	输出信号	16A (mA)
工作电压	AC220 (V)	外形尺寸	86*86*13 (mm)
重量	0.22 (Kg)		

hy329dh-

wt适用于汗蒸房中与电热采暖设备配套使用。温控器采用微电脑控制技术，大液晶屏显示。温度

传感器可根据用户选择测量室温或是测量地面温度。它的特点充分体现了现代温控领域内的新理念:舒适、节能。

主要功能：

- 1、大屏幕液晶显示
- 2、传感器故障检测
- 3、定时开/关机功能
- 4、掉电记忆功能
- 5、蓝色背光（选配）

- 6、低温保护功能
- 7、传感器外置功能（选配）
- 8、红外遥控功能（选配）
- 9、温度校准功能
- 10、继电器输出

技术参数：

电源电压：ac220v

设定范围：0-95

控温精度： ± 1

回差：默认2（0.5-90 可调）

电流负载：阻性16a或20a（选配）

自身功耗：1w

显示：lcd

外壳：高级阻燃abs材料

外型尺寸：86x86x13mm

安装孔距：60mm（标准）

可根据用户要求，灵活设计！

hy329dh-wt fork steam room with electric heating equipment for use. thermostat microcomputer control technology, large lcd screen display. temperature sensor can measure the user to select measurement at room temperature or ground temperature. it features fully reflects the temperature in the field of modern new concept: comfort, energy saving. main features: 1, large-screen liquid crystal display 2, sensor fault detection 3, timer on / off function 4, power-down memory function 5, the blue backlight (optional) 6, the low-temperature protection 7, external sensors (optional) 8, infrared remote control (optional) 9, temperature calibration 10, relay output technical parameters: power supply voltage: ac220v range: 0-95 temperature accuracy: ± 1 backlash: the default 2 (0.5-90 adjustable) current load: resistive 16a or 20a (optional) their power consumption: 1w display: lcd housing: high flame retardant abs material dimensions: 86 x 86 x 13mm installation hole distance: 60mm (standard) according to user requirements, design flexibility!

hy329dh-wt fork steam room with electric heating equipment for use. thermostat microcomputer control technology, large lcd screen display. temperature sensor can measure the user to select measurement at room temperature or ground temperature. it features fully reflects the temperature in the field of modern new concept: comfort, energy

saving. main features: 1, large-screen liquid crystal display 2, sensor fault detection 3, timer on / off function 4, power-down memory function 5, the blue backlight (optional) 6, the low-temperature protection 7, external sensors (optional) 8, infrared remote control (optional) 9, temperature calibration 10, relay output

technical parameters: power supply voltage: ac 220v range: 0-95 temperature accuracy: ± 1 backlash: the default 2 (0.5-90 adjustable) current load: resistive 16a or 20a (optional) their power consumption: 1w display: lcd housing: high flame retardant ABS material dimensions: 86 x 86 x 13mm installation hole distance: 60mm (standard) according to user requirements, design flexibility!