

成都一洋五金专业生产低烟毒金属软管

产品名称	成都一洋五金专业生产低烟毒金属软管
公司名称	成都一洋五金有限公司
价格	6.00/米
规格参数	品牌:Driflex/一洋五金 型号:LFH-10S-19S 规格: 12- 100
公司地址	成都市高新西区天目路77号
联系电话	13348931787

产品详情

低烟毒镀锌金属软管

Low Fire Hazard Galvanized Steel Flexible Conduit

材 质： 镀锌钢带
 PVC 包塑： 黑
 防护等级： IP65
 耐温范围： -10 - +90
 拉 力： 1700N
 Materials: Galvanized Steel
 PVC Coated: Black
 Protection IP65
 Rating:
 Temperature -10 - +90
 Range:
 Tension : 1700N

型号 Part No.	规格	通径	内径(mm)	外径(mm)	弯曲半径 (m)	包装 (m/coil)
镀锌钢带 (S)	Inch	mm	I.D.	O.D.	Bending Radius	Packing
LFH-10S	3/8"	12	12.30-12.60	16.50-16.80	60.0	50
LFH-11S	1/2"	16	15.70-16.00	20.50-20.80	85.0	50
LFH-12S	3/4"	20	19.70-20.00	25.30-25.60	100.0	50
LFH-13S	1"	25	25.30-25.80	30.70-31.20	120.0	50
LFH-14S	1-1/4"	32	32.30-32.80	38.50-39.00	150.0	25
LFH-15S	1-1/2"	38	38.30-38.80	45.70-46.20	180.0	25
LFH-16S	2"	51	50.00-50.50	58.80-59.30	220.0	20
LFH-17S	2-1/2"	64	62.50-63.20	73.50-74.00	310.0	10
LFH-18S	3"	75	73.00-73.70	84.50-85.20	350.0	10
LFH-19S	4"	100	97.50-98.50	109.50-110.50	410.0	10

镀锌铁皮制成，表面低烟毒PVC被覆，
轻质结构，绝佳弯曲性能及低烟毒耐燃特性

Galvanized Steel Core, PVC coated.
Light weight style, excellent flexibility and

，
使用于任何狭小空间或通风不良，
注重生命安全等配管区域。

low fire hazard low smoke.
Use for the place with poor ventilation or the
environment needs more secure care of any
narrow
space for electrical wiring applications.

低烟毒不锈钢金属软管

Low Fire Hazard Stainless Steel Flexible Conduit

材 质： 不锈钢钢带
PVC 包塑： 黑
防护等级： IP65
耐温范围： -10 - +90
拉 力： 1700N
Materials: Stainless Steel
PVC Coated: Black
Protection IP65
Rating:
Temperature -10 - +90
Range:
Tension : 1700N

型号 Part No.	规格	通径	内径(mm)	外径(mm)	弯曲半径 (m)	包装 (m/coil)
		mm	I.D.	O.D.	Bending Radius	Packing
不锈钢钢带 (SInch S)						
LFH-10SS	3/8"	12	12.30-12.60	16.50-16.80	60.0	50
LFH-11SS	1/2"	16	15.70-16.00	20.50-20.80	85.0	50
LFH-12SS	3/4"	20	19.70-20.00	25.30-25.60	100.0	50
LFH-13SS	1"	25	25.30-25.80	30.70-31.20	120.0	50
LFH-14SS	1-1/4"	32	32.30-32.80	38.50-39.00	150.0	25
LFH-15SS	1-1/2"	38	38.30-38.80	45.70-46.20	180.0	25
LFH-16SS	2"	51	50.00-50.50	58.80-59.30	220.0	20
LFH-17SS	2-1/2"	64	62.50-63.20	73.50-74.00	310.0	10
LFH-18SS	3"	75	73.00-73.70	84.50-85.20	350.0	10
LFH-19SS	4"	100	97.50-98.50	109.50-110.50	410.0	10

不锈钢制成，表面低烟毒PVC被覆，
轻质结构，绝佳弯曲性能及低烟毒耐燃特性

Stainless Steel Core, PVC coated.
Light weight style, excellent flexibility and

，
使用于任何狭小空间或通风不良，
注重生命安全等配管区域。

low fire hazard low smoke.
Use for the place with poor ventilation or the
environment needs more secure care of any
narrow
space for electrical wiring applications.