

TACT Switch 8U Series

| | |
|------|-----------------------|
| 产品名称 | TACT Switch 8U Series |
| 公司名称 | 苏州寰立电子有限公司 |
| 价格 | .00/个 |
| 规格参数 | |
| 公司地址 | 苏州市姑苏区阊胥路575号远东大厦712室 |
| 联系电话 | 18962118535 |

产品详情

SPECIFICATIONS

CONTACT RATING: 0.4VA max. @20V AC or DC max.

MECHANICAL LIFE: 40,000 make-and-break cycles.

CONTACT RESISTANCE: Bellow100m Ω ?typ.initial@2-4VDC 100mA.

INSULATION RESISTANCE: 500m Ω ? min.

DIELECTRIC STRENGTH: 500V RMS min@sea level.

OPERATING TEMPERATURE: -30 $^{\circ}$ to 85 $^{\circ}$?

MATERIALS

HOUSING AND BASE: Glass filled nylon 66 or 4/6 flame retardant,heat stabilized(UL 94V-0).

ACTUATOR: Glass filed nylon6/6,flame retardant,heat stabilized(UL94V-0),with standard internal o-ring seal.

SWITCH SUPPORT: Steel,with nickel plated.

CONTACTS/TERMINALS: Silver or gold plated copper alloy.