

# TACT Switch PA Series

产品名称	TACT Switch PA Series
公司名称	苏州寰立电子有限公司
价格	.00/个
规格参数	
公司地址	苏州市姑苏区阊胥路575号远东大厦712室
联系电话	18962118535

## 产品详情

Size:17.5x5.08mm Sub-Miniature Pushbutton Switch

SPECIFICATION SPA S6/S7: 400mA 32VAC-100mA 50VDC-125mA 125VAC

500mA 48VAC-200mA 50VDC-200mA 250VAC PA L6: 100mA 24VDC-life expectancy 200,000 cycles 2A 125VAC-life expectancy 10,000 cycles

INITIAL CONTACT RESISTANCE: 50m max.

INSULATION RESISTANCE: 1G min.at 500VDC.

DIELECTRIC STRENGTH: 1,000 VAC rms.

1,500 VAC rms.for metal material

ELECTRICAL LIFE AT FULL LOAD:

PA S6/S7:500,000 cycles.

PA L6:200,000 cycles.

OPERATING TEMPERATURE: -30 ° C to 85 ° C.

PANEL THICKNESS:

B1 series : 0.8 mm (.031) min. -1.8 mm (.071) max

B2 series : 1.5 mm (.059) min. -4 mm (.157) max B3 series : 3.0 ± 0.25 mm (.118)

TOTAL TRAVEL:

PA S6/S7: 1.5 mm(.059)

PA L6 : 2.5 mm(.098)

OPERATING FORCE:

PA S6/S7: 2N~5N

PA L6 : 5.5N+/-1.5N

CONTACT BOUNCE:10 ms.

MECHANICAL LIFE:1,000,000 cycles.

TORQUE:0.5 Nm max.applied to nut.

1.5 Nm max.for metal material

SOLDERING:350 C max.for 5 seconds