

# 玖宝直销日本NTM日富端子1.25Y-4N

产品名称	玖宝直销日本NTM日富端子1.25Y-4N
公司名称	南京玖宝机电设备有限公司
价格	.00/个
规格参数	品牌:日本NTM日富 型号:1.25Y-4N 产地:日本
公司地址	南京市栖霞区尧化街道科创路1号02幢
联系电话	15051805943

## 产品详情

日本NTM日富端子1.25Y-4N 南京玖宝机电设备中国原装直销

产品介绍

产品品牌：日本NICHIFUニチフ压着端子ニチフ

产品名称：日本日富NTM端子、压着端子

产品包装：出厂原包装

日本日富NTM端子常见型号

8Y-5

8Y-6

14Y-6

14Y-8

0.3Y-2

0.3Y-3

2Y-4N

2Y-4S

2Y-4

2Y-4M

2Y-5

2Y-5M

2Y-5L

2Y-6

2Y-8

3.5Y-4

3.5Y-5

3.5Y-6

5.5Y-4S

5.5Y-4

5.5Y-5

5.5Y-6

0.3Y-3.5N

0.3Y-4N

0.3Y-5

0.75Y-4

1.25Y-2.5

1.25Y-3K

1.25Y-3S

1.25Y-3

1.25Y-3.5

1.25Y-3L

1.25Y-4N

1.25Y-4S

1.25Y-4M

1.25Y-4L

1.25Y-5

1.25Y-6

2Y-3

2Y-3.5S

2Y-3.5

2Y-3.5L

5.5Y-3.5N

1.25Y-3N

1.25Y-3.5K

0.08-3

0.08-3-BOX

0.08-M3.5

0.08-M3.5-BOX

0.3-3

0.3-3-BOX

1.25-3

1.25-3-BOX

1.25-3.5

1.25-3.5-BOX

1.25-4

1.25-4-BOX

1.25-5

1.25-5-BOX

1.25-M3.5

1.25-M3.5-BOX

2-3.5

2-3.5-BOX

2-4

2-4-BOX

2-5-BOX

2-6

2-6-BOX

2-8

2-8-BOX

5.5-4

5.5-4-BOX

5.5-5

5.5-5-BOX

5.5-6

5.5-6-BOX

5.5-8

5.5-8-BOX

5.5-10

5.5-10-BOX

8-5

8-5-BOX

8-6

8-6-BOX

8-8

8-8-BOX

8-10

8-10-BOX

14-5

14-5-BOX

14-6

14-6-BOX

14-8

14-8-BOX

14-10

14-10-BOX

14-12-BOX

22-6-BOX

22-8-BOX

22-10-BOX

22-12-BOX

38-8-BOX

38-10-BOX

38-12-BOX

60-8-BOX

R0.3-2

R0.3-3

R0.3-3N

R0.3-3.5

R0.3-4

R0.3-5

R1.25-2

R1.25-2S

R1.25-3

R1.25-3N

R1.25-3S

R1.25-3.5N

R1.25-3.5S

R1.25-3.5

R1.25-3.5M

R1.25-3.5L

R1.25-4M

R1.25-4

R1.25-5

R1.25-6

R1.25-8

R1.25-10

R2-2

R2-3N

R2-3S

R2-3

R2-3.5N

R2-3.5NS

R2-3.5

R2-3.5S

R2-3.5M

R2-4S

R2-4M

R2-4

R2-5M

R2-5

R2-5L

R2-6

R2-8

R2-10

R2-12

R3.5-4

R3.5-5S

R3.5-5L

R3.5-6L

R3.5-8

R5.5-3M

R5.5-3N

R5.5-3S

R5.5-3.5N

R5.5-3.5S

R5.5-3.5

R5.5-4N

R5.5-4S

R5.5-4

R5.5-5N

R5.5-5S

R5.5-5

R5.5-6

R5.5-8

R5.5-10

R5.5-12

R5.5-14

R8-4S

R8-4

R8-5S

R8-5

R8-6S

R8-6

R8-8

R8-10

R8-12

R8-14

R14-5S

R14-5

R14-6S

R14-6

R14-6L

R14-8S

R14-8

R14-10

R14-12

R14-14

R14-16

R14-20



R22-6

R22-8S

R22-8

R22-10

R22-12

R22-14

R22-16

R22-20

R38-5

R38-6S

R38-6

R38-8S

R38-8

R38-10S

R38-10

R38-12

R38-14

R38-16

R38-20

R60-6S

R60-6

R60-8S

R60-8

R60-10S

R60-10

R60-12

R60-14

R60-16

R60-20

R60-22

R70-8

R70-10

R70-12

R70-14

R70-16

R70-20

R70-22

R80-8

品番各部の寸法mm電線抱合範囲適用工具絶縁体標準色手動工具 b B d DLFH撚線mm2AWG本体  
ヘッドPC 2005-M2.05.11.73.126.515.011.50.5 ~ 0.7520-18NH 5NH 32NH 60ナイロン透明PC  
2005-F2.04.624.513.0NA 10NA 3N10 10N3 5PC 4009-M4.07.41.83.227.716.511.20.75 ~ 1.2518-16NH 11NH 32  
赤PC 4009-F3.956.926.215.0NA 10NA 3N10 11N3 11PC 4020-M4.07.42.43.927.716.52.014NH 12NH 32青PC  
4020-F3.956.926.215.0NA 10NA 3N10 12N3 12

R100-20

R100-22

R150-8

R150-10

R150-12

R150-14

R150-16

R150-18

R150-20

R150-22

R150-27

R180-10

R180-12

R180-14

R180-16

R180-18

R180-20

R180-22

R200-10N

R200-10S

R200-12N

R200-12S

R200-12

R200-14

R200-16

R200-18

R200-20

R200-22

R200-24

R200-27

R325-10N

R325-10S

R325-12N

R325-12S

R325-14S

R325-16

R325-18

R325-20

R325-22

R325-24

R325-27

RD38-10

RD38-12

RD38-孔ナシ

RD60-10

RD60-12

RD60-14

RD60-孔ナシ

RD70-10

RD70-12

RD70-孔ナシ

RD80-10

RD80-12

RD80-14

RD80-孔ナシ

RD100-10

RD100-12

RD100-14

RD100-孔ナシ

RD150-12

RD150-14

RD150-孔ナシ

RD180-12

RD180-14

RD200-12

RD200-14

RD325-12

RD325-14

【特長】難燃性。使用温度範囲：-40 ~ +105 。【用途】着脱式で中継接続の使用に最適。

南京玖宝机电设备有限公司

联系人：王先生

电话：13770506113

QQ：3215027595

jiubaojidian@126.com