

成都一洋五金生产不锈钢编织304防爆穿线管

产品名称	成都一洋五金生产不锈钢编织304防爆穿线管
公司名称	成都一洋五金有限公司
价格	12.78/米
规格参数	品牌:Driflex/一洋五金 型号:PVJ-8S- PVC-19S 规格: 8- 100
公司地址	成都市高新西区天目路77号
联系电话	13348931787

产品详情

防爆型金属
软管

Explosive Proof VJ Steel Flexible
Conduit

材 镀锌钢带+PVC+不锈
质： 钢丝编织

防护等级： IP65

耐温范围： -50 -
+300

拉 1700N
力：

Materials: Galvanized steel + PVC + stainless steel overbraided

Protection IP65

Rating:

Temperature-50 - +300

Range:

Tension : 1700N

型号 Part No.	规格 (Inch S)	通径 mm	内径(mm) I.D.	外径(mm) O.D.	弯曲半径 (mm) Bending Radius	包装 (m/c oil) Packing
PVJ-8S	1/4"	8	7.80-8.10	12.65-12.95	70	50
PVJ-9S	5/16"	10	9.60-10.20	14.65-14.95	70	50
PVJ-10S	3/8"	12	11.50-12.50	17.15-17.45	70	50
PVJ-11S	1/2"	16	14.80-16.00	21.15-21.45	90	50
PVJ-12S	3/4"	20	19.00-20.00	25.95-26.25	110	50
PVJ-13S	1"	25	24.50-25.00	31.35-31.85	150	50

PVJ-14S	1-1/4"	32	31.50-32.50	39.15--39.65	175	25
PVJ-15S	1-1/2"	38	37.50-38.50	46.35-46.85	200	25
PVJ-16S	2"	51	49.50-50.50	59.45-59.95	230	20
PVJ-17S	2-1/2"	64	62.50-65.00	74.15-74.65	250	10
PVJ-18S	3"	75	73.00-76.00	85.15-85.85	300	10
PVJ-19S	4"	100	97.00-103.00	109.00-110.15	500	5

5

镀锌铁皮制成，表面被覆耐延烧PVC材料，

外层编织不锈钢丝，以起到防爆功效。

极佳柔软性及绝对防水、防爆效果

。吸收移动和震动的性能，多方向弯曲挠性。

适合使用于油气水气重之场所。

适合配套铁镀锌接头、铜镀镍、不锈钢或锌合金接头。

Galvanized Steel square-locked core with

flame resistant PVC coated, outside layer with

stainless steel braided to achieve effect

of explosive proof.

High Flexibility, absolutely waterproof explosive

proof effect.

Absorb moving and shake function, high bendability

Use for the place with strong oil-gas and hydrosphere.

Suitable fittings: zinc plated steel, nickel plated brass, Stainless steel or zinc alloyed fittings.