

灯泡全自动装盒机

产品名称	灯泡全自动装盒机
公司名称	温州博航机械有限公司
价格	.00/台
规格参数	博航:最大成型深度 40mm(Speci BH-350F:生产能力 10-25冲/分 浙江平阳:成形面积 255*220
公司地址	平阳县万全镇郑宋大道607号
联系电话	0577-63787928 18966266068

产品详情

概述Application:

该设备是我公司结合国内外先进技术开发研制的新型机型，是集光、电、气、机一体的高科技产品，从而使设备性能和工作效率得到了大幅度提高，实现快速装盒要求，且在快速运行时仍保持平稳、可靠状态。

该机适用块状物品的自动装盒、自动加料。在线数量检测、说明书折叠（1至4折叠）与传送、说明书检测、纸盒吸取成形与传送、物料入盒、压印批号、纸盒两端纸舌封装（也可适用热熔胶）、缺料剔除及成品输出等全过程均属自动完成。

This equipment is new model developing base on integrated domestic and foreign vanguard technology. It is high technology product incorporates pneumatic-photo-electro-mechanic which improve by a large on performance of equipment and working efficiency, realize encasing fast, keep running steady and reliable when fast running.

This machine is suitable for blister package product, adjust automatic feeding structure conveniently, setup quantity of blisters on touch screen randomly.

On line product feeding and detecting, leaflet fold (1-4 folds) and feeding, leaflet detecting, carton opening and forming, products and leaflet pushing into carton, printing batch number, sealing carton with tuck-in or hot melt glue device. Automatically reject lacking of leaflet or product and finished product out.

主要性能特点

PLC自动控制系统、变频调整，电器元件均采用国际或国内知名品牌。

采用人机界面操作系统。

机械过载自动停机。

自动剔除缺包装物和说明书的纸盒。

故障显示、报警和成品计数。

性能稳定、操作简便。

International famous brand of electrical component such as PLC touch screen, frequency inverters, etc.

Adopt human-machine operation system.

Automatically stop when machine is overload.

Automatically reject lacking of package product and leaflet.

Automatically display trouble, Alarm and count finished products.

Stable performance, operation is easy.

主要技术参数 Main technical parameters

装盒速度 Encasing speed		30-100盒/分 (boxes/min)
纸盒 Box	规格 Size	250-350g/m ² (视纸盒大小而定 Base on carton size)
说明书 Leaflet	尺寸范围 Dimension range (l*w*h)	(70-200)*(30-80*15-50)mm
	规格 Size	55-65g/m ²
	未折叠尺寸范围 Unfolded leaflet specification	(100-250)*(100-190)mm (l*w)
压缩空气	折叠范围	(1-4)折 (Fold)
	工作压力	0.5-0.7Mpa
	耗气量	20m ³ /h
Compressed air		
电源总功率 Power supply		380V/220V 50HZ 1.5kw
主电机功率 Main power		0.75kw
外形尺寸 Machine dimension (L*W*H)		3100*1350*1450
整机净重 Machine weight		1200kg