

ARFA立柱式悬臂吊

产品名称	ARFA立柱式悬臂吊
公司名称	阿尔法起重机有限公司
价格	100.00/台
规格参数	品牌:阿尔法 型号:立柱式悬臂吊 产地:中国
公司地址	长垣县起重工业园区巨人大道11号
联系电话	0373-8622848 15836026675

产品详情

特性描述Feature Description

优化设计，结构轻，符合欧洲标准FEM 1.001 A4

Compacted frame, smoothly moving

Frame classification according to FEM 1.001 : A4

扁电缆托令系统供电，运行平稳，操作方便

Smooth and sophisticate operation

Flat cable feeding line with sliding supports

品种多样，满足不同需求，起重量达到5000kg

Complete solution for lifting needs, Max. 5000kg

环氧富锌油漆，漆膜附着力强，十年以上寿命，中黄RAL1028

Finish : Bright yellow polyurethane topcoat RAL 1028

旋臂采用高效的自润滑型推力轴承

Slewing is effected on a plain bearing with a self-lubricating ring

高度调节范围大

Large height adjustment

安装法兰采用M24/10.9级高强螺栓固定

Brackets are secured by H.R.M. 24 bolts, class 10.9.

所以螺栓安装都采用力矩扳手拧紧，紧固力矩达到92mkg

Tightening must be achieved by using torque wrench

Tightening torque: 92mkg.

连接强度高

Strong profile connection

轻型紧凑结构，对建筑要求低

Light construction - low loading for the building

安装方便

Easy to install

起重机控制模式 Control Mode

地操 Pendant

操作简便，无需设置专业驾驶员

Easy control, no additional driver necessary

双挡按钮

Two steps push button, with emergency stop

跟随式或独立滑道非跟随式悬挂

Independent festoon station or fixed suspended under hoist

防护等级为IP65

Protection class IP65

寿命50万次Life time 500,000

遥控 Remote Control

操作简便，无需设置专业驾驶员，操作者在地面自由度大

Easy control, no additional driver, remote access

几万组频点，互不干涉

Flexible frequency selection, total reliable

双挡按钮或摇杆式操纵杆

Two steps push button or joy stick station with emergency stop

防护等级为IP65 Protection class IP65

寿命50万次Life time 500,000

起重机速度 Speed control

起升 Lifting Motor

通常采用双速，造价低，冲击小，节能，定位精确

Pole changed squirrel cage moter, 2 speed with fast and slow selection, precise load handling

IP55 / F class

小车运行 Trolley traversing

手动或变频调速，运行平稳，噪音小，有效防止重物的晃动

Manual push trolley or stepless motorized trolley, more stable movement, safety solution

IP54 / F class

旋转机构 Slewing

手动或变频调速，运行平稳，噪音小，有效防止重物的晃动

Manual or stepless motorized slewing, more stable movement, safety solution

IP54 / F class