

LAG -615水性丙烯酸酯流平剂

产品名称	LAG -615水性丙烯酸酯流平剂
公司名称	黄山澳盛源新材料科技有限公司
价格	.00/个
规格参数	
公司地址	黄山市经济开发区梅林大道89号（注册地址）
联系电话	2555354 13855917939

产品详情

DOPPEL – LAG -615水性丙烯酸酯流平剂

Polyacrylate-based surface additive for aqueous coatings and adhesives to improve leveling. Improves the leveling and substrate wetting in aqueous and radiation-curable printing inks and overprint varnishes.

Product Data

Composition

Solution of a polyacrylate, ionic

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density (20 ° C): 1.03 g/ml

Non-volatile matter: 52 %

Solvents: Dipropylene glycol monomethyl ether

Flash point: 75 ° C

Applications

Coatings and adhesives

Special Features and Benefits

The additive improves leveling and prevents surface defects such as craters and pinholes. It is recommended for all aqueous coatings and adhesives.

Recommended Levels

0.1-1 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Printing Inks and Overprint Varnishes

Special Features and Benefits

The additive improves leveling and substrate wetting and prevents surface defects such as craters and Pinholes. It is recommended for aqueous and radiation-curable printing inks and overprint varnishes.

Recommended Levels

0.1-1 % additive (as supplied) based on the total formulation.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.