

通径	胶管内径			增强层 外径	管外 径	工作压力			爆破压力		最小弯曲 半径	重量
	inch	mm	mm			mm	mpa	psi	mpa	psi		
5	3/16	4.8	11.1	13.4	41.4	6000	16	23720	89	0.32	50/100	
6	1/4	6.4	12.7	15.0	40.0	5800	160	22840	102	0.36	50/100	
8	5/16	7.9	14.3	16.6	36.0	5250	140	20000	114	0.45	50/100	
10	3/8	9.5	16.7	19.0	33.1	4800	132	18840	127	0.54	50/100	
13	1/2	12.7	19.8	22.2	27.6	4000	110	15720	178	0.68	50/100	
16	5/8	15.9	23	25.4	25.0	3630	100	14280	203	0.8	50/100	
19	3/4	19.0	27	29.3	21.5	3120	85	12280	241	0.94	50/100	
25	1	25.4	34.9	38.0	16.5	2400	65	9420	305	1.35	50	
32	1 1/4	31.8	44.5	48.3	12.5	1820	50	7140	419	2.15	20	
38	1 1/2	38.1	50.8	54.6	9.0	1310	36	5140	508	2.65	20	
51	2	50.8	63.5	67.3	8.0	1160	32	4560	635	3.42	20	