进口纳米二氧化硅分散胶体 GT-50

产品名称	进口纳米二氧化硅分散胶体 GT-50
公司名称	广州固铁新材料有限公司
价格	50.00/千克
规格参数	
公司地址	广州市增城区新塘镇南安村七星工业园G栋二楼
联系电话	020-82726119 13924128431

产品详情

GT-50 is an alkaline, aqueous dispersion of colloidal silica that is approximately 25% solids by weight. The silica dispersion is sodium stabilized and the amorphous silica particles carry a negative surface charge. The SiO2 particles are discrete, have a slightly rough, spherical shape, and are present in a narrow particle size distribution. The physical appearance of the dispersion is a translucent liquid, slightly more viscous than water. GT-50 is produced for world-wide ditribution.

Typical Properties

Silica, wt%: 25

pH: 11

Viscosity,mPa.s: 12

Particle Size, nm: 22

Density, g/cm3: 1.18

Na2O, wt%: 0.55

Range of Applications

GT-50 is a versatile product that has many different application and functions.

Storage, Handling, & Transport

GT-50 should be transported and stored at a temperature of 5-35 (40-95oF). If the silica dispersion is allowed to freeze, the silica will irreversably precipitate. For bulk storage, the tank should be sealed and constructed of plastic, fiberglass reinforced plastic, or stainless steel. For packaged goods, any translucent packages should be stored out of direct sunlight or bright light. Under recommended conditions, GT-50 has a shelf life of at least twelve months after production.

GT-50 is available in bulk and packaged quantities. Bulk shipping and packaging sizes can vary by region.

Before handling this material, review the corresponding Material Safety Data Sheet.

GT-50纳米二氧化硅分散液

本产品是一种碱性纳米二氧化硅分散胶体,外观无色透明,略比水粘稠,纳米二氧化硅含量25%。 二氧化硅以无定型球体形式存在,粒径为22nm,粒子表面带有少量负电荷,具有很大比表面积。

1).产品参数

固含量, wt% 25.0

密度, g/ml 1.18

粒径,nm 22

pH 11

粘度, mPa.s 12.0

- 2).特点和用途
- 1. 陶瓷涂料用;
- 2. 精密铸造结合剂;
- 3. 可用作防滑,防结块处理添加剂,耐火纤维中的高温粘结剂;
- 4. 电镀行业用作镀锌封闭剂产品中的耐盐雾添加剂,具有优越的盐雾侵蚀测试表现,同时可提高膜层硬度和耐磨性及附着力。

3)包装和储存

本产品有25、240公斤/桶包装,在5-35条件下保质期为1年。

欢迎新老客户惠顾,量大优惠!

免费提供样品,咨询电话:020-82726119 13924128431