

S11-M系列全密封油浸式配电变压器

| | |
|------|--------------------------------------|
| 产品名称 | S11-M系列全密封油浸式配电变压器 |
| 公司名称 | 台州市黄岩宏业变压器厂（普通合伙） |
| 价格 | 68500.00/台 |
| 规格参数 | 品牌:宏业 型号:S11-M-1250/10 线圈材质:纯铜 |
| 公司地址 | 浙江省台州市黄岩区东城街道龙浦路36号 |
| 联系电话 | 0576-84196522 13968402557 |

产品详情

signal thermometer and pressure relief valve, and enhance the reliability of the transformer.

海拔不超过1000m户内或户外 最高年平均温虚+20 最低气温-25

最高环境气温+40 最高日平均温虚+30 根据用户要求可提供在特殊使用条件下运行的变压器。

1.铁芯选用优质冷轧取向硅钢片，利用自动横剪工艺和应用阶梯接缝（Step-Lap）最新工艺制造，改善了磁通密度在铁芯内部的分布状况，减小了铁心的振动能量，有效地降低了噪声，降低了损耗。2.线圈选用高强度漆包线或纸包线（卷绕变压器式（或饼式）结构）安匝分布均匀，绝缘结构合理，具有很强的抗短路能力。3.变压器器身参数严格要求，防松结构，紧固部分带有锁防松螺母，采用了不用芯结构，能保证长途运输后运行时不松脱。4.波纹油箱的波纹片取变压器薄板，波纹片可以随变压器油体积的变化而涨缩，使变压器与大气隔绝，防止和减缓油的劣化和绝缘受潮，增强运行可靠性，正常运行免维护。5.配有"遥测信号温度压力等级释放阀"，增容量变压器运行及可靠性的系列全密封油浸式配电变压器，包括S9、S11、D11、SZ11等系列产品。全密封油浸式变压器采用全充油密封型，波纹式壳体油箱以自身弹性适应油的膨胀成为永久密封的油箱。该产品已被广泛地应用于城市电网建设和国家重点工程。

application of transformer with (voltage 35kV and below, capacity for the 500kVA) magnetic flux density distribution of inside core, reduced vibration of the core, effectively reduce S9, S11, D11, SZ11 and other products by name of oil tank (with bellows) welded, transformer (with bellows) is filled with oil type, corrugated tank shell to the turn-expansion and flexibility, adapt to resistance and dry-sealed oil tankity. The same for the body big item by gas stipulation structural, fastenig parts with self-locking structure, can assure crane operation after the long-distance transportation not loose.4. The bellows corrugated tank piece replaced oil tank, corrugated, can change with the volume of transformer oil and shrinkage, transformer and atmosphere, prevent and reduce oil from the degradation and insulation damp, enhance the reliability and normal operation maintenance.5. With a "remote"