气动闸板阀、气动方形闸板阀

产品名称	气动闸板阀、气动方形闸板阀
公司名称	永嘉锦鼎阀门股份有限公司
价格	1900.00/个
规格参数	品牌:锦鼎 型号:LMD 产地:温州
公司地址	永嘉县瓯北镇码道村码道中路27弄2号
联系电话	15888215509

产品详情

气动闸板阀、气动方形闸板阀安装、使用要点1、安装前应仔细阅读本说明、并核对阀门型号、通径及技术参数。2、严禁装上阀门后施焊法兰，以免损坏阀门密封圈。管道自先预留的阀门安装距离应适当，法兰两边加垫片。3、两管道中心与阀门通径中心应保持同轴，法兰面应平整，不允许法兰面有较大的偏斜，以保证阀门的夹紧和正常工作。拧紧螺栓应做到均匀对称。

关键字：气动方型插板阀，气动闸板阀，气动方形闸门，气动方形插板闸门，方形闸板门，气动方形闸板阀

公称通径：200×200——1000×1000

主体材质：Q235A、304、316、304L、316L

适用温度：-10~+200℃

连接法兰：GB/T9113、JB/T79

密封型式：硬密封、软密封配套附件

气动闸板阀、气动方形闸板阀是一种粉料、晶粒料、颗粒料及小块物料的流量或输送量的主要控制设备，广泛应用于矿山、粮食等行业控制流量变化或迅速切断（特料直径≤50mm）

类别Category A×A B×B C×C L H D0 n-d

单向

One-way 220×200 256×256 296×296 100 820 300 8-φ12

250×250 306×306 346×346 100 930 340 8-φ14

300×300 356×356 396×396 100 1050 380 8-φ14

400×400 456×456 496×496 100 1140 445 12-φ14

450×450 510×510 556×556 120 1450 530 12-φ18

500×500 560×560 606×606 120 1610 580 16-φ18

双向

Two-way 600×600 660×660 706×706 120 1830 450 16-φ18

700×700 770×770 820×820 140 2130 450 20-φ18

800×800 870×870 920×920 140 2440 450 20-φ18

900×900 974×974 1030×1030 160 2660 450 24-φ23

1000×1000 1074×1074 1130×113 160 2870 450 24-φ23

说明Specification LMD-单向

LMD one-way Ⅰ-手轮

I hand wheel
链条节数M=0.105×-113（×是丝杆中心离地面高度）距地面小于1.7米用于手轮大于1.7米用链轮

Number of chain nodes M = 0.105×-113 (× means the distance of lead screw center from surface); use hand wheel if the height is less than 1.7 m; use chain wheel if the height is more than 1.7 m.

LMD-双向

LMD two-way Ⅱ-链条

II chain

注：可来图来样定作非标的插板闸门

Note: Non-standard screw gate valve could be customized based on drawing or sample.