

高频在线式UPS RATA

产品名称	高频在线式UPS RATA
公司名称	缙云县瑞特电子有限公司
价格	.00/个
规格参数	品牌:RATA 型号:RT-U 设备类型:双变换高频纯在线
公司地址	浙江缙云县东渡镇东渡村上街头
联系电话	86 0578 3146355 18957055355

产品详情

品牌	RATA	型号	RT-U
设备类型	双变换高频纯在线		
型号-高频在线式rt-onlineups	rt1k/1ks	rt2k/2ks	rt3k/3ks
model-high frequency on-line			
额定容量max.capacity	1kva	2kva	3kva
(cos =0.7)			
输入	输入配线 input wiring 电压范围 voltage range 频率范围 frequency range 功率因数 power factor	单相二线+地线 single-phase line two+ground line 118 ~ 300vac 负载load < 50%, 140 ~ 300vac 50% 负载load < 70% 160 ~ 300vac 负载load 70% 46 ~ 54 hz >0 . 95 220vac ± 2%	220vac ± 2%
	voltage		

输出 output	频率 frequency	与输入市电同步(市电模式),50 hz ± 0.2%(电池模式) input synchronized the supply frequency(line mode),50 hz ± 0.2%(battery mode)		
	功率因数 power factor	0.7		
	电流峰值比current crest ratio	3 : 1		
	波形 waveform	正弦波 sine wave		
过载能力 overload capacity	105%-130%维持30秒钟后输入转为旁路 , 130%-300%维持200ms输出转为旁路 上立即关闭输出105%-130% maintain 30 seconds turn off and to bypass output maintain 200ms turn off and to bypass output,300% above turn off output immediately			
效率efficiency	>90%		>91%	>91%
电池标称电压 voltage of the battery	36vdc		96vdc	
转换时间transfer time	零中断zero interruption			
自动旁路automatic bypass	内置integrated			
指示灯indicator	指示负载大小、电池容量和ups运行状态 indicates load/battery capacity,ups running states etc			
警报声音 audible alarm	电池放电battery discharge	当输入断电时每4秒发出警报声 sounding every 4 seconds when mains fails 当电池用尽时每秒发出警告声 sounding every 1 second when battery exhausts		
	ups异常abnormal	连续声 beeping continuously		
通信界 communication interface	rs232+snmp (可选option)			
操作环境 operating environment	温度temperature	0 ~ 40		
	湿度humidity	20%-90% , 无凝结no condensate		
rt-jc外观/包装尺external/shipping size (w × d × h)	482 × 450 × 88/550 × 535 × 215			
rt/rt-c外观/包装尺 external/shipping size (w × d × h)	230 × 485 × 315		330 × 590 × 470	
rt-jc(不带电池)净重/总量net/gross	9/11		11.5/13.5	12

weight(kg) rt/rt-c(内置电池)净重/总量			
net/gross weight(kg) rt/rt-c(不带电池)净重/总量	12.1/13.7	31/33	31
net/gross weight(kg)	5.7/7.7	14.8/16.8	1
选件 option	远程监控适配器(snmp adapter) , 电池箱(battery cubicle)		