

济南升降平台生产厂家

产品名称	济南升降平台生产厂家
公司名称	章丘市同盛涂装设备厂
价格	.00/个
规格参数	
公司地址	山东省章丘市辛寨驻地
联系电话	86-0531-83543283

产品详情

家具烤漆房设计需按国家环保、卫生、安全生产等规范，提供喷漆所需要的洁净空气，合适的照度、温度、湿度以及均匀合理的气流等，及时将污染的空气排出。而家具烤漆房需要提供油漆烘烤所需要的均匀温度场、合适的湿度、清洁的热空气、废气排放等功能。在喷漆时，室内采用全新风送风，送风的湿度、温度不受室体底部存水的影响。The furniture lacquer room should be designed according to the national environmental protection, health, safety and other standards, providing clean air for spray paint, appropriate illumination, temperature, humidity and uniform and reasonable air flow and so on, and discharge the polluted air in time. The furniture baking room needs to provide uniform temperature field, suitable humidity, clean hot air, exhaust emission and so on. When spraying, the indoor air is supplied with fresh air. The humidity and temperature of the air supply are not affected by the water storage at the bottom of the chamber.喷漆房，顾名思义就是在一个房间里对过滤喷漆对象进行喷漆，也被叫做烤漆房。专用环境的设备，能满足涂装作业对温度、湿度、光照度、空气洁净度等要求；能将喷漆作业时产生的漆雾及有机废气限制并处理后排放，是环保型的涂装设备。Spray paint room, as the name suggests, is in a room to spray paint objects, painting is also known as baking paint room. The equipment of special environment can meet the requirements of temperature, humidity, light intensity and air cleanliness of the painting operation. It is an environmentally friendly coating equipment to restrict the paint mist and organic waste gas produced during the painting operation.烤漆时，为节省能源，热风循环使用。由于湿式家具烤漆房室体格栅下部有水，如不采取措施，挥发的水分会通过循环系统回送到室内，增加室内循环风的湿度，导致室内湿度超标。一般，夏季大气的湿度较高，而冬季湿度较低，此外湿度的高低还与地区有很大的关系。涂装标准规定，涂装设备内相对湿度应该在55%~75%之间。When painting, energy saving and hot air circulation are used. Because there is water in the lower part of the chamber of the wet furniture, if no measures are taken, the moisture of the volatilization will be returned to the room through the circulation system to increase the humidity of the indoor circulation wind, causing the indoor humidity to exceed the standard. In general, the humidity in summer is high, while the humidity in winter is low. Moreover, the humidity is also highly related to the area. The painting standard stipulates that the relative humidity in the painting equipment should be between 55%~75%.对喷漆质量要求高的场合。为保证适宜的湿度，可以在送风系统中采用加湿和除湿装置，但大风量的空气调节装置造价、占用空间大，在使用中会增加运行费用。

The situation where the quality of the spray paint is high. In order to ensure suitable humidity, the humidifier and dehumidification device can be used in the air supply system, but the cost of the air conditioning unit with large air

volume is large, and the operating cost will be increased in the use.

济南升降平台哪家便宜 济南尾气抽排设备厂家 济南尾气抽排设备安装 章丘市同盛涂装设备厂(1336 1064673), 位于济南市东郊的章丘市辛寨镇驻地。公司企业法人侯祥平自1990年起从业在涂装行业。曾在华誉、金城、华丰、兴盛等多家烤漆设备厂, 生产、安装、设计、销售和建厂。由此积累了专业经验和好多技术过硬的朋友。章丘市同盛涂装设备厂自正式注册成为独立法人企业时起, 同步与业内老朋友单位达成了兄弟合作支持单位。并吸收了大量的专业技术人员。在专业技术人员与员工的努力支持下, 基于汽车喷烤漆房、家具喷烤漆房基础上, 本厂又开发研究推出了: 各种大、中、小型, 涂装流水线、喷砂房、中央除尘和多种无尘打磨台等系列喷涂设备。我公司实力雄厚、技术先进、拥有多名高级工程师技术人员。先进的技术和专业的人才使得产品质量得到了极大的保证。“环保、节能、提高效率、改善工作环境”是我们永恒的追求目标。专业的制造技术、优良的品质、环保喷涂, 是您明智的选择! 章丘市同盛涂装设备厂联系人: 侯经理电话: 0531-83543283传真: 0531-83543283手机: 15165419777*13361064673商务QQ: 731315162 E-mail: dongshenzi@163.com地址: 山东省章丘市辛寨驻地济南汽车喷烤漆房厂家: <http://www.tstzsb.com> 中国鲁商云网: <http://www.lushangyun.com/>诺商商道系统, -专业互联网应用服务提供商: 济南网站建设www.chinanovo.net诺商商道系统, -专业互联网应用服务提供商: 济南网站建设www.cn-un.net诺商基于多年的优化经验和品牌基础推出的诺商商道系统, 诺商信息您身边的互联网专家!