

## PC AG2677 德国拜耳 清晰透明

产品名称	PC AG2677 德国拜耳 清晰透明
公司名称	上海圆高塑化科技有限公司
价格	2.00/千克
规格参数	德国拜耳:PC AG2677:德国拜耳 德国拜耳:AG2677
公司地址	上海市青浦区练塘镇章练塘路588弄15号1幢2层4区113室
联系电话	15802190887

## 产品详情

Makrolon 2865

MVR (300 ° C/1.2 kg) 10 cm<sup>3</sup>/10 min; flame retardant; UL 94V-2/1.5 mm and 3.0 mm; medium viscosity; easy release

[datasheet](#) [datasheet](#) [datasheet](#)

Makrolon 3105

MVR (300 ° C/1.2 kg) 6.0 cm<sup>3</sup>/10 min; general purpose; high viscosity; easy release

[datasheet](#) [datasheet](#)

Makrolon 3106

MVR (300 ° C/1.2 kg) 6.0 cm<sup>3</sup>/10 min; food contact quality; high viscosity

[datasheet](#) [datasheet](#)

Makrolon 3107

MVR (300 ° C/1.2 kg) 6.0 cm<sup>3</sup>/10 min; general purpose; high viscosity; UV stabilized; easy release

Makrolon 3107 MAS167

MVR (300 ° C/1.2 kg) 6.0 cm<sup>3</sup>/10 min; general purpose; high viscosity; UV stabilized; easy release

#### Makrolon 3108

MVR (300 ° C/1.2 kg) 6.0 cm<sup>3</sup>/10 min; medical devices; suitable for ETO and steam sterilization at 121 ° C; biocompatible according to many ISO 10993-1 test requirements; high viscosity

#### Makrolon 3152

MVR (300 ° C/1.2 kg) 6.0 cm<sup>3</sup>/10 min; food contact quality; high viscosity; easy release; complies with the BfR (formerly BgVV)- recommendations IX, XI and XLII abbr. the EN 71 part 3; toys

[datasheet](#) [datasheet](#)

#### Makrolon 3156

MVR (300 ° C/1.2 kg) 6.0 cm<sup>3</sup>/10 min; food contact quality; high viscosity; easy release

[datasheet](#) [datasheet](#) [datasheet](#)

#### Makrolon 3158

MVR (300 ° C/1.2 kg) 6.0 cm<sup>3</sup>/10 min; medical devices; suitable for ETO and steam sterilization at 121 ° C; biocompatible according to many ISO 10993-1 test requirements; high viscosity; easy release

[datasheet](#) [datasheet](#)

#### Makrolon 3206

MVR (300 ° C/1.2 kg) 5.0 cm<sup>3</sup>/10 min; food contact quality; high viscosity

[datasheet](#) [datasheet](#) [datasheet](#)

#### Makrolon 3207

MVR (300 ° C/1.2 kg) 4.0 cm<sup>3</sup>/10 min; general purpose; high viscosity; UV stabilized; easy release; developed for safety goggles

[datasheet](#) [datasheet](#)

#### Makrolon 3208

MVR (300 ° C/1.2 kg) 5.0 cm<sup>3</sup>/10 min; medical devices; suitable for ETO and steam sterilization at 121 ° C; biocompatible according to many ISO 10993-1 test requirements; high viscosity

[datasheet](#) [datasheet](#)

## Makrolon 3258

MVR (300 ° C/1.2 kg) 5.0 cm<sup>3</sup>/10 min; medical devices; suitable for ETO and steam sterilization at 121 ° C; biocompatible according to many ISO 10993-1 test requirements; high viscosity; easy release

[datasheet](#) [datasheet](#)

## Makrolon 6165 X

MVR (300 ° C/1.2 kg) 28 cm<sup>3</sup>/10 min; flame retardant; UL 94V-0/1.2 mm; low viscosity; easy release; LCD tv frame

[datasheet](#) [datasheet](#) [datasheet](#)

## Makrolon 6265 X

MVR (300 ° C/1.2 kg) 19 cm<sup>3</sup>/10 min; flame retardant; UL 94V-0/1.5 mm; low viscosity; easy release

[datasheet](#) [datasheet](#) [datasheet](#)

## Makrolon 6267 X

MVR (300 ° C/1.2 kg) 19 cm<sup>3</sup>/10 min; flame retardant; UL 94V-0/1.5 mm; low viscosity; UV stabilized; easy release

[datasheet](#) [datasheet](#) [datasheet](#)

## Makrolon 6455

MVR (300 ° C/1.2 kg) 12 cm<sup>3</sup>/10 min; flame retardant; UL 94V-0/3.0 mm; medium viscosity; easy release

[datasheet](#) [datasheet](#) [datasheet](#)

## Makrolon 6457

MVR (300 ° C/1.2 kg) 12 cm<sup>3</sup>/10 min; flame retardant; UL 94V-0/3.0 mm; medium viscosity; UV stabilized; easy release

[datasheet](#) [datasheet](#) [datasheet](#)

## Makrolon 6485

MVR (300 ° C/1.2 kg) 9.0 cm<sup>3</sup>/10 min; flame retardant; UL 94V-0/1.5 mm and 5VA/3.0 mm; medium viscosity; easy release

[datasheet](#) [datasheet](#) [datasheet](#)

## Makrolon 6487

MVR (300 ° C/1.2 kg) 9.0 cm<sup>3</sup>/10 min; flame retardant; UL 94V-0/1.5 mm and 5VA/3.0 mm; medium viscosity; UV stabilized; easy release

[datasheet](#) [datasheet](#) [datasheet](#)

### Makrolon 6555

MVR (300 ° C/1.2 kg) 10 cm<sup>3</sup>/10 min; flame retardant; UL 94V-0/3.0 mm; medium viscosity; easy release

[datasheet](#) [datasheet](#) [datasheet](#)

### Makrolon 6557

MVR (300 ° C/1.2 kg) 10 cm<sup>3</sup>/10 min; flame retardant; UL 94V-0/3.0 mm; medium viscosity; UV stabilized; easy release

[datasheet](#) [datasheet](#) [datasheet](#)

### Makrolon 6717

MVR (300 ° C/1.2 kg) 3.0 cm<sup>3</sup>/10 min; flame retardant; UL 94V-0/2.0 mm; high viscosity; branched; UV stabilized; easy release

[datasheet](#) [datasheet](#) [datasheet](#)

### Makrolon 8025

MVR (300 ° C/1.2 kg) 6.0 cm<sup>3</sup>/10 min; 20 % glass fiber reinforced; milled fiber; high viscosity; easy release; precision parts

[datasheet](#) [datasheet](#) [datasheet](#)

### Makrolon 8035

MVR (300 ° C/1.2 kg) 4.0 cm<sup>3</sup>/10 min; 30 % glass fiber reinforced; milled fiber; high viscosity; easy release; precision parts

[datasheet](#) [datasheet](#) [datasheet](#)

### Makrolon 8325

MVR (300 ° C/1.2 kg) 4.0 cm<sup>3</sup>/10 min; 20 % glass fiber reinforced; high viscosity; easy release

[datasheet](#) [datasheet](#) [datasheet](#)

### Makrolon 8345

MVR (300 ° C/1.2 kg) 3.0 cm<sup>3</sup>/10 min; 35 % glass fiber reinforced; high viscosity; easy release

[datasheet](#) [datasheet](#) [datasheet](#)

### Makrolon 9125

MVR (300 ° C/1.2 kg) 8.0 cm<sup>3</sup>/10 min; 20 % glass fiber reinforced; flame retardant; UL 94V-0/1.5 mm; medium viscosity; easy release

datasheet datasheet datasheet

#### Makrolon 9415

MVR (300 ° C/1.2 kg) 6.0 cm<sup>3</sup>/10 min; 10 % glass fiber reinforced; flame retardant; UL 94V-0/1.5 mm and 5VA/3.0 mm; high viscosity; easy release

datasheet datasheet datasheet

#### Makrolon 9417

MVR (300 ° C/1.2 kg) 6.0 cm<sup>3</sup>/10 min; 10 % glass fiber reinforced; flame retardant; UL 94V-0/1.5 mm and 5VA/3.0 mm; high viscosity; UV stabilized; easy release

datasheet datasheet datasheet

#### Makrolon 9425

MVR (300 ° C/1.2 kg) 5.0 cm<sup>3</sup>/10 min; 20 % glass fiber reinforced; flame retardant; UL 94V-0/1.5 mm and 5VA/3.0 mm; high viscosity; easy release

datasheet datasheet datasheet

#### Makrolon AG2677

MVR (300 ° C/1.2 kg) 12 cm<sup>3</sup>/10 min; medium viscosity; UV stabilized; easy release; automotive glazing; roof modules

datasheet datasheet datasheet

#### Makrolon AL2447

MVR (300 ° C/1.2 kg) 19 cm<sup>3</sup>/10 min; Automotive lighting; low viscosity; UV stabilized; easy release; headlamp lenses for automotive forward lighting

datasheet datasheet datasheet

#### Makrolon AL2647

MVR (300 ° C/1.2 kg) 12 cm<sup>3</sup>/10 min; Automotive lighting; medium viscosity; UV stabilized; easy release; headlamp lenses for automotive forward lighting

datasheet datasheet datasheet

#### Makrolon AX2675

MVR (300 ° C/1.2 kg) 12 cm<sup>3</sup>/10 min; medium viscosity; easy release; automotive exterior roof trim + pillar appliques; optimized and especially suitable for high-gloss surfaces with highest requirements "Piano-black"; tailored for the use in combination with Polysiloxan coatings

datasheet datasheet

## Makrolon AX2677

MVR (300 ° C/1.2 kg) 12 cm<sup>3</sup>/10 min; medium viscosity; easy release; UV stabilized; automotive exterior roof trim + pillar appliques; optimized and especially suitable for high-gloss surfaces with highest requirements "Piano-black"; tailored for the use in combination with Polysiloxan coatings

[datasheet](#) [datasheet](#)

## Makrolon DP1-1821

MVR (300 ° C/1.2 kg) 6.0 cm<sup>3</sup>/10 min; lenses, optical; high viscosity; UV stabilized; easy release; high purity

[datasheet](#) [datasheet](#) [datasheet](#)

## Makrolon EM9417

MVR (300 ° C/1.2 kg) 6.0 cm<sup>3</sup>/10 min; 10 % glass fiber reinforced; flame retardant; high viscosity; UV stabilized; easy release

[datasheet](#) [datasheet](#)

## Makrolon ET IR320

PC/IR absorber concentrate; Extrusion; high viscosity; special grade for heat absorbing ; solid sheet; multi wall sheets / profiles

[datasheet](#) [datasheet](#)