

## 德国科思创 FR3015 阻燃 FR3015

产品名称	德国科思创 FR3015 阻燃 FR3015
公司名称	上海圆高塑化科技有限公司
价格	6.00/KG
规格参数	德国科思创:PC/ABS FR3015:德国科思创 德国科思创:FR3015
公司地址	上海市青浦区练塘镇章练塘路588弄15号1幢2层4区113室
联系电话	15802190887

## 产品详情

我司主要经营：古比雪夫氮VOLGAMID 沙伯基础SABIC、德国拜耳、美国杜邦、德国BASF、日本宝理、日本三菱、日本帝人、韩国三星、美国雪佛龙菲利普斯等旗下的PA6/66/612/46、PC、POM、PPS、LCP、PPO、PBT、PET、PPA、PEI、PC/ABS、PC/PBT、PC/PET、ABS等工程塑料，美国路博润，德国拜耳，美国山都平的TPU、TPV、TPX、TPR等多种热塑性弹性体塑料。供美国苏威,日本住友，日本三井生产的PTFE、PEEK、PFA、PVDF、PEP、COC、PES等特种工程塑料。

### Makrolon 3108

MVR (300 ° C/1.2 kg) 6.0 cm/10 min; medical devices; suitable for ETO and steam sterilization at 121 ° C; biocompatible according to many ISO 10993-1 test requirements; high viscosity

### Makrolon 3152

MVR (300 ° C/1.2 kg) 6.0 cm/10 min; food contact quality; high viscosity; easy release; complies with the BfR (formerly BgVV)- recommendations IX, XI and XLII abbr. the EN 71 part 3; toys

### Makrolon 3156

MVR (300 ° C/1.2 kg) 6.0 cm/10 min; food contact quality; high viscosity; easy release

### Makrolon 3158

MVR (300 ° C/1.2 kg) 6.0 cm/10 min; medical devices; suitable for ETO and steam sterilization at 121 ° C; biocompatible according to many ISO 10993-1 test requirements; high viscosity; easy release

#### Makrolon 3206

MVR (300 ° C/1.2 kg) 5.0 cm/10 min; food contact quality; high viscosity

#### Makrolon 3208

MVR (300 ° C/1.2 kg) 5.0 cm/10 min; medical devices; suitable for ETO and steam sterilization at 121 ° C; biocompatible according to many ISO 10993-1 test requirements; high viscosity

#### Makrolon 3258

MVR (300 ° C/1.2 kg) 5.0 cm/10 min; medical devices; suitable for ETO and steam sterilization at 121 ° C; biocompatible according to many ISO 10993-1 test requirements; high viscosity; easy release

#### Makrolon 6165 X

MVR (300 ° C/1.2 kg) 28 cm/10 min; flame retardant; UL 94V-0/1.2 mm; low viscosity; easy release; LCD tv frame

#### Makrolon 6265 X

MVR (300 ° C/1.2 kg) 19 cm/10 min; flame retardant; UL 94V-0/1.5 mm; low viscosity; easy release

#### Makrolon 6267 X

MVR (300 ° C/1.2 kg) 19 cm/10 min; flame retardant; UL 94V-0/1.5 mm; low viscosity; UV stabilized; easy release

#### Makrolon 6455

MVR (300 ° C/1.2 kg) 12 cm/10 min; flame retardant; UL 94V-0/3.0 mm; medium viscosity; easy release

#### Makrolon 6457

MVR (300 ° C/1.2 kg) 12 cm/10 min; flame retardant; UL 94V-0/3.0 mm; medium viscosity; UV stabilized; easy release

#### Makrolon 6485

MVR (300 ° C/1.2 kg) 9.0 cm/10 min; flame retardant; UL 94V-0/1.5 mm and 5VA/3.0 mm; medium viscosity; easy release

#### Makrolon 6487

MVR (300 ° C/1.2 kg) 9.0 cm/10 min; flame retardant; UL 94V-0/1.5 mm and 5VA/3.0 mm; medium viscosity; UV stabilized; easy release

#### Makrolon 6555

MVR (300 ° C/1.2 kg) 10 cm/10 min; flame retardant; UL 94V-0/3.0 mm; medium viscosity; easy release

#### Makrolon 6557

MVR (300 ° C/1.2 kg) 10 cm/10 min; flame retardant; UL 94V-0/3.0 mm; medium viscosity; UV stabilized; easy release

Makrolon 6717

MVR (300 ° C/1.2 kg) 3.0 cm/10 min; flame retardant; UL 94V-0/2.0 mm; high viscosity; branched; UV stabilized; easy release

Makrolon 8025

MVR (300 ° C/1.2 kg) 6.0 cm/10 min; 20 % glass fiber reinforced; milled fiber; high viscosity; easy release; precision parts