

原装美国泰扬牌permatex80017 航空器专用3号密封胶不固化低粘度

| | |
|------|--|
| 产品名称 | 原装美国泰扬牌permatex80017 航空器专用3号密封胶不固化低粘度 |
| 公司名称 | 上海庾合实业有限公司 |
| 价格 | 1.00/卷 |
| 规格参数 | 品牌:泰扬permatex 型号:80017 产地:美国 |
| 公司地址 | 上海市金山区亭林镇兴工路225号1幢E139室 |
| 联系电话 | 021-5429 9816 13761538926 |

产品详情

Permatex Form-A-Gasket三号密封剂80017/3D

Permatex Form-A-Gasket NO.3 Sealant

不固化液态垫片密封剂/涂层/涂覆剂。是一种粘度低，可刷涂或填充于材料的小间隙部位。持续工作温度可达204 ，同时耐防冻剂、飞机燃料、强去垢剂和强润滑剂。

主要用途：

可靠的膏状密封剂和垫片涂层。缓慢干燥，表面柔软，推荐用于柔性法兰和经常承受振动的部位。耐温范围：-54 -204 。耐汽油和其它液体。符合MIL-S-45180D标准。建议用途：
密封预制垫片、油底壳垫片。

包装规格：80017 ，16盎司/瓶

Slow-drying, non-hardening brush-top sealant approved for use in aviation as well as automotive applications. Temperature range -65 ° F to 400 ° F (-54 ° C to 204 ° C); resists gasoline, oil and grease.

DIRECTIONS:

Use brush to apply a thin, even coat to each surface. Allow to air-dry a few minutes before fastening the parts into position. If thinning is necessary, add 188 proof denatured alcohol. For use on most types of gaskets, machined surfaces and screw thread connections of airplane and automobile engines.

Automobile

Suggested Applications: Close-fitting machined surfaces, sealing hoses, and solid gaskets.

Marine

Suggested Applications: Close-fitting machined surfa