

CAT猫牌2510高压柱塞泵DTRO膜配件

产品名称	CAT猫牌2510高压柱塞泵DTRO膜配件
公司名称	厦门泉球机械设备有限公司
价格	.00/个
规格参数	胜凡:哈威 SAP084:SAP084 瑞典:德国
公司地址	中国（福建）自由贸易试验区厦门片区嵩屿北三里89号2508室
联系电话	18050107839

产品详情

CAT猫牌2510高压柱塞泵DTRO膜配件

厦门泉球机械设备有限公司

刘工180 5010 7839 扣:288 167 0769

公司高质量的国际采购员和业务人员、强大的信息及物流网络、保证了公司能以非常快的速度，将可靠的产品交给您放心的使用。

美国CAT猫牌3531DHS柱塞泵

美国CAT猫牌3531HS柱塞泵

cat猫牌 57柱塞泵

猫泵660 修理包30820

CAT猫牌泵2SF22ELS高压柱塞泵

美国CAT猫牌7CP6170高压泵

CAT猫牌820高压柱塞泵

CAT猫牌1531高压柱塞泵

美国CAT猫牌34017 修理包

美国CAT猫牌31040 修理包

美国CAT猫牌33835 修理包

美国CAT猫牌33834 修理包

CAT猫牌230高压柱塞泵

CAT猫牌310高压柱塞泵

CAT猫牌311高压柱塞泵

CAT猫牌435高压柱塞泵

CAT猫牌660高压柱塞泵

CAT猫牌1537高压柱塞泵

CAT猫牌1541高压柱塞泵

CAT 2SF05SEEL高压柱塞泵

CAT猫牌3cp1140高压柱塞泵

CAT猫牌7CP6170高压柱塞泵

CAT猫牌柱塞泵1541.220特质泵

CAT猫牌7002高压柱塞泵

CAT猫牌高压泵水封（低压）58*45（3541专用）

CAT猫牌高压泵水封（高压）58*45（3541专用）

高压泵油封NOK/AC1374E

骨架油封TG 60*85*10

高压泵蓄能器ADB210/24-210B

在线增压泵BM 30.11KW

伺服电机控制阀3/8 NPT,1.4539,HH500,230V

瑞典胜凡SUNFAB柱塞泵SC108R , SCP-108R-N-DL4-L35-S0S-000

瑞典胜凡SUNFAB柱塞泵SC047R , SCP-047R-N-DL4-L35-SOS-000

瑞典胜凡SUNFAB柱塞泵SC056R , SCP-056R-N-DL4-L35-S0S-000

瑞典胜凡SUNFAB柱塞泵SC064R , SCP-064R-N-DL4-L35-S0S-000

瑞典胜凡SUNFAB柱塞泵SC084R , SCP-084R-N-DL4-L35-S0S-000

瑞典胜凡SUNFAB柱塞泵SC017R , SCP-017R-N-DL4-L35-S0S-000

瑞典胜凡SUNFAB柱塞泵SC034R , SCP-034R-N-DL4-L35-S0S-000

挪威SKIPPER DL1

挪威SKIPPER EML224 COMPACT

挪威SKIPPER EML224 Graphic

挪威SKIPPER DL850 270 kHz

Repeaters中继器

Compact Multi Repeater CD401MR-SB

DGR360 Digital Gyro Repeater

Compact Log Repeater CD401LR-SA

Digital Depth indicator SKIPPER IR301

Digital Speed Indicator SKIPPER IR300

Navigation Transducers导航传感器

挪威SKIPPER 38 kHz Transducers

挪威SKIPPER 24 kHz Transducers

挪威SKIPPER 200 kHz Transducers

挪威SKIPPER 50 kHz Transducers

Bottom Arrangement底部布置

SKIPPER offer a wide wariety of bottom arrangement.

This includes Standard Tanks, Combo Tanks, Ice protected Tanks, Sea Valves and special adapters for retrofit.

1)Tank

ETNALC Aluminium Combo Tank铝组合罐

ETNST Standard Tank标准罐

ETNSTC Combo Tank组合罐

ETNSTCL Combo Tank组合罐

ETNSTCI Ice Protected Combo Tank冰保护组合罐

ETNSTCLF Low Frequency Combo Tank低频组合罐

ETNSTCILF Ice Protected Low Frequency Combo Tank

2)Sea valve通海阀

SB-60-SA 60 mm Ball Valve Single Bottom球阀单底

DB-60-SA 60 mm Ball Valve Double 球阀双底

DB-100-SA 100 mm Gate Valve Double Bottom

TYPICAL DILUTION RATES vs. HOLE SIZE

17 1/2 " 12 1/2 " 8 1/2 "

TYPICAL FORMULATION AND PROPERTIES OF A HYDRO-FOIL GEN 1 SYSTEM

Drillwater (bbl/bbl) Base fluid

KCl (lb/bbl) Water activity and cation exchange

Caustic Soda / Potash Alkalinity control

HYDRO-ZAN (lb/bbl) Viscosifier

HYDRO-PAC LV (lb/bbl) Fluid-loss control

HYDRO-CAP (lb/bbl) Cutting encapsulator

CIRRUS CPG (v/v%) Shale stabilisation

STRATUS CPG (v/v%) Shale stabilisation

DRILL-BAR (lb/bbl) Weighting agent

Drilled Solids (lb/bbl) Drilled solids

HyPR-HIB

HyPR-CAP

HyPR-DRL

HyPR-STAR

KCl (lb/bbl) Water activity and cation exchange

NaCl (lb/bbl) Water activity and cation exchange

pH Alkalinity

HyPR-CAP (lb/bbl) Encapsulating polymer

HyPR-HIB (%) Shale and clay inhibitor

HyPR-DRL (%) Anti-accretion additive

CUMULUS CPG (%) Cloud point glyco