

移印自干氧化铝油墨

产品名称	移印自干氧化铝油墨
公司名称	上海凯贤油墨科技有限公司
价格	180.00/公斤
规格参数	品牌:欧莱斯 型号:MPL 产地:德国
公司地址	上海市嘉定沪宜公路6106号
联系电话	021-59507952-103 18201845192

产品详情

移印自干氧化铝油墨销售厂家!!!

1、本产品是采用高级进口丙烯酸树脂和高级颜料经过细制研磨加工组合而成，适用范围：各种金属喷涂面、金属喷漆面.金属表面.金属烤漆面.陶瓷、石材、电镀(含水电镀)、阳极氧化铝表面、静电喷漆面及烤漆面等制品的丝印及移印，不需加固剂，不需烘烤，即可获得优异的附着力。2、产品特性：平光、附着力佳、流平性佳、硬度强、耐酒精、耐冲压、抗刮伤、耐化学品。3、稀释剂：建议采用本公司配套专用稀释剂开油。4、固化剂：本产品无需加固剂，切勿加不配套的固化剂，会影响其效果5、油墨调配方法：搅拌时先加稀释剂10%左右稀释到印刷适合粘度。6、干燥时间：恒温表干时间自然挥发5-10分钟，实干时间在24小时以内，48小时后达最佳性能，烤箱80 烘烤15分钟性能更优。冬天视地区而定。7、使用期限：一年，过期请弃用，加了其他助剂剩余油墨不可回收。【油墨使用注意事项】1、试印确认符合要求后再批量生产。2、做好被印物的表面清除油脂及杂质工作，以促进附着效果。3、附着力、硬度、耐酸性、耐酒精性、耐化学品性、抗划伤性、耐磨性等性能的检测，需要完全固化后方可检测。4、未经允许情况下，不得将本系列油墨与其它类型油墨混用及配色。5、丝网印刷加适量拉丝膏用本公司特慢干稀释剂更适宜印刷工艺顺畅。【油墨性能检测结果】1、3M胶纸粘在画有百格的油墨表面45度角迅速拉起不脱油。2、纯度99%的酒精500G力在油墨表面来回擦拭100次无脱色。【油墨使用安全规则】1、油墨，稀释剂使用及储存时严禁烟火2、使用时注意施工场所的通风状况良好。3、尽量避免皮肤直接接触。4、本品不慎溅入口、鼻、眼、耳内，应用大量水清洗或直接求助医生。5、对本品过敏者，使用前应涂覆一层皮肤扶肤膏或戴不渗透手套。6、注意作业车间的湿度，湿度过大会影响附着力，温度高容易堵网。 Brand: but MY product name: one from a dry metal INK Numbers: 6486694 1, the product is produced with advanced import acrylic resin and senior pigment after fine grinding system combination to, suitable scope: all kinds of metal coating surface, metal paint surface. The metal surface. Metal paint surface. Ceramic, stone, electroplating (water cut electroplating), anodic alumina surface, electrostatic spray paint surface and paint surface and so on products of screen and pad printing, not needing curing agent, and does not need to bake, can obtain excellent adhesion. 2, the product characteristics: good, adhesion, classification includes glass flow ping sex good, strong hardness, resistance to alcohol resistance, stamping, resistance to scratch, resistance to chemicals. 3, thinner: this company recommended supporting special thinner, open oil. 4, curing agent: this product need not add curing

agent, do not add do not supporting the curing agent, it will affect its effect 5, printing ink allocation methods: first when stirred with thinner 10% dilution to printing for viscosity. 6, dry time: constant temperature dry time table natural volatilize 5-10 minutes, action in time within 24 hours, after 48 hours of the best performance, preheat the oven to 80 °C bake 15 minutes more optimal performance. Winter varies from area to area. 7, use period: a year, overdue please cut up, add the other additives surplus ink not recycling. 【 precautions 】 use ink 1, ShiYin confirmed again after meet the requirements of production. 2, ready to print the surface of things clear grease and impurities work to promote adhesion effect. 3 and adhesion, hardness, resistance, resistance to alcoholic acid resistance, chemical resistance character, anti-damage, wear resistance performance testing, all need to solidify rear can test. 4, without their permission, may not use the ink series with other kinds of printing ink mix and match colors. 5, screen printing and an appropriate amount of cream with the company's drawing slow dry thinners is more suitable for printing process smoothly. 【 ink performance test results 】 1, 3 M stuck in the picture has the tape's ink surface 45 degree Angle quickly pull up not to take off oil. 2 and purity, 99% alcohol 500 G force in ink surface wipe 100 times back and forth without decoloring. 【 ink use safety rules 】 1, printing ink, thinner, use and storage are prohibited during the fireworks 2, when using note the construction site of the ventilation in good condition. 3, try to avoid direct contact with the skin. 4, this product he splashed entrance, nose, eyes, ears, and application in large amounts of water cleaning or directly for help doctors. This article 5, allergy, before the use should be coated a layer of skin and skin creams or wear infiltration gloves.

6, pay attention to the work of the workshop, humidity will influence humidity adhesion, high temperature easy plugging nets.