

MBI6023GFN3 × 4通道恒流LED芯片

产品名称	MBI6023GFN3 × 4通道恒流LED芯片
公司名称	深圳市齐鑫微科技有限公司
价格	.00/个
规格参数	品牌:聚积 型号:MBI6023GFN 封装:TSSOP24
公司地址	深圳市龙岗区横岗街道六约社区埔厦新村秀新二巷5号
联系电话	075583207847 13530921237

产品详情

在线网络联系方式

深圳市齐鑫微科技有限公司

联系人：傅先生

TE：13530921237

TE: 0755-83207847

我司大量现货库存，全新原装现货，可开增值税票，欢迎新老客户惠顾！

温馨提示：产品标价为形式标价，如需购买请联系业务。

1MBI5353High Intergration 0.5~20mA @ 5V supply voltage ; 0.5~10mA @ 3.3V supply voltage专为1:32扫以下扫描屏设计 内建PWM之48通道恒流LED驱动器

2MBI535348-Channel 0.5~20mA @ 5V supply voltage ; 0.5~10mA @ 3.3V supply voltage专为1:32扫以下扫描屏设计 内建PWM之48通道恒流LED驱动器

3MBI5907LED Display Perpheral LED扫描屏专用电源切换开关

4MBI51718-Channel 5~120mA @ 5V & 3.3V supply voltage8-Bit Constant Current LED Driver with LED Error Detection and Run-Time Current Adjustment

5MBI51708-Channel 5~120mA @ 5V & 3.3V supply voltage8-Bit Constant Current LED Sink Driver with Gain Control

6MBI51698-Channel 5~120mA @ 5V & 3.3V supply voltage8-Bit Constant Current LED Sink Driver with Open/Short Circuit Detection

7MBI51688-Channel 5~120mA @ 5V & 3.3V supply vol8-Bit Constant Current LED Sink Driver

8MBI51678-Channel 3~45mA @ 5V supply voltage; 3~30mA @ 3.3V supply voltage8-Channel Constant Current LED Sink Driver

9MBI515516-Channel "0.5~20mA @ 5V supply voltage; 0.5~10mA @ 3.3V supply voltage
"专为低电源电压，1/32 扫以下扫描屏设计之内建SPWM恒流 LED驱动器

10MBI525216-Channel 0.5~20mA @ 5V supply voltage- 0.5~10mA @ 3.3V supply voltage16-Channel PWM Constant Current LED Driver dor 1:16 Time-Multiplexing Applications

11MBI515316-Channel "0.5~20mA @ 5V supply voltage;0.5~10mA @ 3.3V supply voltage
"专为1/32扫以下扫描屏设计之内建16位灰阶PWM恒流LED驱动器

12MBI515116-Channel "0.5~20mA @ 5V supply voltage; 0.5~10mA @ 3.3V supply voltage
"专为1/8扫以下扫描屏设计之内建16位灰阶PWM恒流LED驱动器

13MBI512416-Channel 1 – 25mA@VDD=5V supply voltage; 1 – 10mA@VDD=3.3V supply voltage16-Channel Constant Current LED Sink Driver

14MBI512216-Channel 1~25mA@VDD=5V ; 1~10mA@VDD=3.3V16 Channel Constant Current LED Driver with Ghosting Elimination

15MBI512016-Channel 3 – 25mA@VDD=5V ; 3 – 15mA@VDD=3.3V16-Channel Constant Current LED Sink Driver

16MBI505116-Channel "2~45mA @ 5V supply voltage; 2~30mA @ 3.3V supply voltage "16-Channel PWM Constant Current LED Driver For Time-multiplexing Applications

17MBI504516-Channel IOUT=20mA@VDS=0.2V; VDD=3.3V; IOUT=20mA@VDS=0.2V;
VDD=5.0V内建PWM之16位恒流LED驱动器

18MBI504916-Channel 3-45mA@VDD=5V;3-30mA@VDD=3.3V16-Channel SPWM Constant Current LED Sink
Driver with Diagnosis and Power Saving

19MBI504316-Channel 1~45mA具消鬼影功能、内建PWM之16位恒流LED驱动器

20MBI504216-Channel 2~45mA at 5.0V supply voltage; 2~30mA at 3.3V supply voltage16-Channel Constant
Current LED Driver With 16-bit PWM Control

21MBI504116-Channel 2~30mA16-Channel Constant Current LED Driver With 16-bit PWM Control

22MBI504016-Channel "2~60mA @ 5V supply voltage; 2~45mA @ 3.3V supply voltage "16-Channel Constant
Current LED Driver With 16-Bit PWM Control and Dot-Correction

23MBI503816-Channel 3~45mA @ 5V supply voltage; 3~30mA @ 3.3V supply voltage; 3~25mA @ 5V/3.3V
supply voltage in mSSOP(GM) package16-Channel Constant Current LED Driver with Error Detection/ Power
Saving Mode/ Current Gain

24MBI503916-Channel "8-90mA @5V supply voltage; 3-70mA @3.3V supply voltage "16-Channel Constant
Current LED Sink Driver with Silent Error Detection and Current Gain

25MBI503716-Channel "5~80mA@ 5V supply voltage; 3~60mA@ 3.3V supply voltage "16-Channel Constant
Current LED Driver With Silent Error Detection and Power Saving Modes

26MBI503516-Channel IOUT=20mA@VDS=0.2V; VDD=3.3V; IOUT=20mA@VDS=0.2V;
VDD=5.0V16-Channel Constant Current LED Driver with Low Knee Voltage

27MBI503416-Channel 3-45mA @ 5V supply voltage;3-30mA @ 3.3V supply voltage16-Channel Constant
Current LED Sink Driver with Compulsory Open-circuit Detection and Current Gain

28MBI503116-Channel "8~ 90mA@ 5V supply voltage; 3~70mA@ 3.3V supply voltage "16-Channel Constant
Current LED Driver With 12-Bit PWM Control

29MBI503016-Channel "8~ 90mA@ 5V supply voltage; 3~70mA@ 3.3V supply voltage "16-Channel Constant
Current LED Driver With 16-Bit PWM Control

30MBI502916-Channel 5-90mA @ 5V supply voltage16-Channel Constant Current LED Sink Driver with Error Detection and Current Adjustmen

31MBI502816-Channel 5-90mA @ 5V supply voltage16-Channel Constant Current LED Sink Driver with Current Gain Control

32MBI502716-Channel 5-90mA @ 5V supply voltage16-Bit Constant Current LED Sink Driver with Open-/Short-Circuit Detection

33MBI502616-Channel 5-90mA @ 5V supply voltage16-Channel Constant Current LED Sink Driver

34MBI502416-Channel 1-45mA@ 5V supply voltage; 1-30mA@ 3.3V supply voltage16-Channel Constant Current LED Sink Driver

35MBI502016-Channel 3 – 30mA@VDD=5V ; 3 – 15mA@VDD=3.3V16-Channel Constant Current LED Sink Driver

36MBIA04316-Channel 2~45mA在3.3伏特操作电压 ; 在5.0伏特操作电压内建PWM之16位恒流LED驱动器

37JXI502016-Channel 3 – 45mA@VDD=5V supply voltage; 3 – 30mA@VDD=3.3V supply voltage16-Channel Constant Current LED Sink Driver

38MBI536824-Channel 10 -60 mA8-channel x 3 Constant Current LED Sink Driver

39MBI532424-Channel 1~35mA @ 5V supply voltage;1~25mA @ 3.3V supply voltage3x8-channel Constant Current LED Driver with Com