

# 金属喷塑面油墨金属喷塑面油墨厂家

产品名称	金属喷塑面油墨金属喷塑面油墨厂家
公司名称	上海凯贤印刷科技有限公司
价格	180.00/公斤
规格参数	型号:S90 品牌:OLS 产地:德国
公司地址	上海市嘉定区外冈西冈身路777号
联系电话	021-59507952 18074309897

## 产品详情

具有高色泽、高色彩、高遮盖力、高稳定性、耐酒精及耐磨擦之特点。印刷：丝印移印均可。表干及实干时间：表干时间自然挥发5-10分钟；实干时间在24小时以内。稀释及清洗：SV3慢干开油水、UVK1（移印开油水）同时可使用718洗网水清洗。测试方法（完全干燥后）：1、3m胶纸粘在画有百格的油墨表面，45度角迅速拉起不脱油；2、纯度99%的工业酒精，一千克砝码用棉布包住在油墨表面，以水平力来回拉200次无脱色；3、耐磨：橡皮擦500g力水平来回擦500次。使用方法：1、使用前应充分搅拌，用后随时封闭；2、搅拌时加开油水10-15%，稀释到印刷粘度；3、网板塞网时可用洗网水清洗；4、不得与其它类型油墨混合使用。注意事项：1、塑胶材料的外观相似，但可能是不同的材料，客户需试印确定其符合要求后，再批量印刷；2、在移印过程中，如出现拉丝或散开，可适当加入一些慢干膏即可；3、环境温度过高，将会影响油墨原有质量；4、根据气候变化，请远离火源，阴暗环境下存放。 Oles MPE Plating Ink MPE plating strengthening series ink characteristic s : mainly used in plating surface, enhanced surface, vacuum plating surface. PU surface. UV surface and other materials, with a high color, high color, high covering power, high stability, high alcohol and rub characteristics. Printing: screen printing can be. Surface drying and drying time: surface dry time natural volatile 5-10 minutes; work time within 24 hours. Dilution and cleaning: SV3 slow dry open water, UVK1 ( printing open water) can be simultaneously used 718 washing network water cleaning. Test method ( completely dry ):

- 1, 3M gummed paper in the paintings of the surface of the ink, 45 degree angle quickly pulled off the oil;
- 2, 99% of the purity of industrial alcohol, one kilogram of weight of cotton pack in the ink surface, with a horizontal force pulling back and forth 200 times without decolorization;
- 3: oak, wear resistance eraser 500g force level brush back and forth 500 times.

Usage: 1, use should be fully stirred, use at any time after the closure; 2, add water mixing 10-15%, diluted to 3, screen printing viscosity; the plug is available when washing network water cleaning; 4, not with other types of ink mixing. Note: 1, the plastic material similar in appearance, but may be of different materials, customers need to try to determine its requirements, and then batch printing; 2, in the printing process, such as drawing or spread out, may be appropriate to add some slow dry plaster; 3, the ambient temperature is too high, will affect the quality of the original ink; 4,

according to climate change, please stay away from fire