

# HIWIN上银滑块MGW15H导轨

产品名称	HIWIN上银滑块MGW15H导轨
公司名称	青岛鹏诚达机电设备有限公司
价格	214.00/个
规格参数	品牌:HIWIN上银滑块 型号:上银滑块MGW15H 产地:中国台湾
公司地址	青岛市市北区遵化路27号保利石榴街区1号楼716室
联系电话	86-0532-86025666 05328025666 18363936903

## 产品详情

HIWIN上银滑块山东代理, MGW15H线性导轨, 上银滑块MGW15H

### 选用准则

#### 1.使用条件设定

应用之设备 行程

内部空进之限制 运行速度、加速度

精度之要求 使用频率

刚性之要求 使用环境

负荷方式 要求寿命年限

#### 2.选用系列产品

HG系列：磨床、铣床、车床、钻床、综合加工机、放电加工机、搪床、线切割机、精密量测仪器、木工机器、搬运机器、运送装置。

EG系列：产业自动化机器、半导体机械、雷射雕刻机、包装机器。

MGN/MGW系列：印表机、机器手臂、电子仪器设备、半导体设备。

### 3.选用精度等级

C,H,P,SP,UP等级视设备精度要求而定

### 4.假定滑块尺寸及数目

依经验选用

负荷状态

若与滚珠螺杆配合使用，则使用之直线导轨规格与螺杆外径相似，如螺杆外径为35mm则选用HG35规格

### 5.计算滑块负荷

参照负荷计算例计算单个滑块等效负荷

确认选用之直线导轨静安全系数应超过静安全系数使用表所列之值

### 6.选择预压力

依刚性要求及安装面精度选用

### 7.确认刚性

参照刚性表计算变形量

提高预压力，加大选用尺寸或滑块数以提高刚性

### 8.计算使用寿命

依使用速度、频率计算寿命距离要求

依寿命公式计算选定直线导轨之寿命距离

### 9.润滑选用

润滑剂选用，依设备需求可选择润滑脂、润滑油或特殊润滑剂润滑定期注入润滑脂或自动供油

滚珠型高组装HG系列

HGW15CC HGH15CA HGW20CC HGH20CA HGW25CC HGH25CA HGW30CC HGH30CA

HGW35CC HGH35CA HGW45CC HGH45CA HGW55CC HGH55CA HGW65CC HGH65CA

重负载HGH20HA HGW20HC HGH25HA HGW25HC HGH30HA HGW30HC HGH35HA HGW35HC

HGH45HA HGW45HC HGH55HA HGW55HC HGH65HA HGW65HC及相对应导轨现货供应

低阻装EG系列

EGH15CA EGW15CA EGH20CA EGW20CA EGH25CA EGW25CA EGH30CA EGW30CA

### 紧凑型

EGH15SA EGW15SA EGH20SA EGW20SA EGH25SA EGW25SA EGH30SA EGW30SA及相关

导轨现货供应

### 微型轨道MG系列

MGN5C MGN7C MGN9C MGN12C MGN15C重负载 MGN7H MGN9H MGN12H MGN15H

### 加宽型

MGW5C MGW7C MGW9C MGW12C MGW15C 重负载 MGW7H MGW9H MGW12H MGW15H

### 滚柱型RG系列

RGH25CA RGW25CC RGH30CA RGW30CC RGH35CA RGW35CC RGH45CA RGW45CC

RGH55CA RGW55CC RGH65CA RGW65CC

重负载 RGH25HA RGW25HC RGH30HA RHW30HC

RGH35HA RGW35HC RGH45HA RGW45HC RGH55HA RGW55HC RGH65HA RGW65HC及相对

应导轨现货

### 静音式QH系列

QHH15CA QHW15CA QHH20CA QHW20CA QHW25CA QHH25CA QHH30CA QHW30CA

QHW35CA QHH35CA QHH45CA QHW45CA

重负载QHH30HA QHW30HA QHW35HA QHH35HA QHH45HA QHW45HC及相对应的导轨现货

### 中组装HGL系列

HGL15CA HGL25CA HGL30CA HGL35CA HGL45CA HGL55CA HGL65CA

### 重负载

HGL25HA HGL30HA HGL35HA HGL45HA HGL55HA HGL65HA

### 宽幅型WE系列

WEH17CA WEH21CA WEH27CA WEH35CA WEH50CA

WEW17CC WEW21CC WEW27CC WEW35CC WEW50CC