

# 日本GS蓄电池PXL12180价格

产品名称	日本GS蓄电池PXL12180价格
公司名称	北京弗纳德电源设备有限公司
价格	1.00/只
规格参数	日本GS蓄电池:日本GS蓄电池 PXL12180:PXL12180
公司地址	昌平区回龙观镇发展路8号院
联系电话	15801019246

## 产品详情

### 日本GS蓄电池

型号	电压(V)	容量 20小时率(Ah)	外观尺寸(mm)		高度	总高	重量约(kg)	端子 型式	位置
			长度	宽度					
PE6V1.2	6	1.2	97 ± 1	24 ± 1	51 ± 1	55 ± 2	0.30	F1	J
PE6V3A	6	3	134 ± 1	34 ± 1	60 ± 1	64 ± 2	0.68	F1	C
PE6V3.2	6	3.2	66 ± 1	33 ± 1	118 ± 1	124 ± 2	0.75	F1	K
PE6V4.5	6	4.5	70 ± 1	47 ± 1	102 ± 1	106 ± 2	0.89	F1,F2	A
PE6V7.2	6	7.2	151 ± 1	34 ± 1	94 ± 1	98 ± 2	1.38	F1,F2	C,G
PE6V8	6	8	98.5 ± 1	56.5 ± 1	118 ± 2	118 ± 2	1.52	F1	E,H
PE6V12	6	12	151 ± 1	51 ± 1	94 ± 1	98 ± 2	2.10	F1,F2	C
PE12V1.2	12	1.2	97 ± 1	42 ± 1	51 ± 1	55 ± 2	0.55	F1	F
PE12V2.7	12	2.7	79 ± 1	55 ± 1	102 ± 1	106 ± 2	1.10	F1	G
PE12V3A	12	3	134 ± 1	67 ± 1	61 ± 1	65 ± 2	1.30	F1	D
PE12V4.5	12	4.5	90 ± 1	70 ± 1	102 ± 1	106 ± 2	1.75	F1,F2	B
PE12V4.5	12	4.5	90 ± 1	70 ± 1	102 ± 1	106 ± 2	1.75	F1,F2	G
A									
PE12V7.2	12	7.2	151 ± 1	65 ± 1	94 ± 1	98 ± 2	2.65	F1,F2	D
PE12V12	12	12	151 ± 1	98 ± 1	94 ± 1	F2(98 ± 2), B1(104.5 ± 2)	4.35	F2,B1-a	D,M
PE12V17	12	17	181 ± 1	76 ± 1	167 ± 1	167 ± 1	6.70	B1-a	O
PE12V18	12	18	181 ± 1	76 ± 1	167 ± 1	167 ± 1	6.70	B1-b	O
PE12V24A	12	24	175 ± 1	166 ± 1	125 ± 1	125 ± 1	9.40	B1-a	L
PE12V26A	12	26	175 ± 1	166 ± 1	125 ± 1	125 ± 1	9.40	B1-a	L
PE12V40	12	40	196 ± 2	163 ± 2	174 ± 2	174 ± 2	14.00	B2-a	O

型号	电压(V)	容量 20小时率( Ah)	外观尺寸(mm)			总高	重量约(kg )	端子 型式	位置
			长度	宽度	高度				
PX06090	6	8	151 ± 1	34 ± 1	94 ± 1	101 ± 2	1.45	F2	C
PX12050	12	5	90 ± 1	70 ± 1	102 ± 1	109 ± 2	1.90	F2	G
GT12080- HG	12	8	151 ± 1	65 ± 1	94 ± 1	101 ± 2	2.60	F2	I
PX12090	12	8	151 ± 1	65 ± 1	94 ± 1	101 ± 2	2.85	F2	D
PX12120	12	12	151 ± 1	98 ± 1	94 ± 1	101 ± 2	4.40	F2	D
PX12170	12	17	181 ± 1	76 ± 1	167 ± 1	167 ± 1	6.70	B1	O
TPH12080	12	8	151 ± 1	65 ± 1	94 ± 1	98 ± 2	2.85	F2	D
TPH12100	12	10	151 ± 1	65 ± 1	112 ± 1	116 ± 2	3.50	F2	D

型号	电压(V)	容量 20小时率( Ah)	外观尺寸(mm)			总高	重量约(kg )	端子 型式	位置
			长度	宽度	高度				
PXL06090	6	7.2	151 ± 1	34 ± 1	94 ± 1	101 ± 2	1.45	F2	C
PXL12050	12	5	90 ± 1	70 ± 1	102 ± 1	109 ± 2	1.90	F2	G
PXL12072	12	7.2	151 ± 1	65 ± 1	94 ± 1	101 ± 2	2.75	F2	D
PXL12090	12	7.2	151 ± 1	65 ± 1	94 ± 1	101 ± 2	2.85	F2	D
PXL12120	12	11	151 ± 1	98 ± 1	94 ± 1	101 ± 2	4.40	F2	D
PXL12180	12	18	181 ± 1	76 ± 1	167 ± 1	167 ± 1	6.70	B1-b	O

【GS PORTALAC BATTERY】 【日本電池株式會社】 【日本GS電池】 日本原装进口

Welcome To JAPAN STORAGE BATTERY CO.,LTD.

JAPAN STORAGE BATTERY CO.,LTD. is an American subsidiary of GS Yuasa Corporation of Japan, the world leader in motorcycle and standby storage batteries, which serves the power sports, telecommunications, UPS, and the emergency lighting markets. JAPAN STORAGE BATTERY CO.,LTD. recently entered the renewable energy photovoltaic and storage market in North America. GS Battery ' s headquarters ' in Roswell, Georgia, is the home of the first commercial solar installation with batteries in the state of Georgia.

GS Yuasa Corporation ' s businesses include the manufacture and supply of batteries, power supply systems, lighting equipment, specialty and other electrical equipment. In order to allow us to offer products and services that best meet the needs of our customers around the world, we are continually making modifications and improvements to our R&D, manufacturing, and distribution systems, ensuring that they have a global focus.

As technological innovation accelerates in the energy and environmental fields, new values are required in the storage battery industry. These challenges serve to motivate us and we continually advance with new products and new technologies into the changing world before us. Our corporate slogan, " Next to you " , is where we seek to be as we work towards meeting the needs of the changing world.

We give 100% to making your life richer, to turning your dreams into reality, and to help build a common future for everyone.

日本GS电池公司的业务包括电池，电源系统，照明设备，专业及其它电气设备的制造和供应。为了让我们能够提供的产品和服务\*\*能满足我们的客户在世界各地需要的服务，我们不断地进行修改和改进我们的研发，制造和分销系统，以确保他们有一个全球关注的焦点。

由于技术创新在能源和环境领域的加快，新的值是必需的蓄电池产业。这些挑战可以推动我们，我们不断推出新产品和新技术推进到不断变化的世界在我们面前。我们的企业口号，“你旁边”，是我们努力做到，因为我们努力满足不断变化的世界的需要。

我们给100%让您的生活更丰富，给你的梦想变成现实，并帮助每个人建立一个共同的未来。

## Model Description

PE - Standard

PX - High rate discharge type

PXL - high rate discharge Long Life

GS Battery 's VRLA industrial batteries have exceeded customer 's expectations since they were introduced to the battery market over 30 years ago. Designed to provide long life in a wide range of applications, these batteries are available in standard, long life and super long life models, offering best in class performance and an outstanding value.

Capacities range from 1.2 ah up to over 150 ah and are supported with a full line of connectors, harnesses and installation kits. Applications include telecommunications, computer back-up, emergency lighting, automotive and security back-up models. Our applications department is the best in the industry!