

PVC板材数控开料机PP板材数控开料机

| | |
|------|---------------------------------------|
| 产品名称 | PVC板材数控开料机PP板材数控开料机 |
| 公司名称 | 东莞市麦克德自动化设备有限公司 |
| 价格 | 58000.00/台 |
| 规格参数 | 品牌:麦克德 型号:MKD-1532-P 系统:一体机控制系统 |
| 公司地址 | 大岭山镇沿河东街49号 |
| 联系电话 | 0769-81878981 18002796171 |

产品详情

机型解读 Model interpretation

Mkd-1530-P系列设备是一款电镀设备PP\PVC板材切割开料设备，Y轴使用挡板，以免生锈和人员撞伤。本款设备配有大功率真空泵，方便快捷固定板材。

Mkd-1532-P series equipment is an electroplating equipment PP\PVC plate cutting equipment, Y shaft using the baffle, so as to avoid rust and personnel. This equipment is equipped with high-power vacuum pump, which is convenient and fast for fixing plates.

性能特点 Performance features

1.钢架焊接震动时效及热处理加硬，经CNC平整加工，确保机床刚性耐用不变形；

The steel frame is welded with vibration aging and heat treatment hardening, which is processed by CNC flat to ensure rigidity, durability and non-deformation of the machine tool

2.进口高精度导轨、齿条，原厂驱动及电机，机器运行稳定、速度快、工作噪音小；

Imported high-precision guide rail and rack, original factory drive and motor, stable operation, fast speed and low working noise

3.采用品牌电器元器件、屏蔽电线电缆，使其故障率极低。

The use of branded electrical components and shielded wires and cables makes the failure rate extremely low

适用行业Apply to industry

电镀设备雕刻机广泛应用于电镀设备、实验设备PP、PVC塑胶板材开料切割，电镀槽开料、耐腐蚀板材数控开料，齿轮切割，人造石切割、雕刻加工等。

Electroplating equipment engraving machine is widely used in electroplating equipment, experimental equipment PP, PVC plastic sheet cutting, electroplating trough opening, corrosion resistant sheet CNC opening, artificial stone cutting, engraving and so on.

技术参数Technical parameters

设备型号Equipment model MKD-1530-P

工作行程 (X、Y、Z) Work schedule (X, Y, Z) 1520*3200*150mm

平台尺寸Platform size 1650*3200mm

空程速度Idle speed 15000mm/min

加工速度Processing speed 1000mm/min

主轴转速Spindle speed 24000rpm

主轴功率Spindle power 5.5KW

重复定位精度Repeated positioning accuracy 0.025(300mm)

加工精度The machining accuracy 0.08(300mm)

出力轴The output shaft 雷赛高速步进电机(可选伺服)

运动配置 (龙门动)

Sports configuration (gantry movement)

X、Y高精密斜齿，台湾上银25导轨 (银泰)

X, Y high precision helical teeth,

Taiwan HIWIN (PMI) 25 guide linear

Z台湾TBI丝杆，台湾上银25导轨 (银泰)

Z Taiwan TBI ball screw,

Taiwan HIWIN (PMI) 25 guide linear

工作电源Working power supplyAC-220V/380V5% 50~60Hz

整机重量whole machine weight2500KG

外形尺寸Overall dimensions3700*2500*1680