

# 石材雕刻机 功德碑雕刻机 大理石雕刻机

|      |   |
|------|---|
| 产品名称 | 石材雕刻机 功德碑雕刻机 大理石雕刻机                     |
| 公司名称 | 东莞市麦克德自动化设备有限公司                         |
| 价格   | 46800.00/台                              |
| 规格参数 | 品牌:麦克德<br>型号:MKD-1325-S<br>系统:石材雕刻机专用系统 |
| 公司地址 | 大岭山镇沿河东街49号                             |
| 联系电话 | 0769-81878981 18002796171               |

## 产品详情

### 机型解读 Model interpretation

Mkd-1325-S系列设备是一款重型石材雕刻机设备，三轴配有防尘罩设计，优先防止加工过程中水、粉尘、杂物等飞溅到轨道和其他传动件上，以免生锈和人员撞伤。

Mkd-1325-S series equipment is a heavy stone engraving machine equipment, three shaft equipped with dust cover design, priority to prevent the processing process of water, dust, debris and other spattering to track and other transmission parts, so as to avoid rust and personnel.

### 性能特点 Performance features

1. 钢架焊接震动时效及热处理加硬，经CNC平整加工，确保机床刚性耐用不变形；

The steel frame is welded with vibration aging and heat treatment hardening, which is processed by CNC flat to ensure rigidity, durability and non-deformation of the machine tool

2. 进口高精度导轨、齿条，原厂驱动及电机，机器运行稳定、速度快、工作噪音小；

Imported high-precision guide rail and rack, original factory drive and motor, stable operation, fast speed and low working noise

3. 采用品牌电器元器件、屏蔽电线电缆，使其故障率极低。

The use of branded electrical components and shielded wires and cables makes the failure rate extremely low

## 适用行业 Apply to industry

石材雕刻机广泛应用于石材刻字、石材浮雕，瓷砖雕刻，瓷砖背景墙、石材背景墙，幕墙，墓碑，功德碑，石材艺术品加工等。

Stone engraving machine is widely used in stone carving, stone relief, ceramic tile engraving, tile background wall, stone background wall, curtain wall, tombstone, stele, stone art processing, etc.

## 技术参数 Technical parameters

设备型号 Equipment model MKD-1325-S

工作行程 (X、Y、Z) Work schedule (X, Y, Z) 1320\*2530\*180mm

平台尺寸 Platform size 1350\*2600mm

空程速度 Idle speed 15000mm/min

加工速度 Processing speed 8000mm/min

主轴转速 Spindle speed 24000rpm

主轴功率 Spindle power 3.2KW

重复定位精度 Repeated positioning accuracy 0.025(300mm)

加工精度 The machining accuracy 0.08(300mm)

出力轴 The output shaft 雷赛高速步进电机

## 运动配置 (龙门动)

Sportsconfiguration (gantry movement)

X、Y高精密斜齿，台湾上银25导轨 (银泰)

X, Y high precision helical teeth,

Taiwan HIWIN ( PMI ) 25 guide linear

Z台湾TBI丝杆，台湾上银25导轨 (银泰)

Z Taiwan TBI ball screw,

TaiwanHIWIN ( PMI ) 25 guide linear

工作电源 Working power supply AC-220V/380V5% 50~60Hz

整机重量 whole machine weight 2500KG

外形尺寸 Overall dimensions 3000\*2150\*1680