

GRACO Python Pumps

产品名称	GRACO Python Pumps
公司名称	上海华饰机电涂装设备有限公司
价格	1.00/个
规格参数	
公司地址	上海市松江区泖港镇中南路7号B - 253
联系电话	021-63811387 13621819046

产品详情

GRACO Python Pumps

Python Pumps Pneumatic Operated Chemical Injection Pumps

Protection from corrosion, plugging and freezing

Graco Python pneumatic chemical injection pumps are the right solution for injecting chemicals at well sites and pipelines to protect them from corrosion, plugging and freezing. Python pumps offer features critical to the oil and gas industry:

Ideal for applications that require a pump to operate in an explosion proof environment

These chemical pumps run on regulated natural gas or compressed air

Uses half the air consumption of other pumps in the market

Easy to operate

Lowest out of pocket cost

Extreme duty plungers, seals, and timing valve are designed for up to two years of operation before replacement

The Python is designed to operate in environments from -40 ° F to 175 ° F (-40 ° C to 79 ° C). They have 316 SST wetted parts, plus they ' re sealed against water and dust.

Ultra precision stroke adjustment between to 1 inch (6.4 to 25.4 mm) ensures accurate injection rates.

Reduced fugitive methane emissions.

HNBR, FKN, FKM ETP, and FFKM plunger packings and check valve seals can handle some of the most aggressive chemicals.

Pump cycle rate remains constant regardless of system back pressure.

Fluid outlet size (1/8 " & 3/16 " plungers only)	HiP HF4
Prime/bleed size (1/4 " , 3/8 " , 1/2 " , 5/8 " , & 3/4 " plungers only)	10-32 UNF
Prime/bleed size (1/8 " & 3/16 " plungers only)	1/16 in. npt(f)
Pneumatic inlet size	1/8 in. npt(f) (1/4 npt(f) adapter included)
Pneumatic outlet size (exhaust recovery)	1/8 in. npt(f)

Materials of Construction

Pump/Check Valve Seal Material	See instruction manual. All other packing materials are PEEK and PTFE unless otherwise.
Wetted Parts	See instruction manual. All other materials are 316 stainless steel unless otherwise.