

电镀通风管道开料机PVCPP板材数控雕刻机

产品名称	电镀通风管道开料机PVCPP板材数控雕刻机
公司名称	东莞市麦克德自动化设备有限公司
价格	68000.00/台
规格参数	水冷主轴5.5KW24000rpm:5.5KW变频器 伺服驱动器:伺服电机 一体机系统:包安装培训质保一年
公司地址	大岭山镇沿河东街49号
联系电话	0769-81878981 18002796171

产品详情

1. 钢架焊接震动时效及热处理加硬，经CNC平整加工，确保机床刚性耐用不变形；

The steel frame is welded with vibration aging and heat treatment hardening, which is processed by CNC flat to ensure rigidity, durability and non-deformation of the machine

tool

2. 进口高精度导轨、齿条，原厂驱动及电机，机器运行稳定、速度快、工作噪音小；

Imported high-precision guide rail and rack, original factory drive and motor, stable operation, fast speed and low working noise

3. 采用品牌电器元器件、屏蔽电线电缆，使其故障率极低。

The use of branded electrical components and shielded wires and cables makes the failure rate extremely low

机型解读Model interpretation

Mkd-1530-P系列设备是一款电镀设备PP\PVC板材切割开料设备，Y轴使用挡板，以免生锈和人员撞伤。本款设备配有大功率真空泵，方便快捷固定板材。

Mkd-1532-P series equipment is an electroplating equipment PP\PVC plate cutting equipment, Y shaft using the baffle, so as to avoid rust and personnel. This equipment is equipped with high-power vacuum pump, which is convenient and fast for fixing plates.

性能特点Performance features

1. 钢架焊接震动时效及热处理加硬，经CNC平整加工，确保机床刚性耐用不变形；

The steel frame is welded with vibration aging and heat treatment hardening, which is processed by CNC flat to ensure rigidity, durability and non-deformation of the machine tool

2. 进口高精度导轨、齿条，原厂驱动及电机，机器运行稳定、速度快、工作噪音小；

Imported high-precision guide rail and rack, original factory drive and motor, stable operation, fast speed and low working noise

3. 采用品牌电器元器件、屏蔽电线电缆，使其故障率极低。

The use of branded electrical components and shielded wires and cables makes the failure rate extremely low

适用行业Apply to industry

电镀设备雕刻机广泛应用于电镀设备、实验设备PP、PVC塑胶板材开料切割，电镀槽开料、耐腐蚀板材数控开料，齿轮切割，人造石切割、雕刻加工等。

Electroplating equipment engraving machine is widely used in electroplating equipment, experimental equipment PP, PVC plastic sheet cutting, electroplating trough opening, corrosion resistant sheet CNC opening, artificial stone cutting, engraving and so on.

技术参数Technical parameters

设备型号

Equipment model

MKD-1530-P

工作行程 (X、Y、Z)

Work schedule (X, Y, Z)

1520*3230*150mm

平台尺寸

Platform size

1650*3200mm

空程速度

Idle speed

15000mm/min

加工速度

Processing speed

1000mm/min

主轴转速

Spindle speed

24000rpm

主轴功率

Spindle power

5.5KW

重复定位精度

Repeated positioning accuracy

± 0.025(300mm)

加工精度

The machining accuracy

± 0.08(300mm)

出力轴

The output shaft

雷赛高速步进电机(可选伺服)

运动配置 (龙门动)

Sportsconfiguration (gantry movement)

X、Y高精密斜齿，台湾上银25导轨 (银泰)

X, Y high precision helical teeth,

Taiwan HIWIN (PMI) 25 guide linear

Z台湾TBI丝杆，台湾上银25导轨 (银泰)

Z Taiwan TBI ball screw,

TaiwanHIWIN (PMI) 25 guide linear

工作电源

Working power supply

AC-220V/380V ± 5% 50~60Hz

整机重量

whole machine weight

2500KG

外形尺寸

Overall dimensions

3700*2500*1680

公司介绍

东莞市麦克德自动化设备有限公司——是一家只专注于数控设备及光纤切割设备的研发、生产、销售、培训、售后服务一体化的企业。凭借匠心团队不懈努力，开拓进取，掌握数控设备自主核心技术，服务广大客户。

公司主要生产铜铝板精雕机、铝单板切割机、CNC金属模具精雕机，光纤金属切割机、多工序木工雕刻机、背景墙石材雕刻机、玉石雕刻机、四轴/五轴加工中心、大型非标自动化/数控设备等系列产品。秉承尊重客户、尊重事实、尊重科学的发展理念，以品质质量稳定，运行性能可靠，守诚信、重承诺而得到广大客户的信任与支持。产品广泛运用与铜铝板门花雕刻，铝板别墅大门雕刻，飞机蒙皮、大型外墙铝单板切割，五金模具、塑胶模具、手板模具雕刻，治具、夹具工装雕刻切割，木工、木门、石材刻字、瓷砖背景墙雕刻等行业。不断进取、不断创新、为客户提供优质的品质而努力。公司一直与国内外先进技术、高新技术厂家沟通，研发，拥有先进的生产工艺和生产技术，掌握核心技术。拥有经验丰富的专业技术工程师和设计师，在设备故障、培训、工艺制作方面积累了丰富的经验，随时为客户提供有效、贴心、优质的售后服务。成为雕刻机行业领先品牌。

联系方式

联系人：温先生

移动电话：180 0279 6171

地 址：东莞市大岭山镇沿河东街49号