

艾思瑞单座陶瓷阀，单座陶瓷球阀，SSZ陶瓷阀

产品名称	艾思瑞单座陶瓷阀，单座陶瓷球阀，SSZ陶瓷阀
公司名称	艾思瑞流体控制有限公司
价格	.00/套
规格参数	SSZ ceramic valve:SSZ CGV500
公司地址	中国 四川 成都市 武侯区 西部智谷D区
联系电话	18008053947

产品详情

特种阀门&部件

艾思瑞流体控制有限公司（SEVERE SERVICE ZIRCONIA-品牌 SSZ）公司网站：www.sszvalve.com

公司位于美丽的天府之国——成都.双流，专业从事特种材料技术研究和陶瓷阀门研发生产制造销售，是一家领先的工业特种材料阀门&部件设备制造商。

艾思瑞一直在加大对纳米陶瓷材料的研发力度，探索陶瓷材料性能的更高水平，不断寻求磨损和腐蚀条件的**解决方案，材料有Si₃N₄、SSiC、ZrO₂、SSZ-T1（特种超性能陶瓷）等多种材料可选。2018年和中科院建立陶瓷材料联合研发战略合作，已取得CE/SIL/ISO/BV等认证。SSZ产品1100“零泄漏”陶瓷球阀系列、2100“双向密封调节陶瓷球阀”系列、5000“特种陶瓷管件”CPF系列能抗击急剧研磨和腐蚀工况是公司拳头产品，产品还有陶瓷旋转阀、角阀，无腔体阀、滑板阀、盘阀。公司制造产品口径/压力/温度可达12“/ANSI 900Lb/560。艾思瑞产品覆盖各行业，高质量的产品与服务为其化工、石化、石油、电力、纸浆、造纸等领域用户提供特种阀门和部件，长生命周期的质量保障给客户带来经济效益。

其中多晶硅行业业绩如下：

通威/永祥、大全、新特、东方希望、亚硅、丽豪、晶诺、瑞能、云冶、神硅、东立、康博等业绩提供过产品和服务。

公司距成都天府机场30分钟，欢迎有机会莅临成都工厂考察指导！

艾思瑞流体控制有限公司 (SEVERE SERVICE ZIRCONIA- SSZ)

艾思瑞流体控制有限公司位于美丽的天府之国——成都，从事先进特种材料和纳米陶瓷产品研发与制造的公司，也是行业特种陶瓷材料阀门及部件制造商。公司以SSZ -SEVERE SERVICE ZIRCONIA Company多年陶瓷研发与应用经验为依托，针对中国市场的供应链集中优化，更好地服务于中国客户。艾思瑞一直加大对纳米陶瓷材料的研发力度，探索陶瓷材料的更高性能，不断寻求磨损和腐蚀工况的解决方案。其中SSZ产品1100系列、2100系列等是公司的核心产品，应用覆盖全球，业务包括化工、石化、石油、电力、纸浆、造纸等领域，获得了业内一致好评，也为客户带来了巨大的经济效益，提升安全生产水平，未来，我们将竭尽所能与所有客户共铸明天。

Main parameter :

size : 1/2" ——8"

Temperature : -29 ° C——220 ° C

Pressur : class300#,class600#

Connection mode : ASME B16.5RF

Length ; ASME B16.10

Standard : ASME B16.34

test : API 598

ceramic : Al₂O₃、 ZrO₂ 、 Si₃N₄、 SiC

valve

stem : 316、 17-4PH , Nickel 、 Inconel 、 Titanium Zirkonium 、 Tantalium、 HC、 HB

Valve body : WCB

Material cast steel (ZG 230 - 450), cast stainless steel (ZG 1Cr18Ni9 Ti, ZG 1Cr18Ni 12 Mo 2 Ti), etc

Upper valve cover common type upper valve cover: - 40 ~ + 230 fin type upper valve cover: + 230 ~ + 450

gland type bolt pressing type

Filling material V - shaped PTFE filler, impregnated PTFE asbestos filler, asbestos compression packing, graphite filler

In - valve assembly

Valve core type single seat plunger type valve core

Flow characteristics equal percentage characteristics and linear characteristics

Stainless Steel Surfacing Stellar Alloy, Titanium and Corrosion Resistant Alloy, etc

actuator

Type ZMX (A / B) Pneumatic Film Actuator

Diaphragm material nitrile rubber clip nylon cloth

Spring range 20 ~ 100, 40 ~ 200, 80 ~ 240 kpa

The gas supply pressure is 140 - 400 kpa

Signal interface M16 × 1.5 or ZG1 / 4

Ambient temperature - 25 ~ + 55

Valve action type gas - closed or gas - open

Attachment positioner, air filter pressure reducer, position maintaining valve, travel switch, valve position transmitter, handwheel mechanism, etc

Sexual energy

Leakage is less than 0.01 % of the rated capacity of the valve, conforming to ANSI B Class 16.104 - 1976

Return belt positioner: less than 1 % of full stroke

Without positioner: less than 3 % of full stroke

Basic error band positioner: less than 1 % of full stroke

Without positioner: less than 5 % of full stroke

Note: When using standard V - shaped PTFE filler

Adjustable range 50: 1

艾思瑞流体控制有限公司

苛刻工况应用的特种材料阀门&部件设备制造商

Severe Service Ceramic sealing valve

地址：成都天府新区天工大道1000号联东u谷6A

网站：www.sszvalve.com

Better Ceramic Better Productivity