

## 902型MT98矿用钢丝缠绕的橡胶软管

产品名称	902型MT98矿用钢丝缠绕的橡胶软管
公司名称	陕西延长石油西北橡胶有限责任公司
价格	.00/个
规格参数	
公司地址	咸阳市秦都区西华路一号院内
联系电话	029-33622642 18149022885

## 产品详情

Specifications:

Two Layers of Wire Braided Reinforcements

Size

I.D

W.D

O.D

W.P

P.P

B.P

B.R

W.T

In

Min

Max

Min

Max

Min

Max

MPa

MPa

MPa

mm

kg/m

1/4-2

5.8

6.5

12.9

13.9

16

17.2

56.0

70.0

140

100

0.48

5/16-2

7.8

8.5

14.9

15.9

18

19.2

48.0

60.0

120

115

0.60

3/8-2

9.8

10.5

16.9

17.9

19.9

21.1

40.0

50.0

100

130

0.68

1/2-2

12.8

13.5

20.7

21.7

23.7

24.9

36.0

45.0

90

180

0.93

5/8-2

15.8

16.6

23.7

24.7

26.5

28.1

32.0

40.0

80

205

1.07

3/4-2

18.8

19.8

26.7

27.7

29.4

31.0

25.0

31.5

63

240

1.08

7/8-2

21.8

22.8

30.7

31.0

32.6

34.0

22.0

27.5

55

280

1.28

1-2

24.8

25.8

33.5

34.5

36.0

37.6

21.0

26.5

52

300

1.52

1-1/4-2

31.6

33.6

40.2

41.2

43.8

46.2

17.0

21.5

42.5

420

1.91-

1-1/2-2

37.7

39.8

46.5

47.5

49.8

52.2

12.0

15.0

30

500

2.10

1-3/4-1

44.6

45.6

53.5

54.5

56.8

59.2

9.0

13.5

22.5

550

2.40

2-2

50.7

52.0

59.5

60.5

62.8

65.2

8.0

12.0

20

630

2.51

2-1/2-1

63.5

65.3

73

75

78

80

7

10.5

21

800

3.30

3-1

75.5

77.5

85

87

90

94

6

9

18

920

3.90

3-3/8-1

84.5

86.7

94

96

99



103

5

7.5

15

1000

4.30

3-1/2-1

88.4

90

98.5

100.5

104

108

5

7.5

15

1100

4.54

4-1

101

104.5

112

116

118

123

4

6

12

1300

5.13

### Three Layers of Wire Braided Reinforcements

Size

I.D

W.D

O.D

W.P

P.P

B.P

B.R

W.T

In

Min

Max

Min

Max

Min

Max

MPa

MPa

MPa

mm

kg/m

5/16-3

7.8

8.5

16.5

17.5

19.6

20.8

50.0

75

125

115

0.79

3/8-3

9.8

10.5

18.5

19.5

21.5

22.7

45.0

62.5

112.5

130

0.90

1/2-3

12.8

13.5

22.5

23.5

25.5

26.7

40.0

56

100

180

1.20

5/8-3

15.8

16.6

25.5

26.5

28.3

29.9

35.0

43.5

87.5

205

1.39

3/4-3

18.8

19.8

28.5

29.5

31.2

32.8

28.0

35

70.5

240

1.54

7/8-3

21.8

22.8

31.5

32.5

34.2

35.8

25.0

31.5

62.5

280

1.66

1-3

24.8

25.8

34.6

35.6

37.2

38.8

24.0

30

60.5

300

1.97

1-1/4-3

31.6

33.6

42.0

43.0

45.8

48.2

19.0

24

47.5

420

2.48

1-1/2-3

37.7

39.8

48.0

49.0

51.8

54.2

15.0

19

37.5

500

2.90