

903型耐高温油钢丝编织橡胶软管

产品名称	903型耐高温油钢丝编织橡胶软管
公司名称	陕西延长石油西北橡胶有限责任公司
价格	.00/个
规格参数	
公司地址	咸阳市秦都区西华路一号院内
联系电话	029-33622642 18149022885

产品详情

Size

I.D

W.D

O.D Cover Thickness

W.P

B.P

B.R

W.T

Fixed Length

In

Min

Max

Min

Max

Max

Min

Max

MPa

MPa

mm

kg/m

m(Iron Core)

m(Rubber Core)

3/16-1

4.6

5.4

9.0

10.0

12.5

0.8

1.5

25.0

100

90

0.22

-

100

1/4-1

6.2

7.0

10.6

11.6

14.1

0.8

1.5

22.5

90.0

100

0.25

-

100

5/16-1

7.7

8.5

12.1

13.3

15.7

0.8

1.5

21.5

85.0

115

0.31

-

100

3/8-1

9.3

10.1

14.5

15.7

18.1

0.8

1.5

18.0

72.0

130

0.36

-

100

1/2-1

12.3

13.5

17.5

19.0

21.4

0.8

1.5

16.0

64.0

180

0.45

-

100

5/8-1

15.5

16.7

20.6

22.2

24.5

0.8

1.5

13.0

52.0

200

0.52

50

100

3/4-R1

18.6

19.8

24.6

26.2

28.5

0.8

1.5

10.5

42.0

240

0.65

50

100

1-1

25.0

26.4

32.5

34.1

36.6

0.8

1.5

8.8

35.0

300

0.91

50

50

1-1/4-1

31.4

33.0

39.3

41.7

44.8

1.0

2.0

6.3

25.0

420

1.30

50

-

1-1/2-1

37.7

39.3

45.6

48.0

52.1

1.3

2.5

5.0

20.0

500

1.70

50

-

2-1

50.4

52

58.7

61.7

65.5

1.3

2.5

4.0

8.0

630

2.00

50

-

Two Layers of Wire Braided Reinforcements

Size

I.D

W.D

O.D Cover Thickness

W.P

B.P

B.R

W.T

Fixed Length

In

Min

Max

Min

Max

Max

Min

Max

MPa

MPa

mm

kg/m

m(Iron Core)

m(Rubber Core)

3/16-2

4.6

5.4

10.6

11.6

14.1

0.8

1.5

41.5

166

90

0.32

-

100

1/4-2

6.1

7.0

12.1

13.3

15.7

0.8

1.5

40.0

160

100

0.36

-

100

5/16-2

7.7

8.5

13.7

14.9

17.3

0.8

1.5

35.0

140

115

0.45

-

100

3/8-2

9.3

10.1

16.1

17.3

19.7

0.8

1.5

33.0

132

130

0.54

-

100

1/2-2

12.3

13.5

19.0

20.6

23.0

0.8

1.5

27.5

110

180

0.65

-

100

5/8-2

15.5

16.7

22.2

23.8

26.2

0.8

1.5

25.0

100

200

0.80

50

100

3/4-2

18.6

19.8

26.2

27.8

30.1

0.8

1.5

21.5

85

240

0.94

50

100

1-2

25.0

26.4

34.1

35.7

38.9

0.8

1.5

16.5

65

300

1.35

50

50

1-1/4-2

31.4

33.0

43.3

45.7

49.5

1.0

2.0

12.5

50

420

2.15

50

-

1-1/2-2

37.7

39.3

49.6

52.0

55.9

1.3

2.5

9.0

36

500

2.65

50

-

2-2

50.4

52.0

62.3

64.7

68.6

1.3

2.5

8.0

32

630

3.42

