

水泥检查井钢模具 做工好 不变形

产品名称	水泥检查井钢模具 做工好 不变形
公司名称	保定市飞皇模具制造有限公司
价格	.00/套
规格参数	飞皇模具:飞皇模具 齐全:齐全 保定:保定
公司地址	保定市北市区东金庄乡后辛庄村村西
联系电话	19933355533

产品详情

环保模具非常受欢迎，大进模具厂，拥有环保设备，环评手续齐全，制造专业的环保水泥检查井模具。

水泥检查井钢模具系列：污水井模具、雨水井模具、检测井模具、电力井模具、集水井模具、沉泥井模具等。

水泥检查井钢模具常用规格：

内径70cm、外径90cm

内径100cm、外径120cm

内径120cm、外径140cm

内径125cm、外径165cm

内径150cm、外径190cm

水泥检查井钢模具由外模、内模、井口模具、井盖模具、底座模具、连接孔组合而成。

水泥检查井钢模具材质：主板4mm、肋筋6mm。

水泥检查井钢模具使用方法：首先将井体钢模具内腔喷一层机油，为了脱模方便，在内外模中间放入钢筋网，然后将搅拌好的混凝土注入模具中，振动棒振捣，等混凝土初期凝固便可拆模，约24小时左右。

Environmental protection mold is very popular, Dajin mold factory, with environmental protection equipment, environmental assessment procedures are complete, manufacturing professional environmental protection cement inspection well mold.

Cement inspection well steel mold series: sewage well mold, rain well mold, detection well mold, electric well mold, catchment well mold, caisson well mold, etc.

Common specifications for steel inspection tools for cement inspection wells:

Inner diameter 70cm, outer diameter 90cm

Inner diameter 100cm, outer diameter 120cm

Inner diameter 120cm, outer diameter 140cm

Inner diameter 125cm, outer diameter 165cm

Inner diameter 150cm, outer diameter 190cm

The steel mould for cement inspection wells is composed of an external mould, an internal mould, a wellhead mould, a well cover mould, a base mould and a connecting hole.

Cement inspection well steel mold material: motherboard 4mm, rib 6mm.

Cement inspection well steel mold use method: first, the well steel mold cavity spray a layer of oil, in order to demould convenience, in the middle of the internal and external mold into the steel mesh, and then mix the concrete into the mold, vibrating rod vibration, and so on concrete initial solidification can demolish the mold, about 24 hours.