印刷电路板PCB大幅面自动激光打码深圳厂家直销PCB激光打码机

产品名称	印刷电路板PCB大幅面自动激光打码深圳厂家直销PCB激光打码机
公司名称	深圳市超越激光智能装备股份有限公司
价格	580000.00/台
规格参数	品牌:Beyond laser Tel:18126260045 型号:CY-PCB-8080
公司地址	中国广东省深圳市龙岗区同乐社区水田一路13号
联系电话	0755-28623985 19878408040

产品详情

印刷电路板PCB大幅面自动激光打码深圳厂家直销PCB激光打码机 公司总部生产基地座落于：广东省深圳市龙岗区龙岗街道中心城爱南路227号东进一号文化创意园D栋。 专注于激光研发和激光设备生产，在激光设备研发和应用领域，一直处于领先地位。 目前公司主要产品包括：全自动在线式PCB激光打码机、大幅面覆盖膜激光切割机、双平台激光切割机、FPC紫外激光切割机、皮秒、飞秒等高精度的激光设备，也为国内外企业提供自动化激光设备定制解决方案。 食品行业、航空航天、军工电子、工艺礼品等行业。 超越激光不仅可以为广大客户提供一整套激光加工解决方案，还建立了完美的质量控制和售后服务体系，以高科技、高质量为标准，为用户提供最优质的、最全面的售前、售中、售后技术支持和维护服务。

Name： PCB large format automated laser coding

machine/model：CY-PCB-8080

equipment size：Size of the host 2020X1900X1770mm；Whole machine size 4000X1900X1770mm

Marking range：100mm*100mm（standard lens）

Marking speed：Line speed can reach 7000mm/s

Positioning accuracy：±0.05mm

Repeated positioning accuracy ：±0.02mm

Applicable PCB Size：尺寸小于800mm*800mm；厚度0.5mm-5mm(可根据要求定制）；Size is less then 800mm*800mm Thickness 0.5mm-5mm (can be customized);

Applicable product：PCB white ink, green ink, blue ink, black ink and other inks; copper;stainless steel; aluminum alloy;(depending on the type of laser)

1D code：Code 39,Code 25, Code 39,Code 128,EAN-13, EAN-8, LSBN,etc,etc

2D code type：Data matrix,QR Code,micro QR Code,PDF417,Code 49,Code 16K,etc.

2D code size：Minimum 2D code size 1.5mm*1.5mm(depends on the laser type)

Character Types：支持True Type 字体（JSF），SHX字体，点阵字体（DMF）；Supports TrueType fonts ,single fonts (JSF),SHX font,bitmap fonts (DMF)

Minimum Character Height：0.1mm-0.4mm（取决于激光器类型）(depending on the laser type)Laser light source：紫外Ultraviolet/绿光Green Ray/CO2/Fiber

Average output：3w/10w/10W/50W

Automatic positioning:支持自动拍照，支持2点、3点，4点定位方式/Supports automatic photo,2,3,4 points localization way

base:高精度花岗岩平台/High precision granite platform

visual system：工业CCD定位和读码系统/Industrial CCD positioning and code reading system

Automatic loading and unloading system：上下料小车和真空吸附系统/Feeding trolley and vacuum adsorption system

Range of dimensions：50*50mm-800*800mm

Processing of thickness：0.05mm-5mm

Code ability：30位/place≧2*2mm

power supply：220V/50Hz/8KVA

Gas supply specifications：0.4-0.6MP

Environmental requirements：温度/Temperature15-30°C、湿度/Humidity＜50%

Automatic Read Code：Read 2D code automatically and save data, alarm if can＇t read

Other Automated System：Automatic loading/unloading machines can be customized,