



-----???? 0.20...170m  
@0...±4° & 0.20...120m@±9° ?????0.20...70m @0...±9° & 0.20...40m@±45°  
?????????? 0.4m????? ±0.10m??? (?? FoV)(?? FoV)?????? -9.0°...+9.0°??,  
-45°...+45°????? 18°@6dB?????? 4.6°@0°??? 9.2°@±0°...13°@±45°??  
????? ?????? 0.1°@±6°...0.2°@±9°???0.6°@0°...2.0°@±45°?????? -400  
km/h...+200km/h(??????-'????????'+)????? ?????? 0.28km/h????? ??? ±0.1  
km/h????min.RCS@x m? 10m@170m ???1m@40m ????? ??50ms?????/-??  
?? 6??=2TX/2RX ?+2TX/1RX\*+2RX?-\*1RX ????????????????? ETSI&FCC 76...  
77GHz????? ??/??EIRP <12.0 dBm @ 77GHz / <35.5 dBm - ?????500MHz?? 1  
2V DC / 10A ???24V DC / 10A ??? 4.5 W / 375 mA ??? ? 12 W / 1.0 A ?????  
? 12V DC / 24V DC +8,0 V ... 32 V DC?????????????/? ???? -40°C...+85°C /  
-40°C...+90°C????? acc. LV124 ?? 2 - v1.3 10000 h ? 10 ?????????????? ?? 20 [(  
m/s) /Hz]@10 Hz / 0,14 [(m/s) /Hz]@1000Hz (peak)?? ?? 500 m/s @6 ms hal  
f-sine (10 x shock each in +/-X/Y/Z dir.)????? ISO 16750 IP 6k 9k (?????????)IP  
6k7(??10cm),????????????????????EN 60068-2-60????????? ??(????????????? 8 ID 1  
x CAN -?? 500 kbit/s?????/? ? W \* L \* H (mm) / (??) 136.25 \* 68.4 \* 33.75 / ??  
172 g?? ??/? ???? PBT GF 30 black (BASF-Ultradur B4300G6 LS sw 15073) /  
AC-47100 (AlSi12Cu1(Fe)) die cast aluminium orEN AW 5754 (3.535) AlMg3  
pressed-formedaluminium????????????????????(??????)?? FMCW ??????????????????  
?????????ARS 404-21 ?????? CAN ????????