

生产加工2W系列水阀，直动式电磁阀，铜阀

产品名称	生产加工2W系列水阀，直动式电磁阀，铜阀
公司名称	奉化市旭帆机械制造有限公司
价格	.00/个
规格参数	品牌:亚德客 型号:2W250-50 材质:黄铜
公司地址	奉化市溪口镇茗山北路K幢
联系电话	86 0574 88861507

产品详情

品牌	亚德客	型号	2W250-50
材质	黄铜	连接形式	螺纹
公称通径	50 (mm)	密封形式	软密封型
压力环境	高压	工作温度	高温
标准	国际	流动方向	双向
形态	柱塞式	零部件及配件	阀体
类型(通道位置)	二位三通	适用介质	水，空气，油
用途	排污		

规格specifications

项目型号item	2wb025-06	2wb025-08	2wb040-10	2wb160-15	2wb200-20	2wb250-25
model	2ws025-06	2ws025-08	2ws050-10	2ws160-15	2ws200-20	2ws250-25
工作介质fluids	空气,水,油,瓦斯					
动作方式action way	直动式					
型式 type	常闭型					
流量孔径 flow aperture	2.5		4	1.2		
cv值 cvvalue	0.23		0.60	0.05		
接管口径 caliber size	1/8	1/4	3/8	1/8	1/4	3/8
使用流体粘滞度the use of fluid viscosity	20cst以下					
使用压力use	空气,水,油,瓦斯			空气,水,油		

pressure		
最大耐压力max.pressure resistance	1.0	3.5
工作温度operating temperature	-5 ~ 80	
使用电压范围applicable pressure range	± 10%	
本体材质bulk material	2w:黄铜 2s:不锈钢	
油封材质oil seal material	nbr,epdm或viton	

订购码ordering code

2w 025 08 — ac110v — e

规格代号 specifications code	2w:二位二通电磁阀直动式 2w:two-positiontwo-way solenoid valve direct drive type 2wh: 二位二通电磁阀直动式(高压型), 2wh:two-positiontwo-way solenoid valve direct drive type (high pressure type) 2s: (不锈钢)二位二通电磁阀直动式, 2s:(stainless steel)two-positiontwo-way solenoid valve direct drive type 2sh: (不锈钢)二位二通电磁阀直动式(高压型)电磁阀 2s:(stainless steel)two-positiontwo-way solenoid valvedirect drive type (high pressure type)
流量孔径circulation aperture	012:1.2mm 020:2mm 025:2.5mm 040:4mm
接管口径takeover caliber	06:1/8 08:1/4 10:3/8
标准电压standard voltage	dc12v, dc24v, ac24v 50/60hz , ac110v 50/60hz, ac220v 50/60hz , ac380v 50/60hz
油封代号oil seal code	空白blank:nbr e:epdm(蒸汽用 with steam) v:viton(高温,瓦斯及真空用 with high temperature,gas and vacuum)