

POM YF-20宝理

| | |
|------|--|
| 产品名称 | POM YF-20宝理 |
| 公司名称 | 东莞市晶宏塑胶原料有限公司 |
| 价格 | .00/KG |
| 规格参数 | 生产厂商:日本宝理 牌号:YF-20 用途级别:电动工具,汽车部件,运动器材 |
| 公司地址 | 东莞市樟木头镇百果洞百顺小区三巷5号一楼 (注册地址) |
| 联系电话 | 076989977070 18200646066 |

产品详情

DURACON YF-20

聚甲醛 (POM) 共聚物

Polyplastics Co., Ltd.

产品说明: High Sliding

Physical property rating unit system test method density 1.52 g/cm ISO 1183 melt flow rate (melt flow rate) (190 degrees C/2.16 kg) 5.0 g/10 min ISO 1133 melt volume flow rate (MVR) (190 degrees C/2.16 kg) 3.90 cm³/10 min ISO 1133 water absorption rate (23 degrees C, 24 hr) 0.50% ISO 62 hardness rating unit system test method Luo Standard Tensile Fracture Strain 14% ISO 527-2 Tensile Modulus 2100 MPa ISO 527-2 Tensile Stress 44.0 MPa ISO 527-2 Tensile Fracture Strain 1950 MPa ISO 178 Bending Stress 62.0 MPa ISO 178 Friction Coefficient JIS K7218 Dynamic 10.32 JIS K7218 With steel and steel-dynamic 20.18 JIS K7218 18 wear factor JIS K7218 0.98 MPa, 0.30 m/sec 3 < 1.0 10⁻⁸ m m /N.m JIS K7218 0.98 MPa, 0.30 m/sec 4 60 10⁻⁸ m m /N.m JIS K7218 8 0.060 MPa, 0.30 m/sec 4 60 10⁻⁸ m m /N.m JIS K7218 0.060 MPa, 0.15 m/sec 5 500 10 10⁻⁸ M m /N. m JIS K7218 0.0 m m JIS K7218 0.0.0 MPa, 0.30 m/sec 3 3 5 5 5 Impact Properties of/N.m JIS K7218 Rating Unit System Test Method for Notch Impact Strength of Simply Supported Beams 3.3 kJ/m ISO 179/1eA Thermal Performance Rating Unit System Test Method for Thermal Deformation Temperature (1.8 MPa, Unannealed) 75.0 degree C ISO 75-2/A Linear Thermal Expansion Coefficient Internal Method Flow: 23-55 degree C 1.2E-4 cm/cm/~C Internal Method Horizontal: 23-55 degree C 1.2E-4 cm/cm/~C Internal Method Electrical Performance Rating Unit System Test Method Surface Resistivity 2.0E+16 ohms IEC 60093 Volume Resistivity 1.0E+14 ohms.cm IEC 60093 Flammability Rating Unit System Test Method UL Flame Retardant Class HB UL 94 Supplementary Information Rating Color Number CF2001 Injection Rating Unit System Dry Drying temperature 80.0 to 90.0 C drying time 3.0 to 4.0 HR processing (melt) temperature 190 to 210 C mould temperature 60.0 to 80.0 C injection pressure 49.0 to 98.0 MPa

screw speed 100 to 150 rpm