

# 煤矿用阻燃控制电缆MKVV Mkvvrp

产品名称	煤矿用阻燃控制电缆MKVV Mkvvrp
公司名称	天津市电缆总厂第一分厂
价格	.00/个
规格参数	
公司地址	河北廊坊大城毕演马工业区
联系电话	0316-5960132 15932637551

## 产品详情

煤矿用阻燃控制电缆矿用控制电缆

Fire retardant control cables in mines

产品用途:本产品适用于矿 井下交流额定电压为450/750V及以下配电装置中的电器仪表作控制信号

Scope of application: This product is suitable under the mine pit exchanges the rated voltage is 450/750V and below distribution equipment electric appliance measuring appliance makes the control Signal protection

执行标准 Standards implemented : Q/3210HL33.1-Q/3210HL33.2-2005

型号、名称及使用范围 Model descriptions and Use scope矿用控制电缆

型号Model名称Descriptions使用范围Scope of applicationMKVV煤矿用聚氯乙烯绝缘聚氯乙烯护套控制电缆PVC insulated PVC sheathed control cables for use in mines矿井中一般控制系统中General control system in minesMKVV22煤矿用聚氯乙烯绝缘钢带铠装聚氯乙烯护套控制电缆PVC insulated steel tape armored PVC sheathed control cables for use in mines矿井中一般控制系统中能承受一定冲击力和压力General control system cables are under some impact and pressure in minesMKVV32煤矿用聚氯乙烯绝缘细钢丝铠装聚氯乙烯护套控制电缆PVC insulated fine steel wire armored PVC sheathed control cables for use in mines矿井中一般控制系统能承受一定拉力General control system cables are under some pulling force in minesMKVV42煤矿用聚氯乙烯绝缘粗钢丝铠装聚氯乙烯护套控制电缆PVC insulated thick steel wire armored PVC sheathed control cables for use in mines矿井中一般控制系统能承受较大拉力General control system cables are under big impact pulling force in mines

mineMKVVP煤矿用聚氯乙烯绝缘铜丝编织屏蔽聚氯乙烯护套控制电缆PVC insulated copper wire weave shielded PVC sheathed control cables for use in mines  
 minesMKVVP2煤矿用聚氯乙烯绝缘铜带屏蔽聚氯乙烯护套控制电缆PVC insulated copper tape shielded PVC sheathed control cables for use in mines  
 minesMKVVR煤矿用聚氯乙烯绝缘聚氯乙烯护套软控制电缆PVC insulated PVC sheathed soft control cables for use in mines  
 minesMKVVRP煤矿用聚氯乙烯绝缘铜丝编织屏蔽聚氯乙烯护套软控制电缆PVC insulated copper wire weave shielded PVC sheathed soft control cables for use in mines  
 Request migration situation and strong electromagnetic interference region as general control in mines

## 使用特性 Service characteristics 矿用控制电缆

电缆导体长期允许的工作温度 Long-term service temperature of the cable conductor 70℃  
 额定电压  $U_0/U$   
 $U_0/U$  450/750V 电缆敷设温度 Cable laying temperature 0℃  
 电缆的最小弯曲半径 Minimum bending radius  
 无铠装层的 电缆外径的6倍，有铠装层或铜带屏蔽的 电缆外径的12倍，Non armored outer diameter of cable 6 times  
 有屏蔽层的软电缆 电缆外径的6倍 Shielded layer soft cable outer diameter of cable 6 times  
 销售订购电话：0316-5960132 ；手机：15932637551 联系人；王妹尊

矿用控制电缆 矿用控制电缆