冷镦机，螺母成型机

产品名称	冷镦机，螺母成型机
公司名称	浙江盛维机械与有限公司
价格	.00/个
规格参数	sucwe:123 10b3s:123 瑞安:123
公司地址	瑞安市潘岱街道前垟工业区（瑞湖路旁）
联系电话	13926285726

产品详情

ZheJiang Shengwei Machine Co,.Ltd.is specialized in producing multi-station cold heading machine/bolt former ,was founded in 2006 ,the total area is 17600 square meters,has dozens of engineers and technicians and they have a long time in this field,we have practial experience,advanced technology ,well-equipped ,and complete product line,those make machines pass rates 100%.The company has passed ISO90001and CE certifications,it is one of the most professional manufacturer of Mult-station cold heading machines in China,and most of the machines exported all over the world.High quality and reasonable price and best after sales service. We look forward to cooperating with you. Our machines can be used to make screws, bolts, non-standard bolts, rivets, rod screws etc.1.Diameter:M4 TO M302.Length:25-380mm3.Machine Model:Three Station, Four station, Five Station.Six Station 3die 3 blow, 4 die 4 blow, 5 die 5 blow, 6 die 6 blow4.Material:Copper, Aluminum, Carbon & Stainless steel, Alloy steel, Titanium alloy.Our machines are mainly exported to Africa, South Asia, South America etc.In the global.Welcome to China and check our website and discuss business with us etc.We really hope we can establish the business relation in long-term.We will provide you the best offer with high-quality machine

SWBFSERIES 3-DIE 3-BLOW BOLT FORMER (M6- M12)SHENG WEISPECIFICATION MODELSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBF10B3S10B3SL13B3S13B3SL13B3SXL17B3S17B3SL17B3SXL17B3SUL19B3S19B3SL19B3SXL19B3SULFORGING STATION3CUT-OFF DIA.MAX.(mm)8101215CUT-OUT LENGTH MAX.(mm)70105941301801051802303501401852404 00KICK-OUT LENGTH MAX.(mm)60907612017590175225325120180225325P.K.O.LENGTH MAX.(mm)132017233020303660263035 60CUT-OFF QUILL(D×L) (mm)28×4628×4635×5638×7938×7940×6640×8040×8040×8046×8046×8060×10065×100MAIN DIE HOLE (D×L(mm)50×6550×10560×8570×13570×18570×9580×18580×24080×33093×13593×19093×24093×350DIES PITCH (mm)608793114PUNCH HOLE (D×L) (mm)40×8040×11045×9045×11145×13050×10250×13050×19050×20060×12060×17060×20060×250RAM STROKE(mm)120150140200250160250360460200270360500FORGING POWER(ton)2830505055707080809090100100PRODUCTSSIZE1/4(m6)5/16(m8)3/8(m10)1/2(m12)MAX.LENGTH(mm)50756510015075150200300100150200300MIN.LENCTG121614203016305010020405010 0(mm)162020254020405010025405010 0MAX.OUTPUT(pcs/minute)300240240210180210175110801701251008 0MAIN MOTOR (HP)10151520302030404040505050APP

ROX.WT.(ton)6.57.591113.512.5172126.520232733SWBFSERIES 3-DIE 3-BLOW BOLT FORMER (M16-M30)SHENG WEISPECIFICATION MODELSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBF24B3S24B3SL24B3SXL24B3SUL30B3S33B3S36B3S41B3S45B3SFORGING STATION3CUT-OFF DIA.MAX.(mm)182326293438CUT-OUT LENGTH MAX.(mm)185270320400270300320400450KICK-OUT LENGTH MAX.(mm)185230280335230260290340390P.K.O.LENGTH MAX.(mm)333650603545606070CUT-OFF QUILL(D×L) (mm)60×10060×12060×12060×12075×12084×13090×140110×140115×140MAIN DIE HOLE (D×L(mm)100×195100×240100×294100×360125×240140×280160×294178×385195×420DIES PITCH (mm)126138156174195210PUNCH HOLE (D×L) (mm)75×16075×20075×23275×23290×19796×210105×232120×250135×280RAM STROKE(mm)280360420500360400440500580FORGING POWER(ton)160160175175220260320450600PRODUCTSSIZE5/8(M16)3/4(M20)7/8(M22)1(M24)1-1/8(M27)1-3/4(M30)MAX.LENGTH(mm)150200250300200225250300355MIN.LENCTGHEX.255060100405060801 00(mm)SOCKET355060100606060801 00MAX.OUTPUT(pcs/minute)120100756590756050 40-45MAIN MOTOR (HP)75751001001001251251501 75APPROX.WT.(ton)3944485457759212416 0SWBFSERIES 4-DIE 4-BLOW BOLT FORMER (M6- M12)SHENG WEISPECIFICATION MODELSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBF10B4S10B4SL13B4S13B4SL13B4SXL13B4SUL17B4S17B4SL17B4SXL17B4SUL19B4S19B4SL19B4SXL19B4SLL19B4SULFORGING STATION4CUT-OFF DIA.MAX.(mm)81215CUT-OUT LENGTH MAX.(mm)70105105130180220135180230350140185240310400KICK-OUT LENGTH MAX.(mm)60909012017521511517522532512018022528 0325P.K.O.LENGTH MAX.(mm)132020233034203036602630356060CUT-OFF QUILL(D×L) (mm)28×4628×4635×5638×7938×7938×7940×6640×8040×8040×8046×8046×8060×10060×10060×100MAIN DIE HOLE (D×L(mm)50×6550×10560×10570×13570×18570×24070×13580×18580×24080×33093×13593×19093×24093×29493×350DIES PITCH (mm)6093114PUNCH HOLE (D×L) (mm)40×8040×11045×11045×11145×13045×17550×11150×13050×19050×20060×12060×17060×20060×23260×250RAM STROKE(mm)120150150200250350180250360460200270360420500FORGING POWER(ton)404065657070858590 90120130PRODUCTSSIZE1/4(m6)3/8(m10)1/2(m12)MAX.LENGTH(mm)507575100150200100150200300100150200250300MIN.LENCTGHEX.121616203040163050100204050501 00(mm)SOCKET162020254040204050100254050501 00MAX.OUTPUT(pcs/minute)300240240200180140200175110801701251009080MAIN MOTOR (HP)15 15203030303040404050505050APPROX.WT.(ton)8101213.515.519.5161924292327323539SWBFSERIES 4-DIE 4-BLOW BOLT FORMER (M16-M30)SHENG WEISPECIFICATION MODELSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBF24B4S24B4SL24B4SXL24B4SUL30B4S30B4SL30B4SUL30B4SULL33B4S36B4S36B4SL36B4SXL41B4S45B4SFORGING STATION4CUT-OFF DIA.MAX.(mm)182326293438CUT-OUT LENGTH MAX.(mm)185270320400270320400445300320370460400450KICK-OUT LENGTH MAX.(mm)185230280335230285335370260290340410340390P.K.O.LENGTH MAX.(mm)333650603560607045606060 70CUT-OFF QUILL(D×L) (mm)60×10060×12060×12060×12075×12084×13090×140110×140115×140MAIN DIE HOLE (D×L(mm)100×195100×240100×294100×360125×240125×294125×360125×420145×280160×294160×370160×450178×385195×420DIES PITCH (mm)126138156174195210PUNCH HOLE (D×L) (mm)75×16075×20075×23275×23290×19090×23290×24090×29096×210105×232105×235106×270120×250135×280RAM STROKE(mm)280360420500360430500580400440500600500580FORGING POWER(ton)200200215215265285300320320380420450520635PRODUCTSSIZE5/8(m16)3/4(m20)7/8(m22)1(m24)1-1/8(M27)1&3/4(m30)MAX.LENGTH(mm)150200250300200250305360225250300380300355MIN.LENCTGHEX.255060100406010010050601001001 00100(mm)SOCKET355060100601001001006060100100100100MAX.OUTPUT(pcs/minute)120100756590656055 80605545-504540-45MAIN MOTOR (HP)75751001001001251251251251251501501 75200APPROX.WT.(ton)4 5515662657687988510812816015 2195SWBFSERIES 5-DIE 5-BLOW BOLT FORMER (M6-M12)SHENG WEISPECIFICATION MODELSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBF10B5S10B5SL13B5S13B5SL13B5SXL17B5S17B5SL17B5SXL19B5S19B5SL19B5SXL19B5SLL19B5SULFORGING STATION5CUT-OFF DIA.MAX.(mm)8101215CUT-OUT LENGTH MAX.(mm)70105105130180135180230140185240310400KICK-OUT LENGTH

MAX.(mm)60909012017511517522512018022528032 5P.K.O.LENGTH MAX.(mm)132020233020303626303560 60CUT-OFF QUILL(D×L) (mm)28×4628×4635×5638×7938×7940×6640×8040×8046×8046×8060×10060×10065×100MAIN DIE HOLE (D×L(mm)50×6550×10560×10570×13570×18570×13580×18580×24093×13593×19093×24093×29493×350DIES PITCH (mm)608793114PUNCH HOLE (D×L) (mm)40×8040×11045×11045×11145×13050×11150×13050×19060×12060×17060×20060×23260×250RAM STROKE(mm)120150150200250180250360200270360420500FORGING POWER(ton)4550808590105105110145160170170175PRODUCTSSIZE1/4(m6)5/16(m8)3/8(m10)1/2(m12)MAX.LENGTH(mm)5075751001501001502001001502002503 00MIN.LENCTGHEX.121616203016305020405050100(mm)SOCKET162020254020405025405050100MAX.OUTPUT(pcs/minute)240200200180160180150100140110908070MAIN MOTOR (HP)1520303040404040505075757 5APPROX.WT.(ton)9.511.5141618.51923282732384145SWBFSERIES 5-DIE 5-BLOW BOLT FORMER (M16-M30)SHENG WEISPECIFICATION MODELSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBF24B5S24B5SL24B5SXL24B5SUL30B5S30B5SL30B5SUL33B5S36B5S36B5SL41B5S45B5SFORGING STATION5CUT-OFF DIA.MAX.(mm)CUT-OUT LENGTH MAX.(mm)182326293438KICK-OUT LENGTH MAX.(mm)185270320400270320400300320370400450P.K.O.LENGTH MAX.(mm)185230280335230285335260290340340390CUT-OFF QUILL(D×L) (mm)33366060356060456060 70MAIN DIE HOLE (D×L(mm)60×10060×12060×12060×12075×12084×13090×14090×140110×140115×140DIES PITCH (mm)100×195100×240100×294100×360125×240125×294125×360145×280160×294160×370178×385195×420PUNCH HOLE (D×L) (mm)126138156174195210RAM STROKE(mm)75×16075×20075×23275×23290×19090×23290×24096×210105×232105×235120×250135×280FORGING POWER(ton)28036042050036043050040044050050058 0PRODUCTSSIZE2302302502503203403603504404806307 00MAX.LENGTH(mm)5/8(m16)3/4(m20)7/8(m22)1(m24)1-1/8(m27)1-1/4(m30)MIN.LENCTGHEX.150200250300200250305225250300300355(mm)SOCKET255060100406010050601001001 00MAX.OUTPUT(pcs/minute)355060100606010060601001001 00MAIN MOTOR (HP)100756560706055605550454 0APPROX.WT.(ton)100100100100125125125125150150200200APPROX.WT.(ton)52586369738597100126146180225SWBFSERIES 6-DIE 6-BLOW BOLT FORMER (M8-M20)SPECIFICATION MODELSWBFSWBFSWBFSWBFSWBFSWBFSWBFSWBFSTBF13B6S13B6SXL17B6S17B6SL19B6S19B6SL19B6SUL24B6S30B6SFORGING STATION6CUT-OFF DIA.MAX.(mm)CUT-OUT LENGTH MAX.(mm)10152330KICK-OUT LENGTH MAX.(mm)105180135180140185240200250P.K.O.LENGTH MAX.(mm)90175115175120180225175220CUT-OFF QUILL(D×L) (mm)203020303030354545MAIN DIE HOLE (D×L(mm)35×5638×7940×6640×8046×8075×10095×120DIES PITCH (mm)60×10570×18570×13580×18593×13593×19093×240108×200125×240PUNCH HOLE (D×L) (mm)87114126138RAM STROKE(mm)45×11045×13050×11150×13060×12060×17060×20075×18090×220FORGING POWER(ton)150250180250200270360280360PRODUCTSSIZE95110120120140140150260400MAX.LENGTH(mm)5/16(m8)1/2(m12)5/8(m16)3/4(m20)MIN.LENCTGHEX.75150100150100150200155200(mm)SOCKET163016302040501502 00MAX.OUTPUT(pcs/minute)204020402540502540MAIN MOTOR (HP)150130130130110100909065APPROX.WT.(ton)304040405050751001 25APPROX.WT.(ton)1622.522262935426585